


**1A SURFACE MOUNT SUPER FAST RECOVERY RECTIFIERS**

**FEATURES**

- FOR SURFACE MOUNTED APPLICATIONS
- LOW PROFILE PACKAGE
- BUILT-IN STRAIN RELIEF
- EASY PICK AND PLACE
- PLASTIC MATERIAL USED CARRIES UNDERWRITERS  
LABORATORY CLASSIFICATION 94 V-0
- SUPER FAST SWITCHING
- GLASS PASSIVATED CHIP JUNCTION
- HIGH TEMPERATURE SOLDERING : 250°C/10 SECONDS AT  
TERMINALS

**MECHANICAL DATA**

- CASE : MOLDED PLASTIC
- TERMINALS : SOLDER PLATED
- POLARITY : INDICATED BY CATHODE BAND
- WEIGHT : 0.064 GRAMS



CASE : DO-214AC (SMA)  
DIMENSIONS IN INCHES AND (MILLIMETERS)

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**  
RATINGS AT 25°C AMBIENT TEMPERATURE UNLESS OTHERWISE SPECIFIED  
SINGLE PHASE, HALF WAVE, 60 HZ, RESISTIVE OR INDUCTIVE LOAD.  
FOR CAPACITIVE LOAD, DERATE CURRENT BY 20%

RATINGS	SYMBOL	SFS1A	SFS1B	SFS1D	SFS1E	SFS1G	SFS1H	SFS1J	UNITS
MAXIMUM RECURRENT PEAK REVERSE VOLTAGE	$V_{RRM}$	50	100	200	300	400	500	600	V
MAXIMUM RMS VOLTAGE	$V_{RMS}$	35	70	140	210	280	350	420	V
MAXIMUM DC BLOCKING VOLTAGE	$V_{DC}$	50	100	200	300	400	500	600	V
MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT AT $T_L=90^\circ\text{C}$	$I_o$	1.0							A
MAXIMUM OVERLOAD SURGE 8.3ms SINGLE HALF SINE-WAVE	$I_{FSM}$	30							A
TYPICAL JUNCTION CAPACITANCE (NOTE 1)	$C_j$	15			10			PF	
TYPICAL THERMAL RESISTANCE (NOTE 2)	$\theta_{JL}$	30							°C/W
STORAGE TEMPERATURE RANGE	$T_{STG}$	-55 TO + 150							°C
OPERATING TEMPERATURE RANGE	$T_{OP}$	-55 TO + 125							°C


**ELECTRICAL CHARACTERISTICS (At  $T_A=25^\circ\text{C}$  UNLESS OTHERWISE NOTED)**

CHARACTERISTICS	SYMBOL	SFS1A	SFS1B	SFS1D	SFS1E	SFS1G	SFS1H	SFS1J	UNITS
MAXIMUM FORWARD VOLTAGE AT 1.0A AND 25°C	$V_F$	0.95			1.25		1.85		V
MAXIMUM REVERSE CURRENT AT 25°C	$I_R$	10							µA
MAXIMUM REVERSE RECOVERY TIME (NOTE 3)	$T_{RR}$	35							nS
MARKING		SF1A	SF1B	SF1D	SF1E	SF1G	SF1H	SF1J	


- NOTE : 1. MEASURED AT 1.0 MHZ AND APPLIED REVERSE VOLTAGE OF 4.0 V  
2. THERMAL RESISTANCE FROM JUNCTION TO TERMINAL 5.0mm<sup>2</sup> (.013 mm THICK) LAND AREAS  
3. REVERSE RECOVERY TEST CONDITIONS:  $I_F=0.5A$ ,  $I_R=1.0A$ ,  $I_{RR}=0.25A$

# RATINGS AND CHARACTERISTIC CURVE SFS1A THRU SFS1J


**FIG. 1-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC**




NOTE: 1. RISE TIME = 7ns MAX. INPUT IMPEDANCE = 1 MEGOHM 22PF  
 2. RISE TIME = 10ns MAX. SOURCE IMPEDANCE = 50 OHMS




**FIG. 2-TYPICAL FORWARD CURRENT DERATING CURVE**




**FIG. 3-TYPICAL REVERSE CHARACTERISTICS**



**FIG. 4-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS**



**FIG. 5-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT**



**FIG. 6-TYPICAL JUNCTION CAPACITANCE**

