

DATA SHEET

NEC

MOS FIELD EFFECT TRANSISTOR μ PA2352T1P

DUAL Nch MOSFET

DESCRIPTION

The μ PA2352T1P is a Dual N-channel MOSFET designed for Lithium-Ion battery protection circuit.

Ecologically Flip chip MOSFET for Lithium-Ion battery Protection (EFLIP).

FEATURES

- Monolithic Dual MOSFET
Connecting the Drains on the circuit board is not required because the Drains of the FET1 and the FET2 are internally connected.
- 2.5 V drive available and low on-state resistance
 $R_{SS(on)1} = 43.0 \text{ m}\Omega \text{ MAX. (} V_{GS} = 4.5 \text{ V, } I_S = 2.0 \text{ A)}$
 $R_{SS(on)2} = 45.0 \text{ m}\Omega \text{ MAX. (} V_{GS} = 4.0 \text{ V, } I_S = 2.0 \text{ A)}$
 $R_{SS(on)3} = 55.0 \text{ m}\Omega \text{ MAX. (} V_{GS} = 3.1 \text{ V, } I_S = 2.0 \text{ A)}$
 $R_{SS(on)4} = 67.0 \text{ m}\Omega \text{ MAX. (} V_{GS} = 2.5 \text{ V, } I_S = 2.0 \text{ A)}$
- Built-in G-S protection diode against ESD
- Pb-free bump

ORDERING INFORMATION

PART NUMBER	PACKAGE
μ PA2352T1P-E4-A ^{Note}	4-pin EFLIP-LGA

Note Pb-free (This product does not contain Pb in external electrode and other parts.)

Remark "-E4" indicates the unit orientation (-E4 only).

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C)


Source to Source Voltage (V _{GS} = 0 V)	V _{SSS}	24	V
Gate to Source Voltage (V _{SS} = 0 V)	V _{GSS}	±12	V
Source Current (DC) ^{Note1}	I _{S(DC)}	±4.0	A
Source Current (pulse) ^{Note2}	I _{S(pulse)}	±40	A
Total Power Dissipation (2 units) ^{Note1}	P _T	0.75	W
Channel Temperature	T _{ch}	150	°C
Storage Temperature	T _{stg}	-55 to +150	°C

Notes 1. Mounted on BT resin board of 40.5 mm x 25 mm x 1.5 mm


2. PW ≤ 100 μs, Duty Cycle ≤ 1%

Remark The diode connected between the gate and source of the transistor serves as a protector against ESD. When this device actually used, an additional protection circuit is externally required if a voltage exceeding the rated voltage may be applied to this device.

OUTLINE DRAWING (Unit: mm)



EQUIVALENT CIRCUIT



The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.





Not all products and/or types are available in every country. Please check with an NEC Electronics sales representative for availability and additional information.


ELECTRICAL CHARACTERISTICS (TA = 25°C)

CHARACTERISTICS	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Zero Gate Voltage Source Current	I_{SSS}	$V_{SS} = 24.0\text{ V}, V_{GS} = 0\text{ V}, \text{TEST CIRCUIT 1}$			10	μA
Gate Leakage Current	I_{GSS}	$V_{GS} = \pm 12.0\text{ V}, V_{SS} = 0\text{ V}, \text{TEST CIRCUIT 2}$			±10	μA
Gate Cut-off Voltage	$V_{GS(off)}$	$V_{SS} = 10.0\text{ V}, I_S = 1.0\text{ mA}, \text{TEST CIRCUIT 3}$	0.5	1.0	1.5	V
Forward Transfer Admittance Note	$ y_{fs} $	$V_{SS} = 10.0\text{ V}, I_S = 2.0\text{ A}, \text{TEST CIRCUIT 4}$	2.5			S
Source to Source On-state Resistance Note	$R_{SS(on)1}$	$V_{GS} = 4.5\text{ V}, I_S = 2.0\text{ A}, \text{TEST CIRCUIT 5}$	24.0	35.0	43.0	mΩ
	$R_{SS(on)2}$	$V_{GS} = 4.0\text{ V}, I_S = 2.0\text{ A}, \text{TEST CIRCUIT 5}$	25.0	37.0	45.0	mΩ
	$R_{SS(on)3}$	$V_{GS} = 3.1\text{ V}, I_S = 2.0\text{ A}, \text{TEST CIRCUIT 5}$	31.5	42.0	55.0	mΩ
	$R_{SS(on)4}$	$V_{GS} = 2.5\text{ V}, I_S = 2.0\text{ A}, \text{TEST CIRCUIT 5}$	33.5	50.0	67.0	mΩ
Input Capacitance	C_{iss}	$V_{SS} = 10.0\text{ V}, V_{GS} = 0\text{ V}, f = 1.0\text{ MHz}$		330		pF
Output Capacitance	C_{oss}	TEST CIRCUIT 7		80		pF
Reverse Transfer Capacitance	C_{rss}			55		pF
Turn-on Delay Time	$t_{d(on)}$		$I_S = 4.0\text{ A}, V_{GS} = 4.0\text{ V}, V_{DD} = 20.0\text{ V},$ $R_G = 6.0\text{ }\Omega, \text{TEST CIRCUIT 8}$		22	
Rise Time	t_r			132		ns
Turn-off Delay Time	$t_{d(off)}$			183		ns
Fall Time	t_f			216		ns
Gate to Source Charge	Q_G	$V_{G1S1} = 4.0\text{ V}, I_S = 4.0\text{ A}, V_{DD} = 20.0\text{ V},$ TEST CIRCUIT 9		5.7		nC
Body Diode Forward Voltage Note	$V_{F(S-S)}$	$I_F = 4.0\text{ A}, V_{GS} = 0\text{ V}, \text{TEST CIRCUIT 6}$		1.0		V





Note Pulsed

Both the FET1 and the FET2 are measured. Test circuits are example of measuring the FET1 side.


<p>TEST CIRCUIT 1 I_{SSS}</p> 	<p>TEST CIRCUIT 2 I_{GSS}</p> <p>When FET1 is measured, between GATE and SOURCE of FET2 are shorted.</p> 
<p>TEST CIRCUIT 3 $V_{GS(off)}$</p> <p>When FET1 is measured, between GATE and SOURCE of FET2 are shorted.</p> 	<p>TEST CIRCUIT 4 y_{fs}</p> <p>$\Delta I_S / \Delta V_{GS}$</p> 




TYPICAL CHARACTERISTICS (T_A = 25°C)




SOURCE CURRENT vs. SOURCE TO SOURCE VOLTAGE




FORWARD TRANSFER CHARACTERISTICS




GATE TO SOURCE CUT-OFF VOLTAGE vs. CHANNEL TEMPERATURE




FORWARD TRANSFER ADMITTANCE vs. SOURCE CURRENT




SOURCE TO SOURCE ON-STATE RESISTANCE vs. SOURCE CURRENT




SOURCE TO SOURCE ON-STATE RESISTANCE vs. GATE TO SOURCE VOLTAGE




SOURCE TO SOURCE ON-STATE RESISTANCE vs. CHANNEL TEMPERATURE




CAPACITANCE vs. SOURCE TO SOURCE VOLTAGE




SWITCHING CHARACTERISTICS



DYNAMIC INPUT CHARACTERISTICS




SOURCE TO SOURCE DIODE FORWARD VOLTAGE



< Example of application circuit >

Lithium-Ion battery (1 cell) protection circuit



<Notes for using this device safely>

When you use this device, in order to prevent a customer's hazard and damage, use it with understanding the following contents. If used exceeding recommended conditions, there is a possibility of causing the device and characteristic degradation.

1. This device is very thin device and should be handled with caution for mechanical stress. The distortion applied to the device should become below 2000×10^{-6} . If the distortion exceeds 2000×10^{-6} , the characteristic of a device may be degraded and it may result in failure.
2. Please do not damage the device when you handle it. The use of metallic tweezers has the possibility of giving the wound. Mounting with the nozzle with clean point is recommended.
3. When you mount the device on a substrate, carry out within our recommended soldering conditions of infrared reflow. If mounted exceeding the conditions, the characteristic of a device may be degraded and it may result failure.
4. When you wash the device mounted the board, carry out within our recommended conditions. If washed exceeding the conditions, the characteristic of a device may be degraded and it may result in failure.
5. When you use ultrasonic wave to substrate after the device mounting, prevent from touching a resonance directly. If it touches, the characteristic of a device may be degraded and it may result in failure.
6. When you coat the device after mounted on the board, please consult our company. NEC Electronics recommends the epoxy resin of the semiconductor grade as a coating material.
7. Please refer to Figure 2 as an example of the Mounting Pad. Optimize the land pattern in consideration of density, appearance of solder fillets, common difference, etc in an actual design.
8. The marking side of this device is an internal electrode. Please neither contact with terminals of other parts nor take out the electrode.

Figure 1 Recommended soldering conditions of INFRARED REFLOW

Maximum temperature (Package's surface temperature)	: 260°C or below
Time at maximum temperature	: 10 s or less
Time of temperature higher than 220°C	: 60 s or less
Preheating time at 160 to 180°C	: 60 to 120 s
Maximum number of reflow processes	: 3 times
Maximum chlorine content of rosin flux (Mass percentage)	: 0.2% or less




Figure 2 The example of the Mounting Pad





Figure 3 The unit orientation



- **The information in this document is current as of April, 2009. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC Electronics data sheets or data books, etc., for the most up-to-date specifications of NEC Electronics products. Not all products and/or types are available in every country. Please check with an NEC Electronics sales representative for availability and additional information.**
- No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Electronics. NEC Electronics assumes no responsibility for any errors that may appear in this document.
- NEC Electronics does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC Electronics products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Electronics or others.
- Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of a customer's equipment shall be done under the full responsibility of the customer. NEC Electronics assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
- While NEC Electronics endeavors to enhance the quality, reliability and safety of NEC Electronics products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC Electronics products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment and anti-failure features.
- NEC Electronics products are classified into the following three quality grades: "Standard", "Special" and "Specific".

The "Specific" quality grade applies only to NEC Electronics products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of an NEC Electronics product depend on its quality grade, as indicated below. Customers must check the quality grade of each NEC Electronics product before using it in a particular application.

"Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots.

"Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support).

"Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.

The quality grade of NEC Electronics products is "Standard" unless otherwise expressly specified in NEC Electronics data sheets or data books, etc. If customers wish to use NEC Electronics products in applications not intended by NEC Electronics, they must contact an NEC Electronics sales representative in advance to determine NEC Electronics' willingness to support a given application.

(Note)

- (1) "NEC Electronics" as used in this statement means NEC Electronics Corporation and also includes its majority-owned subsidiaries.
- (2) "NEC Electronics products" means any product developed or manufactured by or for NEC Electronics (as defined above).