

OBSOLETE PRODUCT
 No Recommended Replacement
 or Contact our Technical Support Center at
 1-888-INTERSIL or www.intersil.com/tsc

September 1998

Ultra High Speed Comparator

Features

- Low Propagation Delay (0003/0003L).....2.0/2.1ns
- Low Latch Set Up Time0.8ns
- Low Offset Voltage, Drift Coefficient 1.0mV, 4 μ V/°C
- Wide Common Mode Range +5.2/-2.8V
- Low Power Dissipation 200mW
- Large Differential Input Resistance1M Ω
- Complementary ECL Outputs; 50 Ω Driving Capability
- Resistor Programmable Hysteresis with HFA-0003L
- Pin Compatible with MAX9690/9685 and AD96685
- Available in SOIC

Applications

- Window Detector
- High Speed Peak Detector
- High Speed Threshold Detector
- High Speed Data Acquisition Systems
- Fiber Optic Decision Circuits
- High Speed Phase Detector
- Frequency Counter

Description

The HFA-0003/0003L are monolithic, ultra high speed, voltage comparators. These comparators combine a low input offset voltage (1.0mV) with a low propagation delay (2.0ns) to achieve a large dynamic input range. The low offset voltage also makes these comparators ideally suited for high speed, precision analog-to-digital processing applications. The circuits have differential analog inputs, and provide complementary, ECL compatible (10K and 100K) logic outputs. The outputs are capable of supplying the current required by terminated 50 Ω transmission lines. Both outputs are open emitter structures, requiring external pull-down resistors. The recommended circuit is 50 Ω connected to -2.0V, but any equivalent ECL termination circuit may be used.

The HFA-0003L is a latched version of the HFA-0003. The latch function allows the HFA-0003L to operate in sample-hold or track-hold modes, when synchronous detection is required. The Latch Enable (LE) input can be driven by a standard ECL gate. See the Applications section for more information on this feature.

The HFA-0003L also has an additional feature, user programmable hysteresis. By connecting a resistor from the HYS pin to GND the user can select up to 20mV of input hysteresis. See the Applications section for more information on this feature.


The HFA-0003 is pin compatible with the MAX9690, and SP9680 while providing improved performance. The HFA-0003L is pin compatible with the MAX9685, AD96685, SP9685, HCMP96850, and the VC7695 while providing improved performance.

Part Number Information


PART NUMBER	TEMPERATURE RANGE	PACKAGE
HFA1-0003L-5	0°C to +75°C	16 Lead Ceramic Sidebrazed DIP
HFA1-0003L-9	-40°C to +85°C	16 Lead Ceramic Sidebrazed DIP
HFA2-0003L-5	0°C to +75°C	10 Pin CAN
HFA2-0003L-9	-40°C to +85°C	10 Pin CAN
HFA3-0003-5	0°C to +75°C	8 Lead Plastic DIP
HFA3-0003-9	-40°C to +85°C	8 Lead Plastic DIP
HFA3-0003L-5	0°C to +75°C	16 Lead Plastic DIP
HFA3-0003L-9	-40°C to +85°C	16 Lead Plastic DIP

Pinouts


HFA-0003 (PDIP, CDIP, SOIC)
TOP VIEW



HFA-0003L (PDIP, CDIP, 150 mil SOIC)
TOP VIEW



HFA-0003L (TO-100 CAN)
TOP VIEW



CAUTION: These devices are sensitive to electrostatic discharge; follow proper IC Handling Procedures.
 1-888-INTERSIL or 321-724-7143 | Intersil (and design) is a registered trademark of Intersil Americas Inc.
 Copyright © Intersil Americas Inc. 2002. All Rights Reserved

Specifications HFA-0003, HFA-0003L

Absolute Maximum Ratings (Note 1)

Supply Voltage (GND to V+)	8V
Supply Voltage (GND to V-)	18V
Voltage Between V+ and V- Terminals	20V
Differential Input Voltage	5.5V
Input Voltage	±5V
Differential Ground Voltage (GND1 to GND2)	±1V
Short Duration Output Current (Note 2)	-35mA
Junction Temperature	+175°C
Junction Temperature (Plastic Package)	+150°C
Lead Temperature (Soldering 10 Sec.)	+300°C

Operating Conditions

Operating Temperature Range	HFA-0003/HFA-0003L-9		$-40^{\circ}\text{C} \leq T_A \leq +85^{\circ}\text{C}$
	HFA-0003/HFA-0003L-5		$0^{\circ}\text{C} \leq T_A \leq +75^{\circ}\text{C}$
Storage Temperature Range	$-65^{\circ}\text{C} \leq T_A \leq +150^{\circ}\text{C}$		
Thermal Package Characteristics ($^{\circ}\text{C}/\text{W}$)	θ_{JA}	θ_{JC}	
8 Lead Ceramic Sidebraced DIP	75	13	
8 Lead Plastic DIP	96	34	
8 Lead SOIC	157	43	
16 Lead Ceramic Sidebraced DIP	75	13	
16 Lead Plastic DIP	92	32	
16 Lead SOIC	114	35	
TO-100 Metal CAN	108	32	

CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

Electrical Specifications $V_+ = 5\text{V}$, $V_- = -5.2\text{V}$, $R_L = 50\Omega$ to -2V , Unless Otherwise Specified

PARAMETER	TEMPERATURE	HFA-0003-5/-9			HFA-0003L-5/-9			UNITS
		MIN	TYP	MAX	MIN	TYP	MAX	
INPUT CHARACTERISTICS								
Input Offset Voltage (V_{OS})	+25°C	-	1	3	-	1	3	mV
	Full	-	-	4	-	-	4	mV
Average Offset Voltage Drift (Note 8)	Full	-	-	4	-	-	4	$\mu\text{V}/^{\circ}\text{C}$
Input Bias Current	+25°C	-	5	8	-	5	8	μA
	Full	-	8	13	-	8	13	μA
Input Offset Current	+25°C	-	0.15	0.2	-	0.15	0.2	μA
	Full	-	-	0.3	-	-	0.3	μA
Common Mode Range	Full	-2.8	-	+5.2	-2.8	-	+5.2	V
Differential Input Resistance	+25°C	-	1	-	-	1	-	$\text{M}\Omega$
Common Mode Input Resistance	+25°C	-	9.5	-	-	9.5	-	$\text{M}\Omega$
Input Capacitance	+25°C	-	1	-	-	1	-	pF
TRANSFER CHARACTERISTICS								
Large Signal Voltage Gain	+25°C	-	3100	-	-	3100	-	V/V
	Full	-	1200	-	-	1200	-	V/V
Common Mode Rejection Ratio (Note 3)	+25°C	70	75	-	70	75	-	dB
	Full	70	-	-	70	-	-	dB
Tracking Bandwidth (Note 4)	+25°C	-	270	-	-	270	-	MHz
SWITCHING CHARACTERISTICS								
Propagation Delay Input to Output (t_{PD}) (Notes 5, 8, 9)	+25°C	-	2.0	2.4	-	2.1	2.6	ns
	Full	-	-	2.8	-	-	3.0	ns
Maximum Dispersion (Notes 6, 8)	Full	-	-	200	-	-	200	ps
OUTPUT CHARACTERISTICS								
Output Voltage Level:								
Logic Low (V_{OL})	+25°C	-	-1.83	-1.65	-	-1.83	-1.65	V
	Full	-	-1.83	-1.57	-	-1.83	-1.57	V
Logic High (V_{OH})	+25°C	-0.938	-0.85	-	-0.938	-0.85	-	V
	Full	-1.05	-0.96	-	-1.05	-0.96	-	V

Specifications HFA-0003, HFA-0003L

Electrical Specifications $V_+ = 5V$, $V_- = -5.2V$, $R_L = 50\Omega$ to $-2V$, Unless Otherwise Specified (Continued)

PARAMETER	TEMPERATURE	HFA-0003-5/-9			HFA-0003L-5/-9			UNITS
		MIN	TYP	MAX	MIN	TYP	MAX	
Continuous Output Current (Note 2)	Full	-	-	-30	-	-	-30	mA
LATCH CHARACTERISTICS (HFA-0003L ONLY)								
LE Input Voltage Level:								
Logic Low (V_{IL})	Full	-	-	-	-	-	-1.475	V
Logic High (V_{IH})	Full	-	-	-	-1.105	-	-	V
LE Input Current Level:								
Logic Low ($V_{IL} = -1.85V$)	Full	-	-	-	-	0.06	0.5	μA
Logic High ($V_{IH} = -0.81V$)	Full	-	-	-	-	11	20	μA
Propagation Delay from LE to Output (t_{p_DL}) (Notes 5, 8, 9)	+25°C	-	-	-	-	2.2	2.7	ns
	Full	-	-	-	-	2.6	3.1	ns
Minimum Set-Up Time (t_S) (Notes 8, 9)	+25°C	-	-	-	-	0.8	1.2	ns
	Full	-	-	-	-	-	1.5	ns
Minimum Hold Time (t_H) (Notes 8, 9)	Full	-	-	-	-	0.5	1.0	ns
Minimum LE Pulse Width (t_{PW}) (Notes 8, 9)	+25°C	-	-	-	-	0.9	0.95	ns
	Full	-	-	-	-	-	1.1	ns
POWER SUPPLY								
PSRR (Note 7)	+25°C	70	80	-	70	80	-	dB
	Full	65	-	-	65	-	-	dB
I_{CC}	Full	-	11	13	-	11	13	mA
I_{EE}	Full	-	19	22	-	19	22	mA
Power Dissipation	Full	-	-	200	-	-	200	mW

NOTES:

1. Absolute maximum ratings are limiting values, applied individually, beyond which the servicability of the circuit may be impaired. Functional operation under any of these conditions is not necessarily implied. Exposure to absolute maximum rating conditions may affect device reliability.
2. Outputs have no sink current (+I) capability, since they are open emitter NPN transistors.
3. $-2.0V \leq V_{CM} \leq +4.0V$.
4. Tracking Bandwidth (TBW) is defined as the maximum input frequency at which the outputs still switch between V_{OL} and V_{OH} . $V_{IN} = 15mV_{p-p}$ sinewave centered on 0V.
5. $V_{IN} = 100mV$. V_{OD} is the amount of input overdrive.
6. Dispersion is defined as the change in propagation delay for input overdrives between 0.1V and 1.0V.
7. $+4.5V \leq V_+ \leq +5.5V$ or $-6.2V \leq V_- \leq -4.7V$.
8. This parameter is not tested. It is guaranteed by design, and by device characterization.
9. $V_{OD} = 10mV$.

Applications Information

HFA-0003L Latch Functionality

The Latch Enable (LE) pin of the HFA-0003L controls the function of the on chip latch. When the LE input is at an ECL Logic 1, the latch is open (transparent) and the comparator functions normally. When the LE input switches to a Logic 0, the outputs are latched in unambiguous states dependant on the current input state, providing the set-up and hold times are met. If the latch function is not utilized, the LE input must be connected to an ECL Logic 1 (e.g. GND).

HFA-0003L Hysteresis Functionality

To improve performance in systems with slow transition times, and/or high noise levels, the HFA-0003L allows the user to easily set the amount of input hysteresis. The hysteresis level is set by the current flowing into the HYS input; the larger the current the larger the level of hysteresis. This current is provided by connecting a resistor (R_H) between the HYS pin and GND, and it is recommended that the input

Timing Diagram

