



- ① HEADER : MAT'L: THERMOPLASTIC POLYESTER-GLASS FILLED COLOR - BLACK
- ② CONTACT : MAT'L - COPPER NI ALLOY 725 Δ* 428 : FINISH - .000030 MIN. GOLD OVER .000050 MIN. TO .000150 MAX. NICKEL ON CONTACT AREA, AND .000050 TO .000100 SOLDER ON TAIL.

CATALOG PT. NO.	NO. OF POS.	A	B	C REF.
130-D50-Δ	100	4.998	49	4.900
" D49 "	98	4.898	48	4.800
" D48 "	96	4.798	47	4.700
" D47 "	94	4.698	46	4.600
" D46 "	92	4.598	45	4.500
" D45 "	90	4.498	44	4.400
" D44 "	88	4.398	43	4.300
" D43 "	86	4.298	42	4.200
" D42 "	84	4.198	41	4.100
" D41 "	82	4.098	40	4.000
" D40 "	80	3.998	39	3.900
" D39 "	78	3.898	38	3.800
" D38 "	76	3.798	37	3.700
" D37 "	74	3.698	36	3.600
" D36 "	72	3.598	35	3.500
" D35 "	70	3.498	34	3.400
" D34 "	68	3.398	33	3.300
" D33 "	66	3.298	32	3.200
" D32 "	64	3.198	31	3.100
" D31 "	62	3.098	30	3.000
" D30 "	60	2.998	29	2.900
" D29 "	58	2.898	28	2.800
" D28 "	56	2.798	27	2.700
" D27 "	54	2.698	26	2.600
" D26 "	52	2.598	25	2.500
" D25 "	50	2.498	24	2.400
" D24 "	48	2.398	23	2.300
" D23 "	46	2.298	22	2.200
" D22 "	44	2.198	21	2.100
" D21 "	42	2.098	20	2.000
" D20 "	40	1.998	19	1.900
" D19 "	38	1.898	18	1.800
" D18 "	36	1.798	17	1.700
" D17 "	34	1.698	16	1.600
" D16 "	32	1.598	15	1.500
" D15 "	30	1.498	14	1.400
" D14 "	28	1.398	13	1.300
" D13 "	26	1.298	12	1.200
" D12 "	24	1.198	11	1.100
" D11 "	22	1.098	10	1.000
" D10 "	20	.998	9	.900
" D09 "	18	.898	8	.800
" D08 "	16	.798	7	.700
" D07 "	14	.698	6	.600
" D06 "	12	.598	5	.500
130-D05-Δ	10	.498	4	.400

REV.	DATE	DESCRIPTION
1	3-21-86	REVISED TO ADD DONNA
2	7-1-86	REVISED TO ADD A.E.H.
3	9-30-86	REVISED TO ADD DR

TOLERANCES NOT ACCUMULATIVE WITHIN ANY ONE HEADER PATTERN

DRILLED HOLE : .0453 ± .001 DIA.
 PLATING THICKNESS : .001 MIN. COPPER & .0003 MIN. SOLDER PLATE
 FINISHED HOLE : .040 ± .003 DIA.

P.C. BOARD HOLE LAYOUT

130 SERIES

C-PRESS STRIP HEADER OUTLINE

(DUAL .100 X .100 GRID)

SCALE: 4:1

DATE: 10-4-85

WINCHESTER ELECTRONICS

2454G