

This document was generated on 04/15/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0022031062 Status: Active Description: 2.50mm (.098") Pitch Her Circuits Circuits Documents: 3D Model Drawing (PDF) Product Specification PS-3022-003 (PDF)		h Header, Single Row, 11.10mm (437") Mating Pin Length, 6 <u>Product Specification PS-3022-004 (PDF)</u> <u>Product Specification PS-99020-0088 (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>			Î Î Î
				Series	
Agency Certificat	tion			image - Re	eference only
UL		E29179			
Comorol				EU RoHS	China RoHS
General				ELV and RoHS	
Product Family		PCB Headers		Compliant REACH SVHC	
Series		<u>3022</u> Wire to Deerd		Not Reviewed	
Application		Wire-to-Board		Halogen-Free	
Product Name Physical		N/A		Status	
Breakaway		No		Halogen-Free	lan an nead-sat
Circuits (Loaded)		6		Need more informat	
Circuits (maximum)		6		environmental com	bliance?
Color - Resin		Natural (White)		Email productcompliance@molex.com	
Flammability		94V-0		For a multiple part number RoHS Certificate o	
Glow-Wire Compliant		94 V-0 No		Compliance, click here	
Lock to Mating Part		None			-
Material - Metal		Brass		Please visit the Contact Us section for any	
Material - Plating Mating		Tin		non-product compliance questions.	
Material - Plating Tern		Tin			
Material - Resin	ination	Nylon			
Number of Rows		1			
Orientation		Vertical		Search Parts in this Series	
PC Tail Length (in)		0.134 ln		<u>3022</u> Series	
PC Tail Length (mm)		3.40 mm			
PCB Locator		No		Mates With	
PCB Retention		None		5124	
PCB Thickness Recor	nmended (in)	0.062 ln	ļ	<u> </u>	
PCB Thickness Recor		1.60 mm			
Packaging Type		Bag			
Pitch - Mating Interfac	e (in)	0.098 ln			
Pitch - Mating Interface (mm)		2.50 mm			
Plating min: Mating (µin)		200			
Plating min: Mating (µm)		5			
Plating min: Termination (µin)		200			
Plating min: Termination (µm)		5			
Polarized to Mating Part		No			
Polarized to PCB		No			
Shrouded		No			
Stackable		No			
Temperature Range - Operating		-40°C to +105°C			
Termination Interface:	Style	Through Hole			
Electrical					
Current - Maximum ne	or Contact	34			
COLLECT - MAXIMUM DE					

Current - Maximum per Contact Voltage - Maximum 3A 250V Solder Process Data Lead-free Process Capability

Material Info Old Part Number

Reference - Drawing Numbers Product Specification Sales Drawing Wave Capable (TH only)

3022-06B

PS-3022-003, PS-3022-004, PS-99020-0088 SDAE-3022-NB

This document was generated on 04/15/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

