



Recommended P.C.B. Layout
Layout Tolerance = ± 0.05 mm

NOTE:

- MATERIAL,
HOUSING: HIGH TEMP PLASTIC, UL94-V0, BLACK
TERMINAL: COPPER ALLOY, SQ=0.40±0.03MM
- FINISH:
TERMINAL: GOLD AT CONTACT,
G/F OVER 1um(40u")MIN Ni OVER ALL
- SPEC.:
PRODUCT SPEC: GS-12-629
PACKING SPEC: GS-14-1420
- THE HSG. WILL WITHSTAND EXPOSURE TO 260C
PEAK TEMP. FOR 5 SEC. IN A WAVE SOLDER APPLICATION
WITH A PCB.
- PRODUCT NUMBERING:
20021111 - 0 0 0 XX X X LF

- LEAD FREE
- PLATING:
1: GOLD FLASH ALL OVER
4: 0.25um(10U")GOLD AT CONTACT
8: 0.76um(30U")GOLD AT CONTACT
- PACKING
T: TUBE
- PIN COUNT
06,08,10,...., 98,A0
(6 -100 EVERY EVEN PIN)

mat'l. code				tolerances unless otherwise specified		CUSTOMER COPY		FCJ	
ltr	ecn no	dr	date	linear	.X ± 0.38	projection	www.fciconnect.com		
A	T09-1117	S.LIN	09/15/09		.XX ± 0.25		title		
B	T10-0011	S.LIN	01/22/10		.XXX ± 0.10		1.27X1.27MM BTB,HEADER UNSHROUDED,VERTICAL,TH		
				angles	0° ± 2°		product family		code
				dr	STERLING LIN 09/15/09		585		TWN
				engr	STERLING LIN 09/15/09		size		sheet
				chr	GARY HSIEH 09/15/09		20021111		1 of 1
				appd	JOSEPH HSIA 09/15/09	scale	A4		
sheet index	revision sheet	B	1			scale			

ACAD

PDM: Rev:B

3

STATUS: Released

cage code

Printed: Jan 29, 2010

4

Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriete de c FCI. Droits de reproduction FCI.



All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.