

Technical Data  
Data Sheet 4855, Rev.-

**MURC405-MURC460**  
**Ultrafast Silicon Die**

**Applications:**

- Switching Power Supply • General Purpose • Free-Wheeling Diodes • Polarity Protection Diode

**Features:**

- Glass-Passivated
- Epitaxial Construction.
- Low Reverse Leakage Current
- High Surge Current Capability
- Low Forward Voltage Drop
- Fast Reverse-Recovery Behavior

**Maximum Ratings:**

Characteristics	Symbol	MURC 405	MURC 410	MURC 415	MURC 420	MURC 440	MURC 460	Unit
Peak Repetitive Reverse Voltage	$V_{RRM}$	50	100	150	200	400	600	V
Working Peak Reverse Voltage	$V_{RWM}$							
DC Blocking Voltage	$V_R$							
Average Rectified Forward Current(Square Wave)	$I_{F(AV)}$	4.0 @ $T_A = 80^\circ\text{C}$				4.0 @ $T_A = 40^\circ\text{C}$		A
Non-Repetitive Peak Surge Current (Surge applied at rated load conditions, half wave, single phase, 60Hz)	$I_{FSM}$	125				110		A
Max. Junction Capacitance @ $V_R = 5\text{V}$ , $T_C = 25^\circ\text{C}$ , $f_{SIG} = 1\text{MHz}$ , $V_{SIG} = 50\text{mV}$ (p-p)	$C_T$	100				40		pF
Operating Junction Temperature and Storage Temperature	$T_J, T_{stg}$	-65 to +175						$^\circ\text{C}$

**Electrical Characteristics:**


Characteristics	Symbol	MURC 405	MURC 410	MURC 415	MURC 420	MURC 440	MURC 460	Unit
Max. Instantaneous Forward Voltage (Note1) ( $I_F = 3.0\text{ Amp}$ , $T_J = 150^\circ\text{C}$ ) ( $I_F = 3.0\text{ Amp}$ , $T_J = 25^\circ\text{C}$ ) ( $I_F = 4.0\text{ Amp}$ , $T_J = 25^\circ\text{C}$ )	$V_F$		0.71 0.88 0.89			1.05 1.25 1.28		V
Max. Instantaneous Reverse Current (Note1) (Rated DC Voltage, $T_J = 150^\circ\text{C}$ ) (Rated DC Voltage, $T_J = 25^\circ\text{C}$ )	$I_R$		150 5			250 10		$\mu\text{A}$
Max. Reverse Recovery Time ( $I_F = 1.0\text{ Amp}$ , $di/dt = 50\text{ A}/\mu\text{s}$ ) ( $I_F = 0.5\text{ Amp}$ , $I_R = 1.0\text{ A}$ , $I_{REC}=0.25\text{A}$ )	$t_{rr}$		35 25			75 50		nS
Max. Forward Recovery Time ( $I_F = 1.0\text{ Amp}$ , $di/dt = 100\text{ A}/\mu\text{s}$ , Recover to 1.0 V)	$T_{fr}$		25			50		nS

1. Pulse Test: Pulse Width = 300 $\mu\text{s}$ , Duty Cycle  $\leq 2\%$

- 221 West Industry Court ■ Deer Park, NY 11729-4681 ■ (631) 586-7600 FAX (631) 242-9798 •
- World Wide Web Site - <http://www.sensitron.com> • E-Mail Address - [sales@sensitron.com](mailto:sales@sensitron.com) •

Data Sheet 4855, Rev.-

**Dimensions in inches (mm)**



Top side metalization:  
Al - 25 kÅ minimum or  
Ti/Ni/Ag - 30 kÅ minimum

Bottom side metalization:  
Ti/Ni/Ag - 30 kÅ minimum.  
Bottom side is cathode, top side is anode.

Die type	Area (mil <sup>2</sup> )	Dimension A <sup>(1)</sup> Inch (millimeter)	Dimension B <sup>(1)</sup> Inch (millimeter)	Dimension C <sup>(2)</sup> Inch (millimeter)
Si p-n die	65 x 65	0.065 (1.651)	0.049 (1.254)	0.009 (0.229)

<sup>(1)</sup> Tolerance is ± 0.003" (0.076 mm)


<sup>(2)</sup> Tolerance is ± 0.001" (0.025 mm)

**DISCLAIMER:**


- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.

Data Sheet 4855, Rev.-


**MURC405, MURC410, MURC415, MURC420**




**Figure 1. Typical Forward Voltage**




**Figure 2. Typical Reverse Current**



**Figure 3. Current Derating  
(Mounting Method #3 Per Note 2)**




**Figure 4. Power Dissipation**




**Figure 5. Typical Capacitance**

Data Sheet 4855, Rev.-


**MURC440, MURC460**




**Figure 6. Typical Forward Voltage**




**Figure 7. Typical Reverse Current**



**Figure 8. Current Derating  
(Mounting Method #3 Per Note 2)**



**Figure 9. Power Dissipation**



**Figure 10. Typical Capacitance**