

M6 SERIES
P10TG-XXXXZ2:1 1.5 KV ISOLATED 2 W REGULATED DUAL OUTPUT DIP24
Available Inputs:
12, 24 and 48 VDC Wide Input 2:1
Available Outputs:
(+/-)3.3, 12, 15 and 18 VDC

Other specifications please enquire.

Electrical Specifications

(Typical at + 25° C, nominal input voltage, rated output current unless otherwise specified)

Input Specifications

Voltage range	9 - 18 VDC (12 VDC), 18 - 36 VDC (24 VDC) 36 - 72 VDC (48 VDC)
Filter	Pi Network

Isolation Specifications

Rated voltage	1500 Vdc
Leakage current	1 mA
Resistance	10 ⁹ Ohm
Capacitance	80 pF typ.

Output Specifications

Voltage accuracy	+/- 1 % typ. +/-2% max.
Ripple and noise (at 20 MHz BW)	60 mV p-p, max.
Short circuit protection	Continuous , restart automatic
Line voltage regulation	+/- 0,5 % max.
Load voltage regulation	+/- 0,5 % max.
Temperature coefficient	+/- 0,02 % / °C

General Specifications

Efficiency	70 % to 85 %
Switching frequency	250 KHz, typ.

Environmental Specifications

Operating temperature (ambient)	-40°C to +85°C
Storage temperature	- 55 °C to + 125 °C
Derating	See graph
Humidity	Up to 90 %, non condensing
Cooling	Free air convection


Physical Characteristics

Dimensions	31,75 x 20,32 x 10,16 mm 1,25 x 0,80 x 0,40 inches
Weight	14,5 g
Case material	Non conductive black plastic


Examples of Partnumbers/Modelcode

PART NO.	INPUT VOLTAGE (VDC) Nominal	INPUT CURRENT NO LOAD	INPUT CURRENT FULL LOAD	OUTPUT VOLTAGE (VDC)	OUTPUT CURRENT (max. mA)	EFFICIENCY FULL LOAD (% TYP.)
P10TG-1205Z2:1	9-18	17	225	+/- 5	+/- 200	74
P10TG-1212Z2:1	9-18	17	213	+/- 12	+/- 83	78
P10TG-2405Z2:1	18-36	17	109	+/- 5	+/- 200	76
P10TG-4805Z2:1	36-72	15	56	+/- 5	+/- 200	75
P10TG-4812Z2:1	36-72	15	53	+/- 12	+/- 83	79

Dimensions



Derating Graph and Pinning



Specification can be changed without notice.

Copyright PEAK electronics GmbH

REV:2 / 09.2001