

Electronics

Termination-Insensitive Mixer, 0.5 - 9 GHz

### Features


- Intermodulation Ratio Insensitive to IF Ports Mismatches
- Conversion Loss: 6.5 dB Typical Midband
- Maximum Input Power: 350 mW max. @ 25°C, Derated 3.5 mW/°C
- Low Power: +24 dBm Max.
- MIL-STD-883 Screening Available

### Description

The unique design of the termination insensitive mixer (TIM) enables it to apply high reverse voltage to diodes during their "off" phase, in the LO cycle. This allows for higher power level performance with minimum distortion. In addition the TIM has internal loads that provide a good match and also absorb mixer generated LO frequency terms. Combined, these features give the mixer its insensitivity to external mismatches, plus superior VSWR. Мунсом

MDC-164 V3





Dirensions in 1) dre in mä Unless Offerwise Nared IXXX = (0,010 (XX = ±0,25) XX = (0,02 (X = (0,5) Weight (APPROXI 12 OUNCES = 34 GRAMS

M/A-COM Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. M/A-COM makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does M/A-COM assume any liability whatsoever arising out of the use or application of any product(s) or information. • North America Tel: 800.366.2266 / Fax: 978.366.2266

- Europe Tel: 44.1908.574.200 / Fax: 44.1908.574.300
- Asia/Pacific Tel: 81.44.844.8296 / Fax: 81.44.844.8298

Visit www.macom.com for additional data sheets and product information.

1





# Termination-Insensitive Mixer, 0.5 - 9 GHz

MDC-164 V3

### Electrical Specifications<sup>1</sup>: T<sub>A</sub> = -55°C to +85°C

Parameter	Test Conditions	Frequency	Units	Min	Тур	Мах
Frequency Range	RF, LO Ports IF Port	0.5 - 9 10 - 2000	GHz MHz	_	_	_
Conversion Loss <sup>2</sup>		1 - 7 GHz 0.5 - 1 GHz 7 - 9 GHz	dB dB dB			8.5 10.0 11.0
Isolation	LO to RF	1.5 - 7 GHz 0.5 - 9 GHz	dB dB	17 13	_	_
	LO to IF	1.5 - 7 GHz 0.5 - 9 GHz	dB dB	20 17	_	_
	RF to IF	0.5 - 9 GHz	dB	17	_	_
RF Input	1 dB Compression 1 dB Desensitization	_	dBm dBm	_	+8 +6	_
SSB Noise Figure	Within 1 dB of Conversion Loss Max.	_	-		_	—
3rd Order Input Intercept		2.0 GHz 8.0 GHz	dBm dBm		+15 +17	
3rd Order Intercept Degration	@ IF Termination VSWR 3:1	_	dB	—	1.5	—

1. All specifications apply when operated at +13 dBm available LO power with 50 ohm source and load impedance.

2. For IF frequencies of 10 - 500 MHz and an RF of -10 dBm or lower.

3. Independent of sum frequency match.

This product contains elements protected by United States Patent Number 4,224,572

2

M/A-COM Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. M/A-COM makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does M/A-COM assume any liability whatsoever arising out of the use or application of any product(s) or information.

- Europe Tel: 44.1908.574.200 / Fax: 44.1908.574.300
- Asia/Pacific Tel: 81.44.844.8296 / Fax: 81.44.844.8298


Visit www.macom.com for additional data sheets and product information.




## Termination-Insensitive Mixer, 0.5 - 9 GHz

### **Typical Performance Curves**


#### **Conversion Loss**



### 3rd Order intercept




### IF Port Response




3


M/A-COM Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. M/A-COM makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does M/A-COM assume any liability whatsoever arising out of the use or application of any product(s) or information.

Conversion Loss vs. IF Port Termination <sup>3</sup>



3rd Order Intercept vs. IF Port Termination <sup>3</sup>





Ordering Information

Part Number	Package		
MDC-164 SMA	C-3		

• North America Tel: 800.366.2266 / Fax: 978.366.2266

• Europe Tel: 44.1908.574.200 / Fax: 44.1908.574.300

• Asia/Pacific Tel: 81.44.844.8296 / Fax: 81.44.844.8298

Visit www.macom.com for additional data sheets and product information.

