


0.5A Glass Passivated Bridge Rectifier

Features

- Glass Passivated Die Construction
- Low Forward Voltage Drop
- High Current Capability
- High Surge Current Capability
- Plastic Material – UL Flammability 94V-0
- RoHS Compliant



MBM



Mechanical Data

Case:	MBM, molded plastic
Terminals:	Plated leads solderable per MIL-STD-202, method 208
Polarity:	As marked on case
Mounting Position:	Any
Weight:	0.22 grams

Maximum Ratings And Electrical Characteristics (T_{amb}=25°C)

Symbol	Description	MB1M	MB2M	MB4M	MB6M	MB8M	MB10M	Unit	Conditions
V_{RRM}	Max. Repetitive Peak Reverse Voltage	100	200	400	600	800	1000	V	
V_{RMS}	Max. RMS Voltage	70	140	280	420	560	700	V	
V_{DC}	Max. DC Blocking Voltage	100	200	400	600	800	1000	V	
I_{F(AV)}	Average Rectified Output Current	0.5						A	T _A =40°C, Note 1
		0.8						A	T _A =40°C, Note 2
I_{FSM}	Non-Repetitive Peak Forward Surge Current	30						A	8.3ms single half sine-wave superimposed on rated load (JEDEC Method)
V_F	Forward Voltage per leg	1.0						V	I _F =0.5A

0.5A Glass Passivated Bridge Rectifier

MB1M – MB10M

Symbol	Description	MB1M	MB2M	MB4M	MB6M	MB8M	MB10M	Unit	Conditions
I_R	Max. Reverse DC Current At Rated DC Blocking Voltage per leg	5.0						μA	T _A =25°C
		500						μA	T _A =125°C
I_t²	Rating for Fusing (t<8.3ms)	3.73						A ² s	
C_J	Typical junction capacitance per leg	25						pF	V _R = 4V, f=1MHz
R_{thJA}	Typical Thermal Resistance per leg	85						°C / W	Note 1
R_{thJL}		20							
T_J, T_{STG}	Operating Junction and Storage Temperature Range	-55 to +150						°C	

- Note:** 1. Mounted on glass epoxy PC board with 1.3mm² solder pad.
 2. Mounted on aluminum substrate PC board with 1.3mm² solder pad.

Typical Characteristics Curves

Fig.1- Output Current Derating Curve





Fig.2-Max. Non-repetitive Peak Forward Surge Current Per Leg



0.5A Glass Passivated Bridge Rectifier

MB1M – MB10M

Fig.3-Typical Instantaneous Forward Characteristic Per Leg




Fig.4-Typical Reverse Characteristics Per Leg






Fig.5-Typical Junction Capacitance



0.5A Glass Passivated Bridge Rectifier

MB1M – MB10M

Dimensions in inch (mm)



How to contact us:

MBM

US HEADQUARTERS

28040 WEST HARRISON PARKWAY, VALENCIA, CA 91355-4162

Tel: (800) TAITRON (800) 824-8766 (661) 257-6060

Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415

Email: taitron@taitroncomponents.com

Http://www.taitroncomponents.com

TAITRON COMPONENTS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO C.P.
42970 MEXICO

Tel: +52-55-5560-1519

Fax: +52-55-5560-2190

TAITRON COMPONENTS INCORPORATED REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001 BRAZIL

Tel: +55-11-5574-7949

Fax: +55-11-5572-0052

TAITRON COMPONENTS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

METROBANK PLAZA, 1160 WEST YAN' AN ROAD, SUITE 1503, SHANGHAI, 200052, CHINA

Tel: +86-21-5424-9942

Fax: +86-21-5424-9931

TAITRON
components incorporated

Rev. B/AH 2008-02-16