

### FAST RECOVERY RECTIFIER

VOLTAGE RANGE: 2000 V  
CURRENT: 0.2 A


#### FEATURES

- ◇ Low cost
- ◇ Diffused junction
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with Freon, Alcohol, Isopropanol and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

#### MECHANICAL DATA

- ◇ Case: JEDEC DO-41, molded plastic
- ◇ Terminals: Axial lead, solderable per MIL-STD-202, Method 208
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.012 ounces, 0.34 grams
- ◇ Mounting position: Any

#### DO - 41



#### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		RC2	UNITS
Maximum recurrent peak reverse voltage	$V_{RRM}$	2000	V
Maximum RMS voltage	$V_{RMS}$	1400	V
Maximum DC blocking voltage	$V_{DC}$	2000	V
Maximum average forward rectified current 9.5mm lead length, @ $T_A=75^\circ C$	$I_{F(AV)}$	0.2	A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load @ $T_J=125^\circ C$	$I_{FSM}$	20.0	A
Maximum instantaneous forward voltage @ 0.2 A	$V_F$	2.0	V
Maximum reverse current @ $T_A=25^\circ C$ at rated DC blocking voltage @ $T_A=100^\circ C$	$I_R$	10.0 300.0	$\mu A$
Maximum reverse recovery time (Note1)	$t_{rr}$	1000	ns
Typical junction capacitance (Note2)	$C_J$	15	pF
Typical thermal resistance (Note3)	$R_{\theta JA}$	50	$^\circ C/W$
Operating junction temperature range	$T_J$	-55-----+150	$^\circ C$
Storage temperature range	$T_{STG}$	-55-----+150	$^\circ C$


NOTE: 1. Measured with  $I_F=0.5A$ ,  $I_R=1A$ ,  $I_{rr}=0.25A$ .

2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.


3. Thermal resistance from junction to ambient.

www.galaxycn.com


**FIG.1 – REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM**




NOTES: 1. RISE TIME = 7ns MAX. INPUT IMPEDANCE = 1MΩ, 22pF  
 2. RISE TIME = 10ns MAX. SOURCE IMPEDANCE = 50Ω




**FIG.2 – TYPICAL FORWARD DERATING CURVE**



**FIG.3 – TYPICAL FORWARD CHARACTERISTIC**



**FIG.4- PEAK FORWARD SURGE CURRENT**



**FIG.4- TYPICAL JUNCTION CAPACITANCE**

