



120 VAC Adapter Mounting Plate

System Sensor's MP120K mounting plate is designed to use 120 VAC to power SpectrAlert® Advance horns, strobes, horn/strobes, chimes, and chime/strobes.



The MP120K features an easy plug in design and has been fitted with a power supply that converts the 120VAC to nominal 24V FWR. The mounting plate may be used for indoor or outdoor applications. For indoor applications, complete field wiring and attach the mounting plate to a four inch square back box. Attach the horn, strobe or horn/strobe, chime or chime/strobe to the mounting plate by inserting the product's tabs in the mounting plate's grooves. The device will rotate into position, locking the product's pins into the mounting plate's terminals. The device will temporarily hold in place with a catch until it is secured with a captured mounting screw. For outdoor applications, the MP120K must be installed using the SpectrAlert Advance weatherproof back box and outdoor listed notification appliance.

Features

- Operates at 120VAC
- Indoor / Outdoor use
- Compatible with all two -wire SpectrAlert Advance devices
- Compatible with 4" x 4" x 2 1/8" electrical boxes and System Sensor weatherproof back box
- Plug-in design
- Paint cover provided to protect wiring terminals

Agency Listings



Specifications

Architectural/Engineering Specifications

120 VAC mounting plate model MP120K shall be listed to UL 464 for fire protective signaling systems. The mounting plate shall power a two-wire SpectrAlert® Advance horn, strobe, horn/strobe, chime or chime/strobe from a 120 VAC supply converted to nominal 24V FWR. For indoor applications the mounting plate shall be installed in a 4" x 4" x 2 1/8" junction box, for outdoor applications the mounting plate shall be installed using the proper SpectrAlert Advance outdoor weatherproof back box and outdoor listed notification appliance.

Physical/Operating Specifications

Standard Operating Temperature	-40°F to 151°F (-40°C to 66°C)
Humidity Range	10 to 93% non-condensing (indoor products)
Nominal Voltage	Regulated 120 VAC
Operating Voltage Range	96-132 VAC
Current Draw From AC Line	150 mA max.

Ordering Information

Part No.	Description
MP120K	120 VAC Adapter Mounting Plate

MP120K may be used with any of the following products, at all horn and strobe settings: P2R, P2RH, P2RK, P2RHK, P2W, P2WH, SR, SRH, SRK, SRHK, SW, SWH, PC2R, PC2RH, PC2RK, PC2RHK, PC2W, PC2WH, SCR, SCRH, SCRK, SCRHK, SCW, SCWH, HR, HRK, HW, SR-P, SW-P, SRH-P, SWH-P, P2R-P, P2W-P, P2RH-P, P2WH-P, SCR-P, SCW-P, SCRH-P, SCWH-P, PC2R-P, PC2W-P, PC2RH-P, PC2WH-P, SR-SP, SRH-SP, P2R-SP, P2RH-SP, SCW-SP, SCWH-SP, PC2W-SP, PC2WH-SP, CHR, CHW, CHSR, CHSW.



3825 Ohio Avenue • St. Charles, IL 60174
Phone: 800-SENSOR2 • Fax: 630-377-6495

©2006 System Sensor.
Product specifications subject to change without notice. Visit systemsensor.com for current product information, including the latest version of this data sheet.
A05-0412-000 • 11/06 • #1733