



D4203D

Preliminary

NPN SILICON TRANSISTOR

HIGH VOLTAGE FAST-SWITCHING NPN POWER TRANSISTOR

DESCRIPTION


The UTC **D4203D** is a high voltage fast-switching NPN power transistor. It is characterized by high breakdown voltage, high current capability, high switching speed and high reliability.

The UTC **D4203D** is intended to be used in energy-saving lights, electronic ballasts, high frequency switching power supplies, high frequency power transforms or common power amplifier, etc.

FEATURES

- * High Breakdown Voltage
- * High Current Capability
- * High Switching Speed
- * High Reliability
- * High Resistance to Shock
- * Built-In Diode


INTERNAL SCHEMATIC DIAGRAM



ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen-Free	TO-126	1	2	3	Bulk
D4203DL-T60-K	D4203DG-T60-K		B	C	E	

<div><div>D4203DG-T60-K</div><div><div></div><div></div><div></div></div><div><div>(1)Packing Type</div><div>(2)Package Type</div><div>(3)Halogen Free</div></div></div> <div><div>(1) K: Bulk</div><div>(2) T60: TO-126</div><div>(3) G: Halogen Free</div></div>	
--	--



■ ABSOLUTE MAXIMUM RATINGS ($T_C=25^{\circ}\text{C}$)

PARAMETER	SYMBOL	RATINGS	UNIT
Collector- Base Voltage	V_{CBO}	700	V
Collector-Emitter Voltage ($I_B=0$)	V_{CEO}	400	V
Emitter-Base Voltage	V_{EBO}	9	V
Collector Current (DC)	I_C	2.0	A
Collector Current (pulse)	I_{CP}	4.0	A
Total Power Dissipation	P_C	20	W
Junction Temperature	T_J	150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Pulse Test: Pulse Width = 5.0ms, Duty Cycle < 10%.

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Case	θ_{JC}	6.25	$^{\circ}\text{C/W}$

■ ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Emitter Sustaining Voltage	$V_{CEO(SUS)}$	$I_C=10\text{mA}$, $I_B=0$	400			V
Collector -Base Breakdown Voltage	BV_{CBO}	$I_C=1\text{mA}$, $I_E=0$	700			V
Emitter-Base Breakdown Voltage	BV_{EBO}	$I_E=1\text{mA}$, $I_C=0$	9			V
Collect - Base Cut-off Current	I_{CBO}	$V_{CB}=680\text{V}$, $I_E=0$			100	μA
Collect - Emitter Cut-off Current	I_{CEO}	$V_{CE}=400\text{V}$, $I_B=0$			50	μA
Emitter - Base Cut-off Current	I_{EBO}	$V_{EB}=7\text{V}$, $I_C=0$			10	μA
DC Current Gain	h_{FE1}	$V_{CE}=5\text{V}$, $I_C=5\text{mA}$	6		40	
	h_{FE2}	$V_{CE}=10\text{V}$, $I_C=200\text{mA}$	8		40	
Collector-Emitter Saturation Voltage	$V_{CE(SAT)1}$	$I_C=0.5\text{A}$, $I_B=0.1\text{A}$			0.5	V
	$V_{CE(SAT)2}$	$I_C=1.5\text{A}$, $I_B=0.5\text{A}$			2	V
Base-Emitter Saturation Voltage	$V_{BE(SAT)}$	$I_C=1\text{A}$, $I_B=0.25\text{A}$			1.8	V
Resistive Load	Fall Time	$V_{CC}=24\text{V}$, $I_C=2\text{A}$, $I_{B1}=-I_{B2}=0.4\text{A}$			0.7	μs
	Storage Time				4	μs
Current Gain Bandwidth Product	f_T	$V_{CE}=10\text{V}$, $I_C=0.5\text{A}$	4			MHz

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.