

SEMICONDUCTOR

Green Product

SOD-523 Flat Lead

0

Anode

200mW SOD-523 SURFACE MOUNT Very Small Outline Flat Lead Plastic Package Schottky Barrier Diode

Absolute Maximum Ratings T_A = 25°C unless otherwise noted

Symbol	Parameter	Value	Units				
PD	Power Dissipation	200	mW				
T _{STG}	Storage Temperature Range	-55 to +125	°C				
TJ	Operating Junction Temperature	+125	°C				
V _R	Reverse Voltage	30	V				
I _{F(AV)}	Average Forward Current	200	mA				
I _{FSM}	Peak Forward Surge Current (At 8.3ms single half sine-wave)	1	А				

These ratings are limiting values above which the serviceability of the diode may be impaired.

Specification Features:

- Low Forward Voltage Drop
- Flat Lead SOD-523 Small Outline Plastic Package
- Extremely Small SOD-523 Package
- Surface Device Type Mounting
- RoHS Compliant
- Green EMC
- Matte Tin(Sn) Lead Finish
- Band Indicates Cathode


Electrical Characteristics T_A = 25°C unless otherwise noted

Symbol	Parameter	Test Condition	Limits		Unit
	Falameter		Min	Max	Unit
Bv	Breakdown Voltage	I _R =500μΑ	30		Volts
I _R	Reverse Leakage Current	V _R =10V		1	μA
V _F	Forward Voltage	I _F =200mA		0.6	Volts

DEVICE MARKING CODES:

0


Cathode



ELECTRICAL SYMBOL




Typical Performance Characteristics



VF-Forward Voltage (mV)






Reverse Current vs Reverse VoltageReverse

May 2010, Revision G



SEMICONDUCTOR

Flat Lead SOD-523 Package Outline



May 2010, Revision G



NOTICE

The information presented in this document is for reference only. Tak Cheong reserves the right to make changes without notice for the specification of the products displayed herein.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Tak Cheong Semiconductor Co., Ltd., or anyone on its behalf, assumes no responsibility or liability for any damagers resulting from such improper use of sale.

This publication supersedes & replaces all information reviously supplied. For additional information, please visit our website http://www.takcheong.com, or consult your nearest Tak Cheong's sales office for further assistance.

Number: DB-100 April 14, 2008 / A