

GENERAL DESCRIPTION

The S100-12 is designed for common emitter HF, SSB applications from a 12 volt supply. It may be operated Class A, AB or C. The device has emitter ballasting for ruggedness and reliability.

S100-12
100 WATTS - 12.5 VOLTS
1.5-30 MHz

HF COMMUNICATIONS

ABSOLUTE MAXIMUM RATINGS


Maximum Power Dissipation @ 25 C Case Temperature 250 W

Maximum Voltage and Current

BVces Collector to Emitter Voltage 3.6 V
 BVebo Emitter to Base Voltage 4.0 V
 Ic Collector Current 50 A


Maximum Temperatures

Storage Temperature -65 to +150 °C
 Operating Temperature +200 °C




DIM	Millimeter	TOL	Inches	TOL
L1 : B	A	.13	.975	.005
L2 : E	B	.13	.725	.005
L3 : C	C	5°	45°	5°
	D	.13	.250	.005
	E	3.17 DIA	.125 DIA	.005
	F	.13	.225	.005
	G	12.70 DIA	.500 DIA	.005
	H	REF	.260	REF
	I	.02	.005	.001
	J	.13	.165	.005
	K	.13	.102	.005
	M	.25	1.000	.010

POWER OUTPUT VS POWER INPUT (TYPICAL)



TYPICAL AMPLIFIER LINE UP

Vcc = 12.5 Volts
 Frequency Range = 1.5-30 MHz




S100-12-2


ELECTRICAL CHARACTERISTICS

SYMBOL	CHARACTERISTICS	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
P _{out}	Power Output	f= 1.5 - 30MHz	100			Watts
P _{in}	Power Input	At Rated Power Out, V _c =12.5V			8.5	Watts
P _g	Power Gain		10.7			dB
V _{Vebo}	Voltage - Emitter to Base	I _e = 10mA	3.5			Volts
V _{Vces}	Voltage - Collector to Base	I _c = 100mA	36			Volts
V _{Vceo}	Voltage - Collector to Emitter	I _c = 100mA	16			Volts
IMD	Intermodulation Distortion Level				-30	dBc
VSWR	Load Mismatch Tolerance				30:1	
η _c	Collector Efficiency	At Rated Power Out		65		%
I _{ces}	Collector to Base Cutoff Current	V _{cb} =15V			50	mA
C _{cb}	Capacitance-Collector to Base	V _{cb} =12.5V, f=1MHz		400		pF
h _{FE}	DC-Current Gain	V _{ce} =5V, I _c =1A	10			
θ _{jc}	Thermal Resistance				0.7	°C/W

I_{cq} VS V_{be} (TYPICAL)





DC SAFE OPERATING AREA (TYPICAL)



SPECIFICATIONS MAY BE SUBJECT TO CHANGE WITHOUT NOTICE

118

S100-12-3



SPECIFICATIONS MAY BE SUBJECT TO CHANGE WITHOUT NOTICE

119