

LS4 2150A
LS042150A1FVA000
4-Way Active Splitter (950-2150 MHz)

General Description:

The **LS042150A1FVA000** is a commercial quality 4-way splitter that meets strict level and match specifications achieved through the use of Quintech's proprietary microstrip and SMT technology. It operates over the 950-2150 MHz frequency range and permits signal splitting with zero loss, eliminating the need for external distribution amplifiers. LNB DC power insertion that can be switched on or off via the front panel mounted slide switch (see LNB Power specification below).

Note: All unused RF output ports must have 75 Ω terminations.

Specifications:

Frequency:	950-2150 MHz
Impedance:	75 Ω
P1dB:	+3 dBm
OIP³:	+17.5 dBm
Insertion Loss:	0 ± 2 dB
Frequency Response:	±1 dB
Isolation:	18 dB
Input Return Loss:	14 dB
Output Return Loss:	15 dB
Noise Figure:	9 dB
RF Connectors:	Type F, 75 Ω
Power Requirements:	18-24 V _{DC} , @ 1.0A via 2-pin quick connect barrier strip
LNB Power:	18 V _{DC} , 850 mA max. available for LNB power
Power Consumption:	6 W, plus customer LNB power load
Mechanical:	1 RU (1.75" H x 19" W x 6.5" D)
Weight:	4.5 lbs. gross (boxed), 2.0 lbs. net
Certifications:	CE, NRTL / TUV, FCC Part 15



250 Airport Road • Indiana, PA 15701 • (800) 839-3658 • (724) 349-1412 • Fax: (724) 349-1421

<http://www.quintechelectronics.com/> • info@quintechelectronics.com

© 2009 Quintech Electronics and Communications Inc. All rights reserved. All product designs and specifications are subject to change without notice.
LS042150A1FVA000 Rev J, CO# 13678 (Page 1 of 1)