

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939


Features

- TO-92 Plastic-Encapsulate Transistors
- Capable of 1.0Watts(Tamb=25°C) of Power Dissipation.
- Collector-current 1.5A
- Collector-base Voltage 40V
- Operating and storage junction temperature range: -55°C to +150°C

C


- Marking : SS8050
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1

Symbol	Parameter	Min	Max	Units
OFF CHARA	CTERISTICS			
V _{(BR)CBO}	Collector-Base Breakdown Voltage (t _c =100uAdc, t _e =0)	40		Vdc
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage (l _c =0.1mAdc, l _B =0)	25		Vdc
V _{(BR)EBO}	Emitter-Base Breakdown Voltage (L=100uAdc, I _c =0)	5.0		Vdc
I _{сво}	Collector Cutoff Current (V _{CB} =40Vdc,		0.1	uAdc
I _{CEO}	Collector Cutoff Current (V _{CE} =20Vdc, _b =0)		0.1	uAdc
EBO	Emitter Cutoff Current (V _{EB} =5.0Vdc, <u></u> {=0)		0.1	uAdc
)N CHARAC	TERISTICS			
h _{FE(1)}	DC Current Gain (b=100mAdc, V _{CE} =1.0Vdc)	120	300	
h _{FE(2)}	DC Current Gain (t _c =800mAdc, V _{cc} =1.0Vdc)	40		
V _{CE(sat)}	Collector-Emitter Saturation Voltage (L=800mAdc, L=80mAdc)		0.5	Vdc
V _{BE(sat)}	Base-Emitter Saturation Voltage (t _c =800mAdc, t _b =80mAdc)		1.2	Vdc
V _{EB}	Base- Emitter Voltage (t=1.5Adc)		1.6	Vdc
SMALL-SIG	NAL CHARACTERISTICS			
f _T Transistor Frequency (b=50mAdc, V _{CE} =10Vdc, f=30MHz)		190		MHz
CLASSIFIC/	ATION OF Herm			
Rank	С	D		
Rang	e 120-200	160-300		



SS8050-C

SS8050-D



	INCHES		ММ		
DIM	MIN	MAX	MIN	MAX	NOTE
А	.170	.190	4.33	4.83	
В	.170	.190	4.30	4.83	
С	.550	.590	13.97	14.97	
D	.010	.020	0.36	0.56	
Е	.130	.160	3.30	3.96	
G	.096	.104	2.44	2.64	

www.mccsemi.com



Ordering Information :

Device	Packing		
Part Number-AP	Ammo Packing: 2Kpcs/Ammo Box		
Part Number-BP	Bulk: 100Kpcs/Carton		

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com