

Inductors

Epoxy Conformal Coated, Axial Leaded



STANDARD ELECTRICAL SPECIFICATIONS

IND. (μH)	TOL.	Q MIN.	TEST FREQ. (MHz)	SRF MIN. (MHz)	DCR MAX. (Ohms)	RATED DC CURRENT (mA)
0.10	± 10 %	30	25.2	280	0.085	1400
0.12	± 10 %	30	25.2	280	0.085	1350
0.15	± 10 %	30	25.2	280	0.095	1270
0.18	± 10 %	30	25.2	280	0.12	1200
0.22	± 10 %	40	25.2	280	0.15	1150
0.27	± 10 %	40	25.2	260	0.15	1110
0.33	± 10 %	40	25.2	260	0.15	1110
0.39	± 10 %	40	25.2	220	0.17	1000
0.47	± 10 %	40	25.2	200	0.17	1000
0.56	± 10 %	40	25.2	180	0.17	950
0.68	± 10 %	40	25.2	160	0.18	900
0.82	± 10 %	40	25.2	140	0.18	900
1.0	± 5 %, ± 10 %	40	25.2	135	0.18	815
1.2	± 5 %, ± 10 %	40	7.96	135	0.18	740
1.5	± 5 %, ± 10 %	40	7.96	130	0.20	700
1.8	± 5 %, ± 10 %	40	7.96	125	0.23	655
2.2	± 5 %, ± 10 %	40	7.96	80	0.25	630
2.7	± 5 %, ± 10 %	40	7.96	80	0.28	595
3.3	± 5 %, ± 10 %	40	7.96	70	0.30	575
3.9	± 5 %, ± 10 %	40	7.96	65	0.32	555
4.7	± 5 %, ± 10 %	40	7.96	45	0.35	530
5.6	± 5 %, ± 10 %	40	7.96	40	0.40	500
6.8	± 5 %, ± 10 %	40	7.96	30	0.45	470
8.2	± 5 %, ± 10 %	40	7.96	28	0.56	425
10	± 5 %, ± 10 %	40	7.96	22	0.72	370
12	± 5 %, ± 10 %	40	2.52	20	0.80	350
15	± 5 %, ± 10 %	40	2.52	16	0.88	335
18	± 5 %, ± 10 %	40	2.52	15	1.0	315
22	± 5 %, ± 10 %	40	2.52	13	1.2	285
27	± 5 %, ± 10 %	40	2.52	11	1.35	270
33	± 5 %, ± 10 %	40	2.52	10	1.50	255
39	± 5 %, ± 10 %	40	2.52	9.5	1.70	240
47	± 5 %, ± 10 %	50	2.52	8.5	2.30	205
56	± 5 %, ± 10 %	50	2.52	7.5	2.60	195
68	± 5 %, ± 10 %	50	2.52	6.5	2.90	185
82	± 5 %, ± 10 %	50	2.52	6.0	3.20	175
100	± 5 %, ± 10 %	50	2.52	5.5	3.70	165
120	± 5 %, ± 10 %	60	0.796	5.4	3.80	160
150	± 5 %, ± 10 %	60	0.796	4.75	4.90	150
180	± 5 %, ± 10 %	60	0.796	4.35	5.0	140
220	± 5 %, ± 10 %	60	0.796	4.0	6.50	130
270	± 5 %, ± 10 %	60	0.796	3.7	7.5	120
330	± 5 %, ± 10 %	60	0.796	3.4	9.5	100
390	± 5 %, ± 10 %	60	0.796	2.8	10.5	95
470	± 5 %, ± 10 %	60	0.796	2.56	17.5	90
560	± 5 %, ± 10 %	60	0.796	2.35	18.5	85
680	± 5 %, ± 10 %	60	0.796	2.0	20.0	75
820	± 5 %, ± 10 %	60	0.796	1.60	23.7	65
1000	± 5 %, ± 10 %	50	0.796	1.15	30.0	60

FEATURES

- High performance ferrite core is used in this epoxy conformally coated choke which allows for inductance values to 1000 μH
- Axial lead type, small lightweight design
- Special magnetic core structure contributes to high Q and self-resonant frequencies
- Treated with epoxy resin coating for humidity resistance to ensure long life
- Heat resistant adhesives


RoHS
COMPLIANT

ELECTRICAL SPECIFICATIONS

Inductance Range: 0.1 μH to 1000 μH

Inductance Tolerance: ± 10 % from 0.1 μH to 1000 μH standard, ± 5 % optional

Operating Temperature Range: - 20 °C to + 105 °C

Dielectric Strength: 250 V RMS

MECHANICAL SPECIFICATIONS

Terminal Strength: Pull = 5 pounds, Twist = 360 °C x 3


Protection: Epoxy uniform roll coated

Leads: Tinned copper

ENVIRONMENTAL SPECIFICATIONS

Maximum Temperature Rise: + 20 °C

DIMENSIONS in inches [millimeters]



MODEL	A (Max.)	B (Max.)	C (Max.)	D (Max.)
IRF-24	0.157 [4.0]	0.118 [3.0]	0.394 [10.0]	0.020 [0.5]

DESCRIPTION

IRF-24	6.8 μH	± 10 %	ER	e3
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER INFORMATION

I	R	F	2	4	E	R	6	R	8	K
PRODUCT FAMILY			SIZE		PACKAGE CODE		INDUCTANCE VALUE			TOL.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.