

Micro Commercial Components

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

2SC1623-L6 2SC1623-L7

Features

- High DC Current Gain: h_{FE}=600 Max.(V_{CE}=6.0V, l_C=1.0mA)
- High voltage: V_{CEO}=50V
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1

Maximum Ratings

Symbol	Rating	Rating	Unit
V_{CEO}	Collector-Emitter Voltage	50	V
V_{CBO}	Collector-Base Voltage	60	V
V_{EBO}	Emitter-Base Voltage	5.0	V
Ι _c	Collector Current	100	mA
Pc	Collector power dissipation	200	mW
TJ	Junction Temperature	-55 to +150	°C
T _{STG}	Storage Temperature	-55 to +150	°C

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Тур	Max	Units
OFF CHARACTERISTICS					-
Ісво	Collector Cutoff Current $(V_{CB}=60Vdc, I_E=0)$			0.1	uAdc
I _{EBO}	Emitter Cutoff Current (V _{EB} =5.0Vdc, I _C =0)			0.1	uAdc

ON CHARACTERISTICS


h _F	DC Current Gain*				600	
	(Ե=1.0mAdc, V _{CE} =6.0Vdc)	200		600		
V _{CE(sat)}	Collector Saturation Voltage*					
, ,	(l _c =100mAdc, l _s =10mAdc)		0.15	0.3	Vdc	
$V_{BE(SAT)}$	Base Saturation Voltage*					
	(l _c =100mAdc,l _s =10mAdc)		0.86	1.0	Vdc	
V_{BE}	Base Emitter Voltage*					
	(V _{CE} =6.0Vdc,	0.55	0.62	0.65	Vdc	
(Collector Capacitance					
C_{ob}	(V _{CB} =6.0Vdc, I _E =0, f=1.0MHz)		3.0		pF	
f	Gain Bandwidth product					
f _T	(V _{CE} =6.0Vdc, I _E =10mAdc)		250		MHz	


h: CLASSIFICATION

Marking	L6	L7		
h _{FE}	200-400	400-600		

^{*} Pulse Test PW<350us, duty cycle<2%


NPN Silicon Epitaxial Transistors





DIMENSIONS					
	INCHES		MM		
DIM	MIN	MAX	MIN	MAX	NOTE
Α	.110	.120	2.80	3.04	
В	.083	.098	2.10	2.64	
С	.047	.055	1.20	1.40	
D	.035	.041	.89	1.03	
E	.070	.081	1.78	2.05	
F	.018	.024	.45	.60	
G	.0005	.0039	.013	.100	
Н	.035	.044	.89	1.12	
J	.003	.007	.085	.180	
K	.015	.020	.37	.51	

Suggested Solder Pad Layout





Ordering Information

Device	Packing
(Part Number)-TP	Tape&Reel3Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.