

Solid Tantalum Surface Mount TANTAMOUNT[®], Molded Case, Hi-Rel COTS, Low ESR, Built-In-Fuse


FEATURES

- Terminations: 100 % matte tin, standard, tin/lead available
- Molded case available in three case sizes
- Compatible with "High Volume" automatic pick and place equipment
- High ripple current carrying capability
- Meets EIA 535BAAC case sizes
- Weibull grading and surge current test options per MIL-PRF-55365
- Standard and low ESR options
- Compliant to RoHS Directive 2002/95/EC


RoHS*
COMPLIANT

PERFORMANCE/ELECTRICAL CHARACTERISTICS

Operating Temperature: - 55 °C to + 125 °C
(Above 85 °C voltage derating is required)

Capacitance Range: 0.47 μF to 470 μF

Capacitance Tolerance: ± 10 %, ± 20 %

Voltage Rating: 4 V_{DC} to 50 V_{DC}

ORDERING INFORMATION								
T86	D	107	K	010	E	A	A	S
TYPE	CASE CODE	CAPACITANCE	CAPACITANCE TOLERANCE	DC VOLTAGE RATING AT + 85 °C	TERMINATION/PACKAGING	RELIABILITY LEVEL	SURGE CURRENT	ESR
	See Ratings and Case Codes Table	This is expressed in picofarads. The first two digits are the significant figures. The third is the number of zeros to follow	K = ± 10 % M = ± 20 %	This is expressed in V. To complete the three-digit block, zeros precede the voltage rating. A decimal point is indicated by an "R" (6R3 = 6.3 V)	C = Matte tin/ 7" (178 mm) reel H = Matte tin/ 7" (178 mm), 1/2 reel E = Tin/lead/ 7" (178 mm) reel L = Tin/lead/ 7" (178 mm), 1/2 reel	A = 1.0 % B = 0.1 % S = Hi-Rel standard Z = Non-ER	A = 10 cycles at + 25 °C B = 10 cycles at - 55 °C/+ 85 °C S = 3 cycles at + 25 °C	S = Std. L = Low

DIMENSIONS in inches (millimeters)							
CASE CODE	EIA SIZE	L	W	H	P	Tw	Th (MIN.)
C	6032-28	0.236 ± 0.012 [6.0 ± 0.30]	0.126 ± 0.012 [3.2 ± 0.30]	0.098 ± 0.012 [2.5 ± 0.30]	0.051 ± 0.012 [1.3 ± 0.30]	0.087 ± 0.004 [2.2 ± 0.10]	0.039 [1.0]
D	7343-31	0.287 ± 0.012 [7.3 ± 0.30]	0.170 ± 0.012 [4.3 ± 0.30]	0.110 ± 0.012 [2.8 ± 0.30]	0.051 ± 0.012 [1.3 ± 0.30]	0.095 ± 0.004 [2.4 ± 0.10]	0.039 [1.0]
E	7343-43	0.287 ± 0.012 [7.3 ± 0.30]	0.170 ± 0.012 [4.3 ± 0.30]	0.158 ± 0.012 [4.0 ± 0.30]	0.051 ± 0.012 [1.3 ± 0.30]	0.095 ± 0.004 [2.4 ± 0.10]	0.039 [1.0]

* Pb containing terminations are not RoHS compliant, exemptions may apply

RATINGS AND CASE CODES								
μF	4 V	6.3 V	10 V	16 V	20 V	25 V	35 V	50 V
0.47								C
0.68								C
1.0								C
1.5							C	C
2.2						C	C	C/D
3.3						C	C	C/D
4.7					C	C	C/D	D
6.8				C	C	C	D	D/E
10			C	C	C	C/D	D/E	
15		C	C	C	C/D	D	D/E	
22		C	C	C/D	D	D/E	E	
33		C	C/D	C/D	D/E	E		
47		C/D	C/D	D/E	E			
68	C	C/D	D/E	D	E			
100	C	D/E	D	E				
150	D	D	D/E	E				
220	D	D/E	E					
330	D/E	E						
470	E							

CONSTRUCTION AND MARKING

C, D, E, Cases

Marking: Capacitor marking includes an anode (+) polarity band, capacitance in microfarads and the voltage rating. The Vishay Sprague® trademark is included if space permits. Capacitors rated at 6.3 V are marked 6 V. A manufacturing date code is marked on all capacitors. Capital letter “E” stands for lead (Pb)-free terminations small cap letter “e” stands for SnPb



Solid Tantalum Surface Mount TANTAMOUNT[®],
Molded Case, Hi-Rel COTS, Low ESR, Built-In-Fuse

Vishay Sprague

RATINGS AND PART NUMBER REFERENCE						
CAPACITANCE (μF)	CASE CODE	PART NUMBER	MAX. DC LEAKAGE at + 25 °C (μA)	MAX. DF at + 25 °C 120 Hz (%)	STANDARD (S) MAX. ESR at + 25 °C 100 kHz (Ω)	LOW (L) MAX. ESR at + 25 °C 100 kHz (Ω)
4 V_{DC} AT + 85 °C, 2.7 V_{DC} AT + 125 °C						
68	C	T86C686(1)004(2)(3)(4)(5)	2.7	8	1.40	0.40
100	C	T86C107(1)004(2)(3)(4)(5)	4.0	8	0.80	0.40
150	D	T86D157(1)004(2)(3)(4)(5)	6.0	8	0.60	0.30
220	D	T86D227(1)004(2)(3)(4)(5)	8.8	8	0.60	0.40
330	D	T86D337(1)004(2)(3)(4)(5)	13.2	15	0.60	0.30
330	E	T86E337(1)004(2)(3)(4)(5)	13.2	8	0.50	0.30
470	E	T86E477(1)004(2)(3)(4)(5)	18.8	16	0.50	0.25
6.3 V_{DC} AT + 85 °C, 4 V_{DC} AT + 125 °C						
15	C	T86C156(1)6R3(2)(3)(4)(5)	0.9	6	1.80	0.60
22	C	T86C226(1)6R3(2)(3)(4)(5)	1.1	6	1.80	0.60
33	C	T86C336(1)6R3(2)(3)(4)(5)	1.6	6	1.40	0.60
47	C	T86C476(1)6R3(2)(3)(4)(5)	2.3	6	1.30	0.60
47	D	T86D476(1)6R3(2)(3)(4)(5)	2.3	6	0.90	0.45
68	C	T86C686(1)6R3(2)(3)(4)S	3.3	6	0.80	N/A
68	D	T86D686(1)6R3(2)(3)(4)(5)	3.3	6	0.70	0.35
100	D	T86D107(1)6R3(2)(3)(4)(5)	6.0	8	0.70	0.35
100	E	T86E107(1)6R3(2)(3)(4)(5)	6.0	8	0.70	0.30
150	D	T86D157(1)6R3(2)(3)(4)(5)	9.0	8	0.60	0.30
220	D	T86D227(1)6R3(2)(3)(4)(5)	13.2	8	0.60	0.30
220	E	T86E227(1)6R3(2)(3)(4)(5)	13.2	8	0.50	0.30
330	E	T86E337(1)6R3(2)(3)(4)(5)	19.8	8	0.50	0.30
10 V_{DC} AT + 85 °C, 7 V_{DC} AT + 125 °C						
10	C	T86C106(1)010(2)(3)(4)S	1.0	6	1.80	N/A
15	C	T86C156(1)010(2)(3)(4)(5)	1.5	6	1.80	0.60
22	C	T86C226(1)010(2)(3)(4)(5)	2.2	6	1.40	0.50
33	C	T86C336(1)010(2)(3)(4)(5)	3.3	6	1.30	0.40
33	D	T86D336(1)010(2)(3)(4)(5)	3.3	6	0.90	0.40
47	C	T86C476(1)010(2)(3)(4)S	4.7	6	1.00	N/A
47	D	T86D476(1)010(2)(3)(4)(5)	4.7	6	0.70	0.40
68	D	T86D686(1)010(2)(3)(4)(5)	6.8	6	0.70	0.35
68	E	T86E686(1)010(2)(3)(4)(5)	6.8	6	0.70	0.35
100	D	T86D107(1)010(2)(3)(4)(5)	10.0	8	0.60	0.30
150	D	T86D157(1)010(2)(3)(4)(5)	15.0	8	0.60	0.30
150	E	T86E157(1)010(2)(3)(4)(5)	15.0	8	0.50	0.40
220	E	T86E227(1)010(2)(3)(4)(5)	22.0	8	0.50	0.30
16 V_{DC} AT + 85 °C, 10 V_{DC} AT + 125 °C						
6.8	C	T86C685(1)016(2)(3)(4)(5)	1.1	6	2.00	0.60
10	C	T86C106(1)016(2)(3)(4)(5)	1.6	6	1.80	0.70
15	C	T86C156(1)016(2)(3)(4)S	2.4	6	1.40	N/A
22	C	T86C226(1)016(2)(3)(4)(5)	3.5	6	1.30	0.70
22	D	T86D226(1)016(2)(3)(4)(5)	3.5	6	0.90	0.45
33	C	T86C336(1)016(2)(3)(4)(5)	5.3	6	1.00	0.50
33	D	T86D336(1)016(2)(3)(4)(5)	5.3	6	0.70	0.35
47	D	T86D476(1)016(2)(3)(4)(5)	7.5	6	0.70	0.35
47	E	T86E476(1)016(2)(3)(4)(5)	7.5	6	0.70	0.35
68	D	T86D686(1)016(2)(3)(4)(5)	10.9	6	0.60	0.30
100	E	T86E107(1)016(2)(3)(4)(5)	16.0	8	0.60	0.30
150	E	T86E157(1)016(2)(3)(4)S	24.0	10	0.40	N/A



RATINGS AND PART NUMBER REFERENCE						
CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. DC LEAKAGE at + 25 °C (μ A)	MAX. DF at + 25 °C 120 Hz (%)	STANDARD (S) MAX. ESR at + 25 °C 100 kHz (Ω)	LOW (L) MAX. ESR at + 25 °C 100 kHz (Ω)
20 V_{DC} AT + 85 °C, 13 V_{DC} AT + 125 °C						
4.7	C	T86C475(1)020(2)(3)(4)(5)	0.9	6	2.00	1.00
6.8	C	T86C685(1)020(2)(3)(4)(5)	1.4	6	1.90	0.60
10	C	T86C106(1)020(2)(3)(4)(5)	2.0	6	1.60	0.80
15	C	T86C156(1)020(2)(3)(4)S	3.0	6	1.40	N/A
15	D	T86D156(1)020(2)(3)(4)(5)	3.0	6	0.90	0.45
22	D	T86D226(1)020(2)(3)(4)(5)	4.4	6	0.70	0.35
33	D	T86D336(1)020(2)(3)(4)(5)	6.6	6	0.70	0.40
33	E	T86E336(1)020(2)(3)(4)(5)	6.6	6	0.70	0.40
47	E	T86E476(1)020(2)(3)(4)(5)	9.4	6	0.60	0.30
68	E	T86E686(1)020(2)(3)(4)(5)	13.6	6	0.60	0.30
25 V_{DC} AT + 85 °C, 17 V_{DC} AT + 125 °C						
2.2	C	T86C225(1)025(2)(3)(4)S	0.6	6	2.80	N/A
3.3	C	T86C335(1)025(2)(3)(4)(5)	0.8	6	2.30	2.10
4.7	C	T86C475(1)025(2)(3)(4)(5)	1.2	6	1.90	1.00
6.8	C	T86C685(1)025(2)(3)(4)(5)	1.7	6	1.60	0.60
10	C	T86C106(1)025(2)(3)(4)(5)	2.5	6	1.40	0.60
10	D	T86D106(1)025(2)(3)(4)(5)	2.5	6	1.00	0.50
15	D	T86D156(1)025(2)(3)(4)(5)	3.8	6	0.80	0.40
22	D	T86D226(1)025(2)(3)(4)(5)	5.5	6	0.70	0.35
22	E	T86E226(1)025(2)(3)(4)(5)	5.5	6	0.70	0.35
33	E	T86E336(1)025(2)(3)(4)(5)	8.3	6	0.60	0.30
35 V_{DC} AT + 85 °C, 23 V_{DC} AT + 125 °C						
1.5	C	T86C155(1)035(2)(3)(4)(5)	0.5	6	3.80	2.60
2.2	C	T86C225(1)035(2)(3)(4)S	0.8	6	2.90	N/A
3.3	C	T86C335(1)035(2)(3)(4)S	1.2	6	2.00	N/A
4.7	C	T86C475(1)035(2)(3)(4)S	1.6	6	1.80	N/A
4.7	D	T86D475(1)035(2)(3)(4)(5)	1.6	6	1.20	0.60
6.8	D	T86D685(1)035(2)(3)(4)(5)	2.4	6	1.00	0.50
10	D	T86D106(1)035(2)(3)(4)(5)	3.5	6	0.80	0.50
10	E	T86E106(1)035(2)(3)(4)(5)	3.5	6	0.80	0.50
15	D	T86D156(1)035(2)(3)(4)(5)	5.3	6	0.70	0.50
15	E	T86E156(1)035(2)(3)(4)(5)	5.3	6	0.70	0.50
22	E	T86E226(1)035(2)(3)(4)S	7.7	6	0.60	N/A
50 V_{DC} AT + 85 °C, 33 V_{DC} AT + 125 °C						
0.47	C	T86C474(1)050(2)(3)(4)S	0.5	4	6.70	N/A
0.68	C	T86C684(1)050(2)(3)(4)S	0.5	4	5.90	N/A
1.0	C	T86C105(1)050(2)(3)(4)(5)	0.5	4	4.40	2.70
1.5	C	T86C155(1)050(2)(3)(4)(5)	0.8	6	5.00	3.20
2.2	C	T86C225(1)050(2)(3)(4)S	1.1	6	2.80	N/A
2.2	D	T86D225(1)050(2)(3)(4)(5)	1.1	6	2.10	0.90
3.3	C	T86C335(1)050(2)(3)(4)(5)	1.7	6	2.40	1.60
3.3	D	T86D335(1)050(2)(3)(4)S	1.7	6	2.00	N/A
4.7	D	T86D475(1)050(2)(3)(4)S	2.4	6	1.10	N/A
6.8	D	T86D685(1)050(2)(3)(4)S	3.4	6	0.90	N/A
6.8	E	T86E685(1)050(2)(3)(4)S	3.4	6	0.90	N/A

Notes


- (1) Capacitance tolerance codes: K, M
- (2) Terminations and packaging codes: C, H, E, L
- (3) Reliability level: A, B, S, Z
- (4) Surge current: A, B, S
- (5) ESR: L, S



Solid Tantalum Surface Mount TANTAMOUNT[®],
Molded Case, Hi-Rel COTS, Low ESR, Built-In-Fuse

Vishay Sprague

TYPICAL CURVES AT + 25 °C, IMPEDANCE AND ESR VS. FREQUENCY





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.