

Complementary MOSFET Half-Bridge (N- and P-Channel)


PRODUCT SUMMARY			
	V _{DS} (V)	r _{DS(on)} (Ω)	I _D (A)
N-Channel	20	0.020 at V _{GS} = 4.5 V	9.1
		0.030 at V _{GS} = 2.5 V	7.5
P-Channel	- 20	0.060 at V _{GS} = - 4.5 V	- 5.3
		0.100 at V _{GS} = - 2.5 V	- 4.1

FEATURES


- TrenchFET® Power MOSFET



RoHS*
COMPLIANT



Top View



Ordering Information: Si4500BDY-T1
Si4500BDY-T1-E3 (Lead (Pb)-free)

ABSOLUTE MAXIMUM RATINGS T _A = 25 °C, unless otherwise noted							
Parameter	Symbol	N-Channel		P-Channel		Unit	
		10 sec	Steady State	10 sec	Steady State		
Drain-Source Voltage	V _{DS}	20		- 20		V	
Gate-Source Voltage	V _{GS}	± 12		± 12			
Continuous Drain Current (T _J = 150 °C) ^{a,b}	I _D	T _A = 25 °C	9.1	6.6	- 5.3	- 3.8	A
		T _A = 70 °C	7.3	5.3	- 4.9	- 3.1	
Pulsed Drain Current	I _{DM}	30		- 20		A	
Continuous Source Current (Diode Conduction) ^{a,b}	I _S	2.1	1.1	- 2.1	- 1.1		
Maximum Power Dissipation ^{a,b}	P _D	T _A = 25 °C	2.5	1.3	2.5	1.3	W
		T _A = 70 °C	1.6	0.8	1.6	0.8	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	- 55 to 150				°C	

THERMAL RESISTANCE RATINGS							
Parameter	Symbol	N-Channel		P-Channel		Unit	
		Typ	Max	Typ	Max		
Maximum Junction-to-Ambient ^a	R _{thJA}	t ≤ 10 sec	40	50	41	50	°C/W
		Steady State	75	95	75	95	
Maximum Junction-to-Foot (Drain)	R _{thJF}	20	22	23	26		

Notes:

a. Surface Mounted on FR4 Board.

b. t ≤ 10 sec.

* Pb containing terminations are not RoHS compliant, exemptions may apply.


SPECIFICATIONS $T_J = 25\text{ }^\circ\text{C}$, unless otherwise noted							
Parameter	Symbol	Test Conditions		Min	Typ ^a	Max	Unit
Static							
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\ \mu\text{A}$	N-Ch	0.6		1.5	V
		$V_{DS} = V_{GS}, I_D = -250\ \mu\text{A}$	P-Ch	-0.6		-1.5	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0\ \text{V}, V_{GS} = \pm 12\ \text{V}$	N-Ch			± 100	nA
			P-Ch			± 100	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 20\ \text{V}, V_{GS} = 0\ \text{V}$	N-Ch			1	μA
		$V_{DS} = -20\ \text{V}, V_{GS} = 0\ \text{V}$	P-Ch			-1	
		$V_{DS} = 20\ \text{V}, V_{GS} = 0\ \text{V}, T_J = 55\text{ }^\circ\text{C}$	N-Ch			5	
		$V_{DS} = -20\ \text{V}, V_{GS} = 0\ \text{V}, T_J = 55\text{ }^\circ\text{C}$	P-Ch			-5	
On-State Drain Current ^b	$I_{D(on)}$	$V_{DS} = 5\ \text{V}, V_{GS} = 4.5\ \text{V}$	N-Ch	30			A
		$V_{DS} = -5\ \text{V}, V_{GS} = -4.5\ \text{V}$	P-Ch	-20			
Drain-Source On-State Resistance ^b	$r_{DS(on)}$	$V_{GS} = 4.5\ \text{V}, I_D = 9.1\ \text{A}$	N-Ch		0.016	0.020	Ω
		$V_{GS} = -4.5\ \text{V}, I_D = -5.3\ \text{A}$	P-Ch		0.048	0.060	
		$V_{GS} = 2.5\ \text{V}, I_D = 3.3\ \text{A}$	N-Ch		0.024	0.030	
		$V_{GS} = -2.5\ \text{V}, I_D = -1\ \text{A}$	P-Ch		0.082	0.100	
Forward Transconductance ^b	g_{fs}	$V_{DS} = 15\ \text{V}, I_D = 9.1\ \text{A}$	N-Ch		29		S
		$V_{DS} = -15\ \text{V}, I_D = -5.3\ \text{A}$	P-Ch		11		
Diode Forward Voltage ^b	V_{SD}	$I_S = 2.1\ \text{A}, V_{GS} = 0\ \text{V}$	N-Ch		0.8	1.2	V
		$I_S = -2.1\ \text{A}, V_{GS} = 0\ \text{V}$	P-Ch		-0.8	-1.2	
Dynamic^a							
Total Gate Charge	Q_g	N-Channel $V_{DS} = 10\ \text{V}, V_{GS} = 4.5\ \text{V}, I_D = 9.1\ \text{A}$	N-Ch		11	17	nC
			P-Ch		6.0	9	
Gate-Source Charge	Q_{gs}	N-Channel $V_{DS} = 10\ \text{V}, V_{GS} = 4.5\ \text{V}, I_D = 9.1\ \text{A}$	N-Ch		2.5		nC
			P-Ch		1.3		
Gate-Drain Charge	Q_{gd}	P-Channel $V_{DS} = -10\ \text{V}, V_{GS} = -4.5\ \text{V}, I_D = -5.3\ \text{A}$	N-Ch		3.2		nC
			P-Ch		1.6		
Turn-On Delay Time	$t_{d(on)}$	N-Channel $V_{DD} = 10\ \text{V}, R_L = 10\ \Omega$ $I_D \equiv 1\ \text{A}, V_{GEN} = 10\ \text{V}, R_g = 6\ \Omega$	N-Ch		35	50	ns
Rise Time	t_r		P-Ch		20	30	
			N-Ch		50	80	
Turn-Off Delay Time	$t_{d(off)}$		P-Channel $V_{DD} = -10\ \text{V}, R_L = 10\ \Omega$ $I_D \equiv -1\ \text{A}, V_{GEN} = -4.5\ \text{V}, R_g = 6\ \Omega$	N-Ch		31	
		P-Ch			55	85	
Fall Time	t_f	P-Channel $V_{DD} = -10\ \text{V}, R_L = 10\ \Omega$ $I_D \equiv -1\ \text{A}, V_{GEN} = -4.5\ \text{V}, R_g = 6\ \Omega$	N-Ch		15	30	
			P-Ch		35	60	
Source-Drain Reverse Recovery Time	t_{rr}	$I_F = 2.1\ \text{A}, di/dt = 100\ \text{A}/\mu\text{s}$	N-Ch		30	60	
		$I_F = -2.1\ \text{A}, di/dt = 100\ \text{A}/\mu\text{s}$	P-Ch		25	50	

Notes:


- a. Guaranteed by design, not subject to production testing.
b. Pulse test; pulse width $\leq 300\ \mu\text{s}$, duty cycle $\leq 2\%$.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current



Capacitance








Gate Charge





On-Resistance vs. Junction Temperature

N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted







N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted




P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current



Capacitance








Gate Charge





On-Resistance vs. Junction Temperature

P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted



P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted



Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?72281>.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.