

Low VF Surface Mount Schottky Barrier Rectifiers

Features:

- *Low Surface Mounted Applications
- *Metal-Semiconductor Junction with Guardring
- *Epitaxial Construction
- *Very Low Forward Voltage Drop
- *High Current Capability
- *Plastic Material Has UL Flammability Classification 94V-0
- *For Use in Low Voltage, High Frequency Inverters, Free Wheeling, and Polarity Protection Applications

Mechanical Data

- *Case : Molded Plastic
- *Polarity :Indicated By Cathode Band
- *Weight : 0.002 ounces, 0.064 grams


REVERSE VOLTAGE
40VOLTS
FORWARD CURRENT
3.0 AMPERE



SMA(DO-214AC)

SMA Outline Dimension

unit:mm



SMA		
Dim	Min	Max
A	2.20	2.92
B	4.00	4.60
C	1.27	1.63
D	0.15	0.31
E	4.48	5.59
G	0.10	0.20
H	0.76	1.52
J	1.70	2.62

Maximum Ratings and Electrical Characteristics

Rating 25°C Ambient Temperature Unless Otherwise Specified.
Single Phase Half Wave, 60Hz , Resistive or Inductive Load.
For Capacitive Load, Derate Current by 20%.

Characteristics	Symbol	B340LA	Unit
Maximum Recurrent Peak Reverse Voltage	VRRM	40	V
Maximum RMS Voltage	VRMS	28	V
Maximum DC Blocking Voltage	VDC	40	V
Maximum Average Forward Rectified Current @T _C =100°C	I _{F(AV)}	3.0	A
Peak Forward Surge Current, 8.3 ms Single Half Sine-Wave Superimposed on Rated Load (JEDEC Method)	I _{FSM}	80	A
Maximum Instantaneous At 3.0A DC	VF	0.42	V
Maximum DC Reverse Current @T _j =25°C At Rated DC Blocking Voltage @T _j =100°C	I _R	1.0 80	mA
Typical Junction Capacitance (Note 1)	C _J	250	Pf
Typical Thermal Resistance (Note 2)	R _{θJC}	10	°C/W
Operating Temperature Range	T _J	-55 to+125	°C
Storage Temperature Range	T _{STG}	-55 to+150	°C

NOTES:1.Measured at 1.0MHz applied reverse voltage of 4.0V DC.
2.Thermal Resistance Junction to case.

