


MAU100 Series

1 Watt Ultra Miniature SIP DC/DC Converters

Single and Dual Outputs

Key Features


- Efficiency up to 81%
- Miniature Package
- I/O Isolation 1000VDC
- SMT Technology
- Low Cost
- MTBF > 2,000,000 Hours




MAU100 1W DC/DC's are specially designed to provide the optimum cost/benefit power solution in a miniature SIP package.

The series consists of 33 models with input voltages of 5V, 12V and 24V, and offers standard output voltages of 3.3V, 5V, 9V, 12V, 15V, $\pm 5V$, $\pm 9V$, $\pm 12V$ and $\pm 15V$ for a wide choice.


The MAU100 series is an excellent selection for a variety of applications including distributed power systems, mixed analog/digital subsystems, portable test equipments, local power networks and battery backed systems.



Low Cost




I/O Isolation




Low Profile

Block Diagram

Single Output



Dual Output



Model Selection Guide

Model Number	Input Voltage	Output Voltage	Output Current		Input Current		Load Regulation	Efficiency	
			Max.	Min.	@Max. Load	@No Load			
			VDC	VDC	mA	mA	mA (Typ.)	mA (Typ.)	% (Max.)
MAU101	5 (4.5 ~ 5.5)	3.3	260	5	235		30	10	73
MAU102		5	200	4	281			10	71
MAU103		9	110	2	260			8	76
MAU104		12	84	1.5	258			7	78
MAU105		15	67	1	258			7	78
MAU106		±5	±100	±2	278			10	72
MAU107		±9	±56	±1	262			8	77
MAU108		±12	±42	±0.8	258			7	78
MAU109		±15	±34	±0.7	258			7	79
MAU111	12 (10.8 ~ 13.2)	3.3	260	5	96		12	8	74
MAU112		5	200	4	114			8	73
MAU113		9	110	2	106			5	78
MAU114		12	84	1.5	105			5	80
MAU115		15	67	1	104			5	80
MAU116		±5	±100	±2	113			8	74
MAU117		±9	±56	±1	106			5	79
MAU118		±12	±42	±0.8	104			5	81
MAU119		±15	±34	±0.7	105			5	81
MAU121	24 (21.6 ~ 26.4)	3.3	260	5	49		7	8	73
MAU122		5	200	4	59			8	71
MAU123		9	110	2	54			5	76
MAU124		12	84	1.5	54			5	78
MAU125		15	67	1	53			5	79
MAU126		±5	±100	±2	58			8	72
MAU127		±9	±56	±1	55			5	76
MAU128		±12	±42	±0.8	53			5	79
MAU129		±15	±34	±0.7	53			5	80
MAU151	15 (13.5 ~ 16.5)	5	200	4	93		11	8	72
MAU152		12	84	2	85			5	79
MAU153		15	67	1	85			5	79
MAU154		±5	±100	±2	93			8	72
MAU155		±12	±42	±1	85			5	80
MAU156		±15	±34	±1	85			5	80

Absolute Maximum Ratings

Parameter		Min.	Max.	Unit
Input Surge Voltage (1000 mS)	5VDC Input Models	-0.7	9	VDC
	12VDC Input Models	-0.7	18	VDC
	15VDC Input Models	-0.7	18	VDC
	24VDC Input Models	-0.7	30	VDC
Lead Temperature (1.5mm from case for 10 Sec.)	---	260	°C	
Internal Power Dissipation	---	450	mW	

Exceeding these values can damage the module. These are not continuous operating ratings.

Note :

1. Specifications typical at $T_a=+25^\circ\text{C}$, resistive load, nominal input voltage, rated output current unless otherwise noted.
2. Ripple & Noise measurement bandwidth is 0~20 MHz.
3. These power converters require a minimum output loading to maintain specified regulation.
4. Operation under no-load conditions will not damage these devices; however they may not meet all listed specifications.
5. All DC/DC converters should be externally fused at the front end for protection.
6. Other input and output voltage may be available, please contact factory.
7. Specifications subject to change without notice.

MAU100 Series

Environmental Specifications

Parameter	Conditions	Min.	Typ.	Max.	Unit
Operating Temperature	Ambient	-40	---	+85	°C
Operating Temperature	Case	-25	---	+90	°C
Storage Temperature		-40	---	+125	°C
Humidity		---	---	95	%
Cooling	Free-Air Convection				

Input Specifications

Parameter	Model	Min.	Typ.	Max.	Unit
Input Voltage Range	5V Input Models	4.5	5	5.5	VDC
	12V Input Models	10.8	12	13.2	
	15V Input Models	13.5	15	16.5	
	24V Input Models	21.6	24	26.4	
Reverse Polarity Input Current	All Models	---	---	0.3	A
Input Filter		Internal Capacitor			

Output Specifications

Parameter	Conditions	Min.	Typ.	Max.	Unit
Output Voltage Accuracy		---	±1.0	±3.0	%
Output Voltage Balance	Dual Output Balance Load	---	±0.1	±1.0	%
Line Regulation	For Vin Change 1%	---	±1.2	±1.5	%
Load Regulation	Io=20% to 100%	See Model Selection Guide			%
Ripple & Noise (20MHz)		---	50	75	mVP-P
Ripple & Noise (20MHz)	Over Line, Load & Temp	---	---	150	mVP-P
Ripple & Noise (20MHz)		---	---	5	mVrms
Over Load		120	---	---	%
Temperature Coefficient		---	±0.01	±0.02	%/°C
Output Short Circuit		0.5 Second Max.			

General Specifications

Parameter	Conditions	Min.	Typ.	Max.	Unit
Rated Isolation Voltage	60 Seconds	1000	---	---	VDC
Isolation Test Voltage	Flash Tested for 1 Second	1100	---	---	VDC
Isolation Resistance	500VDC	1000	---	---	MΩ
Isolation Capacitance	100KHz, 1V	---	60	100	pF
Switching Frequency		70	100	120	KHz
MTBF	MIL-HDBK-217F @ 25°C, Ground Benign	2000	---	---	K Hours


Capacitive Load

Models by Vout	3.3V	5V	9V	12V	15V	±5V #	±9V #	±12V #	±15V #	Unit
Maximum Capacitive Load	220	220	220	220	220	100	100	100	100	uF


Note: # For each output .

Input Fuse Selection Guide


5V Input Models	12V Input Models	15V Input Models	24V Input Models
500mA Slow - Blow Type	200mA Slow - Blow Type	150mA Slow - Blow Type	100mA Slow - Blow Type




Efficiency vs Input Voltage (Single Output)




Efficiency vs Input Voltage (Dual Output)




Efficiency vs Output Load (Single Output)



Efficiency vs Output Load (Dual Output)



Derating Curve (3.3V, 5V & ±5V)




Derating Curve (all other output)

MAU100 Series

Test Configurations

Input Reflected-Ripple Current Test Setup



Input reflected-ripple current is measured with a inductor Lin (4.7uH) and Cin (220uF, ESR < 1.0Ω at 100 KHz) to simulate source impedance.



Capacitor Cin, offsets possible battery impedance.

Current ripple is measured at the input terminals of the module, measurement bandwidth is 0–500 KHz.

Peak-to-Peak Output Noise Measurement Test

Use a Cout 0.33uF ceramic capacitor.

Scope measurement should be made by using a BNC socket, measurement bandwidth is 0–20 MHz. Position the load between 50 mm and 75 mm from the DC/DC Converter.



Design & Feature Considerations

Maximum Capacitive Load

The MAU100 series has limitation of maximum connected capacitance at the output.

The power module may be operated in current limiting mode during start-up, affecting the ramp-up and the startup time.

For optimum performance we recommend 100uF maximum capacitive load for dual outputs and 220uF capacitive load for single outputs.

The maximum capacitance can be found in the data.

Input Source Impedance

The power module should be connected to a low ac-impedance input source. Highly inductive source impedances can affect the stability of the power module.



In applications where power is supplied over long lines and output loading is high, it may be necessary to use a capacitor at the input to ensure startup.

Capacitor mounted close to the power module helps ensure stability of the unit, it is commended to use a good quality low Equivalent Series Resistance (ESR < 1.0Ω at 100 KHz) capacitor of a 2.2uF for the 5V input devices, a 1.0uF for the 12V,15V input devices and a 0.47uF for the 24V devices.

Output Ripple Reduction

A good quality low ESR capacitor placed as close as practicable across the load will give the best ripple and noise performance.



To reduce output ripple, it is recommended to use 1.0uF capacitors at the output.




Thermal Considerations

Many conditions affect the thermal performance of the power module, such as orientation, airflow over the module and board spacing. To avoid exceeding the maximum temperature rating of the components inside the power module, the case temperature must be kept below 95°C.

The derating curves are determined from measurements obtained in an experimental apparatus.



Mechanical Data



Tolerance	Millimeters	Inches
	.X±0.25	.XX±0.01
	.XX±0.25	.XXX±0.01
Pin	±0.05	±0.002


Pin Connections

Pin	Single Output	Dual Output
1	+Vin	+Vin
2	-Vin	-Vin
4	-Vout	-Vout
5	No Pin	Common
6	+Vout	+Vout


Connecting Pin Patterns

Top View (2.54 mm / 0.1 inch grids)

Single Output



Dual Output



Physical Characteristics

Case Size	:	19.5×6.1×10.2 mm (5 & 12V Input) : 0.77×0.24×0.4 inches
Case Size	:	19.5×7.1×10.2 mm (24V Input) : 0.77×0.28×0.4 inches
Case Material	:	Non-Conductive Black Plastic

Weight	:	2.2g(5 & 12V Input) 2.6g(24V Input)
---------------	---	--

Units are encapsulated in a low thermal resistance molding compound which has excellent chemical resistance and electrical properties in high humidity environment and over a wide operating temperature range.
The encapsulant and outer shell of the unit have UL94V-0 ratings. The leads are tin plated for better soldering.