

B320B-B360B

Surface Mount Schottky Barrier Rectifiers


REVERSE VOLTAGE: 20 --- 60 V
CURRENT: 3.0 A



DO - 214AA(SMB)

Features

- Plastic package has Underwriters Laborator Flammability Classification 94V-0
- For surface mounted applications
- Low profile package
- Built-in strain relief
- Metal silicon junction, majority carrier conduction
- High surge capability
- High current capability, low forward voltage drop
- Low power loss, high efficiency
- For use in low voltage high frequency inverters, free wheeling and polarity protection applications
- Guardring for overvoltage protection
- High temperature soldering guaranteed: 250°C/10 seconds at terminals



Dimensions in millimeters

Mechanical Data

- Case: JEDEC DO-214AA, molded plastic over passivated chip
- Polarity: Color band denotes cathode end
- Weight: 0.003 ounces, 0.093 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified

		B320B	B330B	B340B	B350B	B360B	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	20	30	40	50	60	V
Maximum RMS voltage	V_{RWS}	14	21	28	35	42	V
Maximum DC blocking voltage	V_{DC}	20	30	40	50	60	V
Maximum average forward rectified current at T_L (SEE FIG.1) (NOTE 2)	$I_{(AV)}$	3.0					A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	100.0					A
Maximum instantaneous forward voltage at 3.0A (NOTE.1)	V_F	0.50			0.70		V
Maximum DC reverse current @ $T_A=25^\circ\text{C}$ at rated DC blocking voltage (NOTE1) @ $T_A=100^\circ\text{C}$	I_R	0.5					mA
		20					
Typical thermal resistance (NOTE2)	R_{JA} R_{JL}	50.0 10.0					°C/W
Operating junction and storage temperature range	T_{STG}	-65 --- +150					°C
Storage temperature range	T_J	-65 --- +150			-65 --- +150		°C

NOTE: 1. Pulse test: 300 μs pulse width, 1% duty cycle
2. P.C.B. mounted with 0.55" X 0.55" (14.0 X 14.0 mm²) copper pad areas

<http://www.luguang.cn>

[mail:lge@luguang.cn](mailto:lge@luguang.cn)

B320B-B360B

Surface Mount Schottky Barrier Rectifiers

Ratings AND Characteristic Curves

FIG.1 – FORWARD DERATING CURVE




FIG.2– PEAK FORWARD SURGE CURRENT




FIG.3 – TYPICAL FORWARD CHARACTERISTICS




FIG.4 – TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE




FIG.6– TYPICAL TRANSIENT THERMAL IMPEDANCE

