

## PLL Product Specification

**Model:** PLL401-1750      **Rev:** B      **Date:** 4/17/2003  
**Customer:** VARI-L COMPANY      **AppNote:** 108  
**Operating Temperature Range:** ( -35 ° to 85 ° C)

Parameter	Min	Typ	Max	Units	X	Remarks
Frequency Range -	1700	1750	1800	MHz	X	
Step Size -		200		kHz	X	
Settling Time - To within 1.0 kHz		4	10	mSec		
Output Power -	-6	-3	0	dBm	X	
Output Phase Noise:						
1 kHz		-70	-64	dBc/Hz		
10 kHz		-93	-87	dBc/Hz	X	
100 kHz		-113	-107	dBc/Hz		
Power Supply -	2.85	3	3.15	Volts		
Supply Current -		18	25	mA	X	
Spurious Product - 200 kHz		-75	-70	dBc	X	
Reference Feedthrough -		-80	-70	dBc		
Harmonic Suppression:						
2nd Harmonic		-10	-8	dBc	X	
3rd Harmonic		-15	-12	dBc	X	
Ref Osc Signal:						
Frequency		10		MHz		
Amplitude	0.4		2	Vp-p		
Phase Noise - 1 kHz		-145		dBc/Hz		
Input Impedance		10		kΩ		
Output Impedance -		50		Ω		

### Package Information

Package Type:	PLL400	Drawing Number:	60080
Dimensions:	0.6 x 0.6 x 0.14 inches	Drawing Revision:	B

### Comments

**X** Indicates parameter to be tested 100% in production

4895 Peoria Street Denver, CO 80239 tel: 303.371.1560 fax: 303.371.0845 sales@vari-l.com	<b>Our Products Include:</b>	PLL Synthesizer Modules	Narrow-Band Voltage Controlled Oscillators	<b>ISO 9001 Certified</b>
		Wide-Band Voltage Controlled Oscillators	Couplers	
Contact the Vari-L Sales Department for custom solutions to your RF and microwave component assembly needs.				
<b>Vari-L Company, Inc.    www.vari-l.com</b>				