


# TaNFilm<sup>®</sup> Precision SIP Network Commercial and MIL Qualified



## 4700 Series

- Inherent reliability
- MIL-PRF-83401 qualified
- Custom configuration available
- Bonded leads not susceptible to solder reflow problems
- Absolute tolerance to  $\pm 0.1\%$  - ratio accuracy to  $\pm 0.01\%$
- Absolute TCR to  $\pm 15\text{ppm}/^\circ\text{C}$  - ratio accuracy to  $\pm 5\text{ppm}/^\circ\text{C}$



The IRC 4700 Series is the ultimate combination of precision performance, reliability, and long term stability in a low profile, TaNFilm<sup>®</sup> SIP package. Rugged welded lead construction combined with the inherent passivation characteristics of tantalum nitride insure superior ongoing performance over the installed life of the part.

Visit our website to view a graphical demonstration of IRC's TaNFilm reliability and performance features.

## Electrical Data

Schematic	Resistance Range ( $\Omega$ )	Absolute Tolerance	Ratio Tolerance	Absolute TCR ( $\text{ppm}/^\circ\text{C}$ )	Tracking TCR ( $\text{ppm}/^\circ\text{C}$ )	Element Power (mW)
<b>C Commercial</b>	49.9 - 99.9	F, G, J	F, G	$\pm 50; \pm 100; \pm 300$	$\pm 20$	120
	100 - 200	B, D, F, G, J	D, F, G	$\pm 25; \pm 50; \pm 100; \pm 300$	$\pm 15$	
	201 - 1.9K	B, D, F, G, J	B, D, F, G	$\pm 25; \pm 50; \pm 100; \pm 300$	$\pm 10$	
	2.0K - 200K	B, D, F, G, J	A, B, D, F, G	$\pm 15; \pm 25; \pm 50; \pm 100; \pm 300$	$\pm 5$	
<b>G Commercial</b>	20 - 49.9	F, G, J	F, G	$\pm 50; \pm 100; \pm 300$	$\pm 20$	200
	50.0 - 199	D, F, G, J	B, D, F, G	$\pm 25; \pm 50; \pm 100; \pm 300$	$\pm 5$	
	200 - 999	B, D, F, G, J	A, B, D, F, G	$\pm 25; \pm 50; \pm 100; \pm 300$	$\pm 5$	
	1.0K - 100K	B, D, F, G, J	T, Q, A, B, D, F, G	$\pm 15; \pm 25; \pm 50; \pm 100; \pm 300$	$\pm 5$	
	101K - 400K	B, D, F, G, J	A, B, D, F, G	$\pm 15; \pm 25; \pm 50; \pm 100; \pm 300$	$\pm 5$	
<b>F Commercial</b>	49.9 - 99.9	F, G, J	F, G	$\pm 50; \pm 100; \pm 300$	$\pm 20$	120
	100 - 199	F, G, J	D, F, G	$\pm 25; \pm 50; \pm 100; \pm 300$	$\pm 10$	
	200 - 999	B, D, F, G, J	B, D, F, G	$\pm 25; \pm 50; \pm 100; \pm 300$	$\pm 5$	
	1.0K - 200K	B, D, F, G, J	A, B, D, F, G	$\pm 15; \pm 25; \pm 50; \pm 100; \pm 300$	$\pm 5$	

Consult factory for tighter tolerances and TCR. Custom circuits and special testing available.

### General Note

IRC reserves the right to make changes in product specification without notice or liability. All information is subject to IRC's own data and is considered accurate at time of going to print.

© IRC Advanced Film Division • 4222 South Staples Street • Corpus Christi Texas 78411 USA  
Telephone: 361 992 7900 • Facsimile: 361 992 3377 • Website: www.irctt.com



4700 Series Issue January 2009 Sheet 1 of 4

# TaNFilm® Precision SIP Network Commercial and MIL Qualified



## MIL-PRF-83401 Qualification Data

Schematic	Resistance Range	Absolute Tolerance	Element Power	Size	Characteristic
C	100 - 100K	B, F, G, J	120	6, 8, 10	M, H, K
G	100 - 100K	B, F, G, J	200	6, 8, 10	M, H, K

## Package Specification Data

Schematic	Package Power (mW)			Voltage Rating	Temperature Range	Substrate	Lead Finish	Noise
	6-pin	8-pin	10-pin					
C, F (MIL and Commercial)	600	840	1080	$\sqrt{PxR}$ not to exceed 100V	-65°C to +125°C	99.6% Alumina	Gold Plate (60/40 Sn/Pb available)	<-30dB
G (MIL)	360	480	800					
G (Commercial)	600	800	1000					


## Environmental Data

Test Per MIL-PRF-83401	MIL-PRF-83401 $\Delta R$ Limits			TaNFilm® Test Data $\Delta R$	
	M	K	H	Max	Typical
Thermal Shock And Power Conditioning	±0.7%	±0.7%	±0.5%	±0.10%	±0.02%
Low Temperature Operation	±0.5%	±0.25%	±0.1%	±0.05%	±0.02%
Short-term Overload	±0.5%	±0.25%	±0.1%	±0.1%	±0.02%
Terminal Strength	±0.25%	±0.25%	±0.1%	±0.1%	±0.02%
Resistance To Solder Heat	±0.25%	±0.25%	±0.1%	±0.1%	±0.02%
Moisture Resistance	±0.5%	±0.5%	±0.4%	±0.1%	±0.02%
Shock	±0.25%	±0.25%	±0.25%	±0.1%	±0.02%
Vibration	±0.25%	±0.25%	±0.25%	±0.1%	±0.02%
Life	±2.0%	±0.5%	±0.5%	±0.1%	±0.02%
High Temperature Exposure	±1.0%	±0.5%	±0.2%	±0.1%	±0.02%
Low Temperature Storage	±0.5%	±0.25%	±0.1%	±0.1%	±0.02%
25°C Double Load	±2.0%	±0.5%	±0.5%	±0.05%	±0.02%


# TaNFilm<sup>®</sup> Precision SIP Network Commercial and MIL Qualified



## Schematic Data



## Physical Data



# TaNFilm<sup>®</sup> Precision SIP Network Commercial and MIL Qualified



## Ordering Data - Commercial

Sample Part No. .... SIP - 4781 - 03 - 1001 F B

### Model

4761 = 6-pin SIP, schematic C, gold terminations  
 4761SD = 6-pin SIP, schematic C, 60/40 Sn/Pb terminations  
 4768 = 6-pin SIP, schematic F, gold terminations  
 4768SD = 6-pin SIP, schematic F, 60/40 Sn/Pb terminations  
 4769 = 6-pin SIP, schematic G, gold terminations  
 4769SD = 6-pin SIP, schematic G, 60/40 Sn/Pb terminations

4781 = 8-pin SIP, schematic C, gold terminations  
 4781SD = 8-pin SIP, schematic C, 60/40 Sn/Pb terminations  
 4788 = 8-pin SIP, schematic F, gold terminations  
 4788SD = 8-pin SIP, schematic F, 60/40 Sn/Pb terminations  
 4789 = 8-pin SIP, schematic G, gold terminations  
 4789SD = 8-pin SIP, schematic G, 60/40 Sn/Pb terminations

4701 = 10-pin SIP, schematic C, gold terminations  
 4701SD = 10-pin SIP, schematic C, 60/40 Sn/Pb terminations  
 4708 = 10-pin SIP, schematic F, gold terminations  
 4708SD = 10-pin SIP, schematic F, 60/40 Sn/Pb terminations  
 4709 = 10-pin SIP, schematic G, gold terminations  
 4709SD = 10-pin SIP, schematic G, 60/40 Sn/Pb terminations

### Absolute TCR

01 =  $\pm 100\text{ppm}/^\circ\text{C}$ ; 02 =  $\pm 50\text{ppm}/^\circ\text{C}$ ; 03 =  $\pm 25\text{ppm}/^\circ\text{C}$ ; 11 =  $\pm 15\text{ppm}/^\circ\text{C}$

### Resistance

Standard 4-digit MIL resistance code  
 Example: 1001 = 1000 $\Omega$ ; 50R0=50 $\Omega$

### Absolute Tolerance

J =  $\pm 5\%$ ; G =  $\pm 2\%$ ; F =  $\pm 1.0\%$ ; D =  $\pm 0.5\%$ ; B =  $\pm 0.1\%$

### Optional Ratio Tolerance to R<sub>1</sub>

F =  $\pm 1.0\%$ ; D =  $\pm 0.5\%$ ; C =  $\pm 0.25\%$ ; B =  $\pm 0.1\%$ ; A =  $\pm 0.05\%$ ; Q =  $\pm 0.02\%$ , T =  $\pm 0.01\%$

Custom schematics and screening available.

Screening available for non-QPL values and tolerances. Contact factory for ordering information.

## Ordering Data - Military (MIL-PRF-83401)

Sample Part No. .... M83401 - 08 - H - 1002 - F - G

### Model

M83401 = Military qualified resistor network

### Size

07 = RZ060 6-pin SIP  
 08 = RZ080 8-pin SIP  
 09 = RZ090 10-pin SIP  
 21 = RZ210 Hi-Rel 6-pin SIP  
 22 = RZ220 Hi-Rel 8-pin SIP  
 23 = RZ230 Hi-Rel 10-pin SIP

### Characteristic per MIL-PRF-83401

M; K; H

### Resistance

Standard 4-digit MIL resistance code  
 Example: 1001 = 1000 $\Omega$ ; 50R0=50 $\Omega$

### Absolute Tolerance Code

J =  $\pm 5\%$ ; G =  $\pm 2\%$ ; F =  $\pm 1\%$ ; B =  $\pm 0.1\%$

### Schematic

C; G

Standard termination is gold plate. Contact factory for optional 60/40 Sn/Pb hot solder dip finish.  
 Screening available for non-QPL values and tolerances. Contact factory for ordering information.