

# Photoelectric Sensor BOS 15K-R-B2-02 Sn=2000mm Retroreflective

## Common Data


Sensortype	Retroreflective
Switching frequency	500 Hz
Rated operating distance Sn in mm	2000
Repeat accuracy	< 5% from Sn
Hysteresis	< 20%
Indication Supply Voltage	no
Indication Switching element on	yes, red LED
Indication Special funktion	LED green Stability indicator
Ambient temperature	-15...+55°C
On-delay	< 1 ms
Off-delay	< 1 ms
Light	Red light
Sensitivity Adjustment	Poti
Blind zone / min Reflector distance	0/15mm
Special funktion	Polarizing filter / Stab. indicator
Permissible ambient light	3000 Lux
Output funktion	light-on or dark-on

## Mechanical Data

Measurements	29x52x13
Shock	Halfsinus, 30gn, 11ms
Vibration	10...55Hz, 1,5mm Amplitude 3x2h
Housing material	ABS UL 94 V-O
Material of sensing face	PMMA
Degree of protection	IP66
Connection	Cable
Type of Cable	PVC

## Electrical Data

Current	DC
Switching funktion	NO/NC
Output	PNP/NPN
Rated operational voltage Ue	24V DC
Rated operational current Ie	100mA
Supply Voltage	10...30V DC
Ripple	max. 6% from UB
Frequency of Supply Voltage	DC
Voltage drop	<1,5V
Short protection	yes
Protected against polarity reversal	no
Rated insulation voltage	75VDC
max. Load capacity	0,5 µF



Utilization categories  
Insulation class

Datasheet number:

Definitions see general catalog.  
If not otherwise noted, ratings according to  
IEC 60947-5-2 (DIN EN60947-5-2)

Balluff GmbH  
P.O.Box 1160  
73761 Neuhausen Germany  
Phone (07158) 173-0 Fax (07158) 5010

Datenblatt by CD-ROM - 10/2004

**BALLUFF**