



Datasheet

Multi-mode Gigabit Ethernet SFP Transceiver

SFP-GD-MX



Features

- Data rate 1.062 to 1.25 Gb/s
- Single 3.3 V supply
- 2km reach for 50/125 μm MMF (500 MHz·km)
3km reach for 50/125 μm MMF (1000 MHz·km)
1km reach for 62.5/125 μm MMF (500 MHz·km)
1km reach for 62.5/125 μm MMF (1000 MHz·km)
- Gigabit Ethernet IEEE 802.3z compliance
- SFP MSA SFF-8074i compliance
- Telcordia GR-468 compliance
- 21 CFR 1040.10 and 1040.11 compliance
- TÜV compliance
- RoHS 5/6 compliance (Lead Exemption)
- Class 1 Laser
- Color coded bail latch : Grey

General Operating

Parameter	Symbol	Min.	Typical	Max.	Unit
Supply Voltage	V_{cc}	3.135	3.3	3.465	V
Total Current	I_{cc}	-	-	300	mA
Power Supply Noise Rejection ^a	PSR	100	-	-	mV _{p-p}
Operating Temperature	T_{opr}	-5	-	70	°C
Storage Temperature	T_{stg}	-40	-	85	°C
Data Rate GbE	DR	-	1250	-	Mbps
Data Rate FC	DR	-	1062.5	-	Mbps

a) 20 Hz to 155 MHz

Transmitter Specifications (Optical)

Parameter	Symbol	Min	Typical	Max	Unit
Optical Power	P_{op}	-9	-5	-3	dBm
Average Launch Power of Off Tx	P_{off}	-	-	-30	dBm
Extinction Ratio (Dynamic)	ER	9	-	-	dB
Eye Mask	IEEE 802.3Z, SONET/SDH compliant				
Total Jitter	TJ	-	-	200	ps
Optical Rise Time ^b	t_r	-	-	260	ns
Optical Fall Time ^b	t_f	-	-	260	ns
Mean Wavelength	λ	1270	1310	1355	nm
Spectral Width (RMS)	$\Delta\lambda$	-	-	4	nm
Relative Intensity Noise	RIN	-	-	-120	nm

b) 20% to 80% values


Transmitter Specifications (Electical)

Parameter	Symbol	Min	Typical	Max	Unit
Input Differential Impedence	R_{in}	80	100	120	Ω
PECL Single Ended Data Input Swing	$V_{in,p-p}$	250	-	1200	mV
TxFault_Fault	V_{fault}	2	-	V_{cc}	V
TxFault_Normal	V_{normal}	V_{ee}	-	$V_{ee}+0.5$	V
TxDisable_Disable	V_d	2	-	V_{cc}	V
TxDisable_Enable	V_{en}	V_{ee}	-	$V_{ee}+0.8$	V

Receiver Specifications (Optical)

Parameter	Symbol	Min	Typical	Max	Unit
Receive Power Low ^c	$R_{sens,low}$	-	-19	-17	dBm
Receive Power High ^c	$R_{sens,high}$	-3	-	-	dBm
Damage Threshold for Receiver	$P_{in,damage}$	6	-	-	dBm
Wavelength ^d	λ	1270	-	1355	nm
Maximum Reflectance of Receiver	RX_r	-	-	-12	dB
LOS Assert	LOS_A	-32	-	-	dBm
LOS De-assert	LOS_D	-	-	-17	dBm
LOS Hysteresis	Hys	0.5	-	-	dB

 b) $2^{23}-1$ PRBS, BER 10^{-10}
Receiver Specifications (Electrical)

Parameter	Symbol	Min	Typical	Max	Unit
PECL Single Ended Data Output Swing	$V_{out,p-p}$	185	-	800	mV
Data Output Rise Time	t_r	-	-	260	ps
Data Output Fall Time	t_f	-	-	260	ps



Timing and Electrical

Parameter	Symbol	Min	Typical	Max	Unit
Tx Disable Negate Time	t_{on}	-	-	1	ms
Tx Disable Assert Time	t_{off}	-	-	10	μs
Time To Initialize, Including Reset Of Tx Fault	t_{init}	-	-	300	ms
Tx Fault Assert Time	t_{fault}	-	-	100	μs
Tx Disable To Reset	t_{reset}	10	-	-	μs
LOS Assert Time	$t_{loss_{on}}$	-	-	100	μs
LOS De-assert Time	$t_{loss_{off}}$	-	-	100	μs
Serial ID Clock Rate	f_{serial_clock}	-	-	100	KHz
RX_LOS Voltage (High)	RX_{LOS_H}	2	-	-	V
RX_LOS Voltage (Low)	RX_{LOS_L}	-	-	0.8	V
LOS Output Voltage-Fault	$V_{LOS\ fault}$	2	-	V_{cc}	V
LOS Output Voltage-Normal	$V_{LOS\ normal}$	V_{ee}	-	$V_{ee}+0.5$	V
MOD_DEF (0:2)-High	V_H	2	-	V_{cc}	V
MOD_DEF (0:2)-Low	V_L	V_{ee}	-	$V_{ee}+0.5$	V




Pin	Function	Notes
1	V _{ee} T	TX GND
2	TX_FAULT	Open Collector
3	TX_DISABLE	Internally Pulled High
4	MOD_DEF2	Serial Data Input
5	MOD_DEF1	Serial Clock Input
6	MOD_DEF0	Internally Grounded
7	NC	Not Connected
8	LOS	Open Collector
9	V _{ee} R	RX Ground
10	V _{ee} R	RX Ground
11	V _{ee} R	RX Ground
12	RXD-	RX Data Negative
13	RXD+	RX Data Positive
14	V _{ee} R	RX GND
15	V _{cc} R	RX Power
16	V _{cc} T	TX Power
17	V _{ee} T	TX GND
18	TXD+	TX Data Positive
19	TXD-	TX Data Negative
20	V _{ee} T	TX GND

Outline Drawing



Units in mm(inch)




Ordering Information

Model	Description	Protocol	Wavelength (nm)	Output Power (dBm)		Receiver Sensitivity (dBm)	Link Budget (dBm)	Saturation Power (dBm)	Supply Voltage (V)	Connectors	Max. Power Dissipation	Distance Range (km)
				Min.	Max.							
SFP-GD-MX	Multi-mode Gigabit Ethernet SFP Transceiver	GbE / FC	1310	-9	-3	-17	8	-3	3.3	LC	1	0 - 2

MRV has more than 50 offices throughout the world. Addresses, phone numbers, and fax numbers are listed at www.mrv.com. Please e-mail us at sales@mrv.com or call us for assistance.

MRV (West Coast USA)

20415 Nordhoff St.
Chatsworth, CA 91311
800-338-5316
818-773-0900

MRV (East Coast USA)

295 Foster St.
Littleton, MA 01460
800-338-5316
978-952-4700

MRV (International)

Business Park Moerfelden
Waldeckerstrasse 13
64546 Moerfelden-Walldorf
Germany
Tel. (49) 6105/2070
Fax. (49) 6105/207-100

All statements, technical information and recommendations related to the products herein are based upon information believed to be reliable or accurate. However, the accuracy or completeness thereof is not guaranteed, and no responsibility is assumed for any inaccuracies. Please contact MRV Communications for more information. MRV Communications and the MRV Communications logo are trademarks of MRV Communications, Inc. Other trademarks are the property of their respective holders.