

# PRELIMINARY DATA SHEET

# ELPIDA

# MOS INTEGRATED CIRCUIT MC-45D16CD641KS

## 16 M-WORD BY 64-BIT DDR SYNCHRONOUS DYNAMIC RAM MODULE (SO DIMM)

### Description

The MC-45D16CD641KS is a 16,777,216 words by 64 bits DDR synchronous dynamic RAM module on which 8 pieces of 128M DDR SDRAM:  $\mu$ PD45D128164 are assembled.

These modules provide high density and large quantities of memory in a small space without utilizing the surface-mounting technology on the printed circuit board.

Decoupling capacitors are mounted on power supply line for noise reduction.

### Features

- 16,777,216 words by 64 bits organization
- Clock frequency

Part number	/CAS latency	Clock frequency (MAX.)	Module type
MC-45D16CD641KS-C75	CL = 2.5	133 MHz	DDR SDRAM
	CL = 2	100 MHz	SO DIMM
MC-45D16CD641KS-C80	CL = 2.5	125 MHz	Design specification
	CL = 2	100 MHz	Rev.1.0 compliant

- Fully Synchronous Dynamic RAM with all signals except DM, DQS and DQ referenced to a positive clock edge
- Double Data Rate interface  
Differential CLK (/CLK) input  
Data inputs and DM are synchronized with both edges of DQS  
Data outputs and DQS are synchronized with a cross point of CLK and /CLK
- Quad internal banks operation
- Possible to assert random column address in every clock cycle
- Programmable Mode register set  
/CAS latency (2, 2.5)  
Burst length (2, 4, 8)  
Wrap sequence (Sequential / Interleave)
- Automatic precharge and controlled precharge
- CBR (Auto) refresh and self refresh
- 2.5 V  $\pm$  0.2 V Power supply for V<sub>DD</sub>
- 2.5 V  $\pm$  0.2 V Power supply for V<sub>DDQ</sub>
- SSTL\_2 compatible with all signals
- 4,096 refresh cycles / 64 ms
- Burst termination by Precharge command and Burst stop command
- 200-pin dual in-line memory module (Pin pitch = 0.6 mm)
- Unbuffered type
- Serial PD


The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.  
Not all devices/types available in every country. Please check with local Elpida Memory, Inc. for availability and additional information.

**Ordering Information**

Part number	Clock frequency (MAX.)	Package	Mounted devices
MC-45D16CD641KS-C75	133 MHz	200-pin Dual In-line Memory Module (Socket Type)	8 pieces of $\mu$ PD45D128164G5 (Rev. K) (10.16 mm (400) TSOP (II))
MC-45D16CD641KS-C80	125 MHz	Edge connector: Gold plated 31.75 mm height	

**Pin Configuration**


**200-pin Dual In-line Memory Module Socket Type (Edge connector: Gold plated)**



/xxx indicates active low signal.

- A0 - A11 : Address Inputs  
[Row: A0 - A11, Column: A0 - A9]
- BA0, BA1 : SDRAM Bank Select
- DQ0 - DQ63 : Data Inputs/Outputs
- CK0 - CK2 : Clock Input  
(positive line of differential pair)
- /CK0 - /CK2 : Clock Input  
(negative line of differential pair)
- CKE0 : Clock Enable Input
- /S0, /S1 : Chip Select Input
- /RAS : Row Address Strobe
- /CAS : Column Address Strobe
- /WE : Write Enable
- DQS0 - DQS7 : Low Data Strobe
- DM(0 - 7) / DQS(9 - 16) : Low Data Masks /  
High Data Strobe
- SA0 - SA2 : Address Input for EEPROM
- SDA : Serial Data I/O for PD
- SCL : Clock Input for PD
- VDD : Power Supply
- VSS : Ground
- VDDID : VDD Identification Flag
- VDDQ : Power Supply for DQ and DQS
- VREF : Input Reference
- VDDSPD : Power supply for EEPROM
- NC : No Connection
- /RESET : Reset Input

## Block Diagram



- Remarks**
- The value of all resistors of DQs, DQSs, DM/DQSs is  $22 \Omega \pm 5\%$
  - D0 – D7:  $\mu$ PD45D128164 (2M words  $\times$  16 bits  $\times$  4 banks)

## Electrical Specifications

- All voltages are referenced to  $V_{SS}$  (GND).
- After power up, wait more than 1 ms and then, execute **Power on sequence and CBR (Auto) refresh** before proper device operation is achieved.

## Absolute Maximum Ratings

Parameter	Symbol	Condition	Rating	Unit
Voltage on power supply pin relative to $V_{SS}$	$V_{DD}, V_{DDQ}$		-0.5 to +3.6	V
Voltage on input pin relative to $V_{SS}$	$V_T$		-0.5 to +3.6	V
Short circuit output current	$I_O$		50	mA
Power dissipation	$P_D$		12	W
Storage temperature	$T_{stg}$		-55 to +125	°C

**Caution** Exposing the device to stress above those listed in Absolute Maximum Ratings could cause permanent damage. The device is not meant to be operated under conditions outside the limits described in the operational section of this specification. Exposure to Absolute Maximum Rating conditions for extended periods may affect device reliability.

## Recommended Operating Conditions

Parameter	Symbol	Condition	MIN.	TYP.	MAX.	Unit
Supply voltage	$V_{DD}$		2.3	2.5	2.7	V
Supply voltage for DQ, DQS	$V_{DDQ}$		2.3	2.5	2.7	V
Input reference voltage	$V_{REF}$		$0.49 \times V_{DDQ}$		$0.51 \times V_{DDQ}$	V
Termination voltage	$V_{TT}$		$V_{REF} - 0.04$	$V_{REF}$	$V_{REF} + 0.04$	V
High level dc input voltage	$V_{IH}$ (DC)		$V_{REF} + 0.15$		$V_{DD} + 0.3$	V
Low level dc input voltage	$V_{IL}$ (DC)		-0.3		$V_{REF} - 0.15$	V
Input differential voltage (CLK and /CLK)	$V_{ID}$ (DC)		0.36		$V_{DDQ} + 0.6$	V
Input crossing point voltage (CLK and /CLK)	$V_{IX}$		$0.5 \times V_{DDQ} - 0.2$		$0.5 \times V_{DDQ} + 0.2$	V
Operating ambient temperature	$T_A$		0		70	°C

## Capacitance ( $T_A = 25\text{ °C}$ , $f = 100\text{ MHz}$ )

Parameter	Symbol	Test condition	MIN.	TYP.	MAX.	Unit
Input capacitance	$C_{i1}$	A0 - A11, BA0, BA1, /RAS, /CAS, /WE	TBD		TBD	pF
	$C_{i2}$	CK0 - CK2, /CK0 - /CK2	TBD		TBD	
	$C_{i3}$	CKE0	TBD		TBD	
	$C_{i4}$	/S0, /S1	TBD		TBD	
Data input/output capacitance	$C_{i/o1}$	DM(0-7) / DQS(9-16), DQS0 - DQS7	TBD		TBD	pF
	$C_{i/o2}$	DQ0 - DQ63	TBD		TBD	

**DC Characteristics 1 (Recommended Operating Conditions unless otherwise noted)**

Parameter	Symbol	Test condition	/CAS latency	Grade	MIN.	MAX.	Unit	Notes
Operating current (ACT-PRE)	IDD0	t <sub>RC</sub> = t <sub>RC(MIN.)</sub> , t <sub>CK</sub> = t <sub>CK(MIN.)</sub> , One bank, Active-precharge, DQ, DM and DQS inputs changing twice per clock cycle, Address and control inputs changing once per clock cycle		-C75		920	mA	
				-C80		840		
Operating current (ACT-READ-PRE)	IDD1	t <sub>RC</sub> = t <sub>RC(MIN.)</sub> , t <sub>CK</sub> = t <sub>CK(MIN.)</sub> , One bank, Active-read-precharge, I <sub>O</sub> = 0 mA, Burst length = 2, Address and control inputs changing once per clock cycle	CL = 2	-C75		980	mA	1
				-C80		920		
				-C75		1020		
				-C80		960		
Precharge power down standby current	IDD2P	CKE ≤ V <sub>IL(MAX.)</sub> , t <sub>CK</sub> = t <sub>CK(MIN.)</sub> , All banks idle, Power down mode				80	mA	
Idle standby current	IDD2N	CKE ≥ V <sub>IH(MIN.)</sub> , t <sub>CK</sub> = t <sub>CK(MIN.)</sub> , /CS ≥ V <sub>IH(MIN.)</sub> , All banks idle, Address and other control inputs changing once per clock cycle				400	mA	
Active power down standby current	IDD3P	CKE ≤ V <sub>IL(MAX.)</sub> , t <sub>CK</sub> = t <sub>CK(MIN.)</sub> , One bank active, Power down mode				400	mA	
Active standby current	IDD3N	/CS ≥ V <sub>IH(MIN.)</sub> , CKE ≥ V <sub>IH(MIN.)</sub> , t <sub>CK</sub> = t <sub>CK(MIN.)</sub> , t <sub>RC</sub> = t <sub>TRAS(MAX.)</sub> , One bank, Active-precharge, DQ, DM and DQS inputs changing twice per clock cycle, Address and other control inputs changing once per clock cycle				560	mA	
Operating current (Burst read)	IDD4R	t <sub>CK</sub> = t <sub>CK(MIN.)</sub> , Continuous burst read, Burst length = 2, I <sub>O</sub> = 0mA, One bank active, Address and control inputs changing once per clock cycle	CL = 2	-C75		1080	mA	2
				-C80		1080		
				-C75		1340		
				-C80		1280		
Operating current (Burst write)	IDD4W	t <sub>CK</sub> = t <sub>CK(MIN.)</sub> , Continuous burst write, Burst length = 2, One bank active, Address and control inputs changing once per clock cycle	CL = 2	-C75		1040	mA	2
				-C80		1040		
				-C75		1300		
				-C80		1240		
CBR (Auto) refresh current	IDD5	t <sub>RFC</sub> = t <sub>RFC(MIN.)</sub>		-C75		1360	mA	
				-C80		1280		
Self refresh current	IDD6	CKE ≤ 0.2 V				16	mA	

**Notes 1.** IDD1 depends on output loading and cycle rates. Specified values are obtained with the output open.

**2.** IDD4R and IDD4W depend on output loading and cycle rates. Specified values are obtained with the output open.

**DC Characteristics 2 (Recommended Operating Conditions unless otherwise noted)**


Parameter	Symbol	Test condition	MIN.	MAX.	Unit	Notes
Input leakage current	I <sub>I(L)</sub>	V <sub>I</sub> = 0 to 3.6 V, all other pins not under test = 0 V	-5	5	μA	
Output leakage current	I <sub>O(L)</sub>	D <sub>OUT</sub> is disabled, V <sub>O</sub> = 0 to V <sub>DDQ</sub> + 0.3 V	-5	5	μA	
Output high current	I <sub>OH</sub>	V <sub>OUT</sub> = V <sub>DDQ</sub> - 0.43 V	-15.2		mA	
Output low current	I <sub>OL</sub>	V <sub>OUT</sub> = 0.35 V	15.2		mA	

**AC Characteristics (Recommended Operating Conditions unless otherwise noted)****Test Conditions**

Parameter	Symbol	Value	Unit	Notes
Input Reference voltage (Input timing measurement reference level)	$V_{REF}$	$V_{DDQ} \times 0.5$	V	
Termination voltage (Output timing measurement reference level)	$V_{TT}$	$V_{REF}$	V	1
High level ac input voltage	$V_{IH}(ac)$	$V_{REF} + 0.31$	V	
Low level ac input voltage	$V_{IL}(ac)$	$V_{REF} - 0.31$	V	
Input differential voltage (CK0 - CK2 and /CK0 - /CK2)	$V_{ID}(ac)$	0.7	V	
Input signal slew rate	SLEW	1	V/ns	2

**Notes** 1. Output waveform timing is measured where the output signal crosses through the  $V_{TT}$  level.

2. Slew rate is to be maintained in the  $V_{IL}(ac)$  to  $V_{IH}(ac)$  range of the input signal swing.  $SLEW = (V_{IH}(ac) - V_{IL}(ac)) / \Delta t$



**Synchronous Characteristics**

Parameter		Symbol	-C75 (PC266B)		-C80 (PC200)		Unit	Note
			MIN.	MAX.	MIN.	MAX.		
Clock cycle time	CL = 2.5	t <sub>CK</sub>	7.5	15	8	15	ns	
	CL = 2		10	15	10	15		
CLK high-level width		t <sub>CH</sub>	0.45	0.55	0.45	0.55	t <sub>CK</sub>	
CLK low-level width		t <sub>CL</sub>	0.45	0.55	0.45	0.55	t <sub>CK</sub>	
DQ output access time from CLK, /CLK		t <sub>AC</sub>	-0.75	0.75	-0.8	0.8	ns	
DQS output access time from CLK, /CLK		t <sub>DQSCK</sub>	-0.75	0.75	-0.8	0.8	ns	
DQS-DQ skew (for DQS and associated DQ signals)		t <sub>DQSQ</sub>	-0.5	0.5	-0.6	0.6	ns	
DQS-DQ skew (for DQS and all DQ signals)		t <sub>DQSOA</sub>	-0.5	0.5	-0.6	0.6	ns	
Data out low-impedance time from CLK, /CLK		t <sub>LZ</sub>	-0.75	0.75	-0.8	0.8	ns	
Data out high-impedance time from CLK, /CLK		t <sub>HZ</sub>	-0.75	0.75	-0.8	0.8	ns	
Half clock period		t <sub>HP</sub>	t <sub>CH</sub> , t <sub>CL</sub>		t <sub>CH</sub> , t <sub>CL</sub>		ns	
DQS read preamble		t <sub>RPRE</sub>	0.9	1.1	0.9	1.1	t <sub>CK</sub>	
DQS read postamble		t <sub>RPST</sub>	0.4	0.6	0.4	0.6	t <sub>CK</sub>	
DQ-DQS hold, DQS to first DQ to go non-valid, per access		t <sub>QH</sub>	t <sub>HP</sub> - 0.75		t <sub>HP</sub> - 1		ns	
DQ and DM input setup time		t <sub>DS</sub>	0.5		0.6		ns	
DQ and DM input hold time		t <sub>DH</sub>	0.5		0.6		ns	
DQ and DM input pulse width (for each input)		t <sub>DIPW</sub>	1.75		2		ns	
DQS write preamble setup time		t <sub>WPRES</sub>	0		0		ns	
DQS write preamble		t <sub>WPRE</sub>	0.25		0.25		t <sub>CK</sub>	
Write postamble		t <sub>WPST</sub>	0.4	0.6	0.4	0.6	t <sub>CK</sub>	
Write command to first DQS latching transition		t <sub>DQSS</sub>	0.75	1.25	0.75	1.25	t <sub>CK</sub>	
DQS input high pulse width		t <sub>DQSH</sub>	0.35		0.35		t <sub>CK</sub>	
DQS input low pulse width		t <sub>DQSL</sub>	0.35		0.35		t <sub>CK</sub>	
DQS falling edge to CLK setup time		t <sub>DSS</sub>	0.2		0.2		t <sub>CK</sub>	
DQS falling edge hold time from CLK		t <sub>DSH</sub>	0.2		0.2		t <sub>CK</sub>	
Address and control input setup time		t <sub>IS</sub>	0.9		1.1		ns	
Address and control input hold time		t <sub>IH</sub>	0.9		1.1		ns	
Address and control input pulse width		t <sub>IPW</sub>	2.2		2.5		ns	
Internal write to read command delay		t <sub>WTR</sub>	1		1		t <sub>CK</sub>	

**Remark** These specifications are applied to the monolithic device.



**Asynchronous Characteristics**

Parameter	Symbol	-C75(PC266B)		-C80(PC200)		Unit
		MIN.	MAX.	MIN.	MAX.	
ACT to REF/ACT command period (operation)	t <sub>RC</sub>	65		70		ns
REF to REF/ACT command period (refresh)	t <sub>RFC</sub>	75		80		ns
ACT to PRE command period	t <sub>RAS</sub>	45	120,000	50	120,000	ns
PRE to ACT command period	t <sub>RP</sub>	20		20		ns
ACT to READ/WRITE delay	t <sub>RCD</sub>	20		20		ns
ACT(one) to ACT(another) command period	t <sub>RRD</sub>	15		15		ns
Write recovery time	t <sub>WR</sub>	15		15		ns
Auto precharge write recovery time + precharge time	t <sub>DAL</sub>	35		35		ns
Mode register set command cycle time	t <sub>MRD</sub>	15		15		ns
Exit self refresh to command	t <sub>XSNR</sub>	75		80		ns
Refresh time (4,096 refresh cycles)	t <sub>REF</sub>		64		64	ms

**Serial PD**

**(1/2)**


Byte No.	Function Described	Hex	Bit 7	Bit 6	Bit 5	Bit 4	Bit 3	Bit 2	Bit 1	Bit 0	Notes	
0	Defines the number of bytes written into serial PD memory	80H	1	0	0	0	0	0	0	0	128 bytes	
1	Total number of bytes of serial PD memory	08H	0	0	0	0	1	0	0	0	256 bytes	
2	Fundamental memory type	07H	0	0	0	0	0	1	1	1	DDR SDRAM	
3	Number of rows	0CH	0	0	0	0	1	1	0	0	12 rows	
4	Number of columns	09H	0	0	0	0	1	0	0	1	9 columns	
5	Number of banks	02H	0	0	0	0	0	0	1	0	2 banks	
6	Data width	40H	0	1	0	0	0	0	0	0	64 bits	
7	Data width (continued)	00H	0	0	0	0	0	0	0	0	0	
8	Voltage interface	04H	0	0	0	0	0	1	0	0	SSTL_2	
9	CL = 2.5 Cycle time	-C75	75H	0	1	1	1	0	1	0	1	7.5 ns
		-C80	80H	1	0	0	0	0	0	0	0	8 ns
10	CL = 2.5 Access time	-C75	75H	0	1	1	1	0	1	0	1	0.75 ns
		-C80	80H	1	0	0	0	0	0	0	0	0.8 ns
11	DIMM configuration type	00H	0	0	0	0	0	0	0	0	None	
12	Refresh rate/type	80H	1	0	0	0	0	0	0	0	Normal	
13	SDRAM width	10H	0	0	0	1	0	0	0	0	x8	
14	Error checking SDRAM width	00H	0	0	0	0	0	0	0	0	None	
15	Minimum clock delay	01H	0	0	0	0	0	0	0	1	1 clock	
16	Burst length supported	0EH	0	0	0	0	1	1	1	0	2, 4, 8	
17	Number of banks on each SDRAM	04H	0	0	0	0	0	1	0	0	4 banks	
18	/CAS latency supported	0CH	0	0	0	0	1	1	0	0	2, 2.5	
19	/CS latency supported	01H	0	0	0	0	0	0	0	1	0	
20	/WE latency supported	02H	0	0	0	0	0	0	1	0	1	
21	SDRAM module attributes	20H	0	0	1	0	0	0	0	0	Differential Clock	
22	SDRAM device attributes : General	00H	0	0	0	0	0	0	0	0	V <sub>DD</sub> ± 0.2 V	
23	CL = 2 Cycle time	-C75	A0H	1	0	1	0	0	0	0	0	10 ns
		-C80	A0H	1	0	1	0	0	0	0	0	10 ns
24	CL = 2 Access time	-C75	75H	0	1	1	1	0	1	0	1	0.75 ns
		-C80	80H	1	0	0	0	0	0	0	0	0.8 ns
25-26												
27	t <sub>RP</sub> (MIN.)	-C75	50H	0	1	0	1	0	0	0	0	20 ns
		-C80	50H	0	1	0	1	0	0	0	0	20 ns
28	t <sub>RRD</sub> (MIN.)	-C75	3CH	0	0	1	1	1	1	0	0	15 ns
		-C80	3CH	0	0	1	1	1	1	0	0	15 ns
29	t <sub>RCD</sub> (MIN.)	-C75	50H	0	1	0	1	0	0	0	0	20 ns
		-C80	50H	0	1	0	1	0	0	0	0	20 ns
30	t <sub>TRAS</sub> (MIN.)	-C75	2DH	0	0	1	0	1	1	0	1	45 ns
		-C80	32H	0	0	1	1	0	0	1	0	50 ns
31	Module bank density	10H	0	0	0	1	0	0	0	0	64M bytes	

Byte No.	Function Described	Hex	Bit 7	Bit 6	Bit 5	Bit 4	Bit 3	Bit 2	Bit 1	Bit 0	Notes	
32	Command and address signal input setup time	-C75	90H	1	0	0	1	0	0	0	0	0.9 ns
		-C80	B0H	1	0	1	1	0	0	0	0	1.1 ns
33	Command and address signal input hold time	-C75	90H	1	0	0	1	0	0	0	0	0.9 ns
		-C80	B0H	1	0	1	1	0	0	0	0	1.1 ns
34	Data signal input setup time	-C75	50H	0	1	0	1	0	0	0	0	0.5 ns
		-C80	60H	0	1	1	0	0	0	0	0	0.6 ns
35	Data signal input hold time	-C75	50H	0	1	0	1	0	0	0	0	0.5 ns
		-C80	60H	0	1	1	0	0	0	0	0	0.6 ns
36-61												
62	SPD revision	00H	0	0	0	0	0	0	0	0	0	
63	Checksum for bytes 0 - 62	-C75	94H	1	0	0	1	0	1	0	0	
		-C80	1AH	0	0	0	1	1	0	1	0	
64-71	Manufacture's JEDEC ID code											
72	Manufacturing location											
73-90	Manufacture's P/N											
91	Revision Code											
93-94	Manufacturing date											
95-99	Assembly serial number											
100-127	Mfg specific	00H	0	0	0	0	0	0	0	0	0	

**Timing Chart**

Refer to the  $\mu$ PD45D128442, 45D128842, 45D128164 Data sheet (E0030N).

**Package Drawing**



**CAUTION FOR HANDLING MEMORY MODULES**

When handling or inserting memory modules, be sure not to touch any components on the modules, such as the memory IC, chip capacitors and chip resistors. It is necessary to avoid undue mechanical stress on these components to prevent damaging them.

When re-packing memory modules, be sure the modules are NOT touching each other. Modules in contact with other modules may cause excessive mechanical stress, which may damage the modules.

MDE0107

**NOTES FOR CMOS DEVICES****① PRECAUTION AGAINST ESD FOR MOS DEVICES**

Exposing the MOS devices to a strong electric field can cause destruction of the gate oxide and ultimately degrade the MOS devices operation. Steps must be taken to stop generation of static electricity as much as possible, and quickly dissipate it, when once it has occurred. Environmental control must be adequate. When it is dry, humidifier should be used. It is recommended to avoid using insulators that easily build static electricity. MOS devices must be stored and transported in an anti-static container, static shielding bag or conductive material. All test and measurement tools including work bench and floor should be grounded. The operator should be grounded using wrist strap. MOS devices must not be touched with bare hands. Similar precautions need to be taken for PW boards with semiconductor MOS devices on it.

**② HANDLING OF UNUSED INPUT PINS FOR CMOS DEVICES**

No connection for CMOS devices input pins can be a cause of malfunction. If no connection is provided to the input pins, it is possible that an internal input level may be generated due to noise, etc., hence causing malfunction. CMOS devices behave differently than Bipolar or NMOS devices. Input levels of CMOS devices must be fixed high or low by using a pull-up or pull-down circuitry. Each unused pin should be connected to  $V_{DD}$  or GND with a resistor, if it is considered to have a possibility of being an output pin. The unused pins must be handled in accordance with the related specifications.

**③ STATUS BEFORE INITIALIZATION OF MOS DEVICES**

Power-on does not necessarily define initial status of MOS devices. Production process of MOS does not define the initial operation status of the device. Immediately after the power source is turned ON, the MOS devices with reset function have not yet been initialized. Hence, power-on does not guarantee output pin levels, I/O settings or contents of registers. MOS devices are not initialized until the reset signal is received. Reset operation must be executed immediately after power-on for MOS devices having reset function.

CME0107

The information in this document is subject to change without notice. Before using this document, confirm that this is the latest version.

No part of this document may be copied or reproduced in any form or by any means without the prior written consent of Elpida Memory, Inc.

Elpida Memory, Inc. does not assume any liability for infringement of any intellectual property rights (including but not limited to patents, copyrights, and circuit layout licenses) of Elpida Memory, Inc. or third parties by or arising from the use of the products or information listed in this document. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of Elpida Memory, Inc. or others.

Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of the customer's equipment shall be done under the full responsibility of the customer. Elpida Memory, Inc. assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.

**[Product applications]**

Elpida Memory, Inc. makes every attempt to ensure that its products are of high quality and reliability. However, users are instructed to contact Elpida Memory's sales office before using the product in aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment, medical equipment for life support, or other such application in which especially high quality and reliability is demanded or where its failure or malfunction may directly threaten human life or cause risk of bodily injury.

**[Product usage]**

Design your application so that the product is used within the ranges and conditions guaranteed by Elpida Memory, Inc., including the maximum ratings, operating supply voltage range, heat radiation characteristics, installation conditions and other related characteristics. Elpida Memory, Inc. bears no responsibility for failure or damage when the product is used beyond the guaranteed ranges and conditions. Even within the guaranteed ranges and conditions, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Elpida Memory, Inc. products does not cause bodily injury, fire or other consequential damage due to the operation of the Elpida Memory, Inc. product.

**[Usage environment]**

This product is not designed to be resistant to electromagnetic waves or radiation. This product must be used in a non-condensing environment.

If you export the products or technology described in this document that are controlled by the Foreign Exchange and Foreign Trade Law of Japan, you must follow the necessary procedures in accordance with the relevant laws and regulations of Japan. Also, if you export products/technology controlled by U.S. export control regulations, or another country's export control laws or regulations, you must follow the necessary procedures in accordance with such laws or regulations.

If these products/technology are sold, leased, or transferred to a third party, or a third party is granted license to use these products, that third party must be made aware that they are responsible for compliance with the relevant laws and regulations.

M01E0107