

ROITHNER LASERTECHNIK

A-1040 WIEN, FLEISCHMANNGASSE 9
 TEL: +43 -1- 586 52 43 FAX: +43 -1- 586 41 43
 e-mail: rlt@mcb.at, <http://www.roithner.mcb.at>

VCSEL TEL-3A TECHNICAL DATA


Infrared Wavelength VCSEL

Lasing wavelength: 840 nm typ.

Max. optical power: 3 mW typ., lasing aperture \varnothing 10 μ m typ.

Package: epoxy molded ceramic heatsink, 8° circular round beam (FWHM)

Very low threshold current, low operating current, high speed



Absolute Maximum Ratings (T_c=25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Optical Output Power	P _o	5	mW
LD Reverse Voltage	V _{R(LD)}	10	V
Operation Temperature	T _C	-10 .. +70	°C
Storage Temperature	T _{STG}	-40 +85	°C

Optical-Electrical Characteristics (T_c = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Optical Output Power	P _o	I _F = 10 mA	1.0	2.0	3.0	mW
Threshold Current	I _{th}		1.5	2.0	3.0	mA
Threshold Variation	Δ I _{th}	T _A = 0 .. 70°C	- 1	0	+ 1	mA
Operation Current	I _{op}	P _o = 1.5 mW		7	10	mA
Operating Voltage	V _{op}	I _F = 10 mA	1.8	2.2	2.5	V
Slope Efficiency	η	I _F = 10 mA	0.15	0.25	0.35	mW/mA
Series Resistance	R _S	I _F = 10 mA		50		Ω
Wavelength	λ _p	I _F = 10 mA	820	840	860	nm
Risetime / Falltime	t _r / t _f			200		ps
Beam Divergence	θ	I _F = 10 mA		8		°
Spectral Width	Δλ	I _F = 10 mA		0.5		nm
Wavelength Drift	Δλ _p /ΔT	I _F = 10 mA		0.05		nm/°C