


Radiation	Type	Technology	Case
infrared	ELD-810-525	AlGaAs/AlGaAs	5 mm plastic lens

Description

High-power, high-speed,
double heterostructure with removed substrate,
with stand off lead

Applications

Optical communications,
safety equipment



Note: Special packages without stand off available on request

Maximum Ratings

$T_{amb} = 25^\circ\text{C}$, unless otherwise specified

Parameter	Test Conditions	Symbol	Value	Unit
Forward current (DC)		I_F	100	mA
Peak forward current	($t_p \leq 50 \mu\text{s}$, $t_p/T = 1/2$)	I_{FM}	200	mA
Surge forward current	($t_p \leq 10 \mu\text{s}$)	I_{FSM}	2000	mA
Reverse voltage	$I_R = 100 \mu\text{A}$	V_R	5	V
Operating temperature range		T_{amb}	-20 to +100	°C
Storage temperature range		T_{stg}	-55 to +100	°C
Weight			0.33	g

Optical and Electrical Characteristics

$T_{amb} = 25^\circ\text{C}$, unless otherwise specified

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Forward voltage	$I_F = 100 \text{ mA}$	V_F		1.8	2.1	V
Radiant power	$I_F = 100 \text{ mA}$	Φ_e		28		mW
Peak wavelength	$I_F = 100 \text{ mA}$	λ_p		810		nm
Spectral bandwidth at 50%	$I_F = 100 \text{ mA}$	$\Delta\lambda_{0.5}$		35		nm
Viewing angle		ϕ		20		deg.
Switching time	$I_F = 100 \text{ mA}$	t_r, t_f		40		ns