

ROITHNER LASERTECHNIK

A-1040 WIEN, FLEISCHMANNGASSE 9
TEL: +43 -1- 586 52 43 FAX: +43 -1- 586 41 43
e-mail: rlt@mcb.at http://www.roithner-laser.com

ELD-740-525 TECHNICAL DATA

PRELIMINARY

INFRARED GaAlAs LED

Technology: **GaAlAs structure**
Peak Wavelength: **740 nm typ.**
Package: **5 mm bluish clear plastic**



Absolute Maximum Ratings (Tc=25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Reverse Voltage	V_R	5	V
Reverse Current	I_R	10	μ A
Soldering Temperature	T_S	260	°C for 5 s
Operating Temperature	T_{OP}	-20 .. +100	°C
Storage Temperature	T_{STG}	-40 .. +85	°C

Optical-Electrical Characteristics (Tc = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Optical Output Power	P_O	$I_F = 100$ mA	25	28	30	mW
Forward Voltage	V_F	$I_F = 20$ mA		1.5	2.0	V
Forward Current	I_F	cw		20	100	mA
Peak Forward Current	I_P	dutycycle 50% @ $t_p \leq 50\mu$ s		200		mA
Power Dissipation	P_D	25 °C, free air		130		mW
Switching time on	t_r			30		ns
Switchung time off	t_f			40		ns
Peak Wavelength	λ_P	$I_F = 100$ mA		740		nm
Spectrum Half Width	$\Delta\lambda_{1/2}$	$I_F = 100$ mA		25		nm
Viewing Angle	$2\theta_{1/2}$	$I_F = 100$ mA		20		°