

Sound Processor Series for Car Audio

# Sound Processor with Built-in 3-band Equalizer

BD37524FS



No.10085EAT05

## ● Description

BD37524FS is sound processors built-in 3-band equalizer for car audio. The functions are stereo 5ch input selector, input-gain control, main volume, loudness, 5ch fader volume, LPF for subwoofer, level meter. Moreover, "Advanced switch circuit", that is ROHM original technology, can reduce various switching noise (ex. No-signal, low frequency likes 20Hz & large signal inputs). "Advanced switch" makes control of microcomputer easier, and can construct high quality car audio system.

## ● Features

- 1) Reduce switching noise of input gain control, mute, main volume, fader volume, bass, treble, loudness by using advanced switch circuit [Possible to control all steps]
- 2) Built-in 1 differential input selector and 4 single-ended input selectors
- 3) Built-in ground isolation amplifier inputs, ideal for external stereo input.
- 4) Built-in input gain controller reduces switching noise for volume of a portable audio input.
- 5) Decrease the number of external components by built-in 3-band equalizer filter, LPF for subwoofer, loudness filter. And, possible to control Q, Gv, fo of 3-band equalizer and fc of LPF, fo, Gv of loudness by I<sup>2</sup>C BUS control freely
- 6) It is possible for the bass, middle, and treble to the gain adjustment quantity of ±20dB and 1 dB step gain adjustment.
- 7) Terminals for the subwoofer outputs are equipped.
- 8) Bi-CMOS process is suitable for the design of low current and low energy. And it provides more quality for small scale regulator and heat in a set.
- 9) Package is SSOP-A24. Putting input-terminals together and output-terminals together can make PCB layout easier and can makes area of PCB smaller.
- 10) It is possible to control by 3.3V / 5V for I<sup>2</sup>C BUS.

## ● Applications

It is the optimal for the car audio. Besides, it is possible to use for the audio equipment of mini Compo, micro Compo, TV etc with all kinds.

● Line up matrix

Function	Specifications
Input selector	<ul style="list-style-type: none"> <li>Stereo 4 input</li> <li>Differential 1 input</li> </ul>
Input gain	<ul style="list-style-type: none"> <li>0~20dB (1dB step)</li> <li>Possible to use "Advanced switch" for prevention of switching noise.</li> </ul>
Mute	<ul style="list-style-type: none"> <li>Possible to use "Advanced switch" for prevention of switching noise.</li> </ul>
Volume	<ul style="list-style-type: none"> <li>+15dB~-79dB (1dB step), -∞</li> <li>Possible to use "Advanced switch" for prevention of switching noise.</li> </ul>
Bass	<ul style="list-style-type: none"> <li>-20~+20dB (1dB step)</li> <li>Q=0.5, 1, 1.5, 2 variable</li> <li>fo=60, 80, 100, 120Hz</li> <li>Possible to use "Advanced switch" at changing gain</li> </ul>
Middle	<ul style="list-style-type: none"> <li>-20~+20dB (1dB step)</li> <li>Q=0.75, 1, 1.25, 1.5 variable</li> <li>fo=500, 1k, 1.5k, 2.5kHz variable</li> <li>Possible to use "Advanced switch" at changing gain</li> </ul>
Treble	<ul style="list-style-type: none"> <li>-20~+20dB (1dB step)</li> <li>Q=0.75, 1.25 variable</li> <li>fo=7.5k, 10k, 12.5k, 15kHz variable</li> <li>Possible to use "Advanced switch" at changing gain</li> </ul>
Fader	<ul style="list-style-type: none"> <li>+15dB~-79dB(1dB step), -∞dB</li> <li>Possible to use "Advanced switch" for prevention of switching noise.</li> </ul>
Loudness	<ul style="list-style-type: none"> <li>0dB~20dB(1dB step)</li> <li>fo=250/400/800Hz</li> <li>Possible to use "Advanced switch" for prevention of switching noise.</li> </ul>
LPF	<ul style="list-style-type: none"> <li>fc=55/85/120/160Hz, pass</li> <li>Phase shift (0°/180°)</li> </ul>
Level meter	<ul style="list-style-type: none"> <li>I2C BUS control</li> <li>DC Output</li> </ul>

● Absolute maximum ratings (Ta=25°C)

Item	Symbol	Rating	Unit
Power supply Voltage	VCC	10.0	V
Input voltage	Vin	VCC+0.3~GND-0.3	V
Power Dissipation	Pd	1000 ≈1	mW
Storage Temperature	Tastg	-55~+150	°C

※This value decreases 8mW/°C for Ta=25°C or more.

ROHM standard board shall be mounted.

Thermal resistance θja = 125(°C/W)

ROHM Standard board

Size : 70x70x1.6(mm<sup>3</sup>)

Material : A FR4 glass epoxy board(3% or less of copper foil area)

● Operating conditions

Item	Symbol	MIN	TYP	MAX	Unit
Power supply Voltage	VCC	7.0	—	9.5	V
Temperature	Topr	-40	—	+85	°C

### ● Electrical characteristics

(Unless specified particularly, Ta=25°C, VCC=8.5V, f=1kHz, Vin=1Vrms, Rg=600Ω, RL=10kΩ, A1 input, Input gain 0dB, Mute off, Volume 0dB, Tone control 0dB, Loudness 0dB, LPF OFF, Fader 0dB)

BLOCK	Item	Symbol	Limit			Unit	Condition
			Min.	Typ.	Max.		
GENERAL	Current upon no signal	I <sub>Q</sub>	—	38	48	mA	No signal
	Voltage gain	G <sub>V</sub>	-1.5	0	1.5	dB	G <sub>V</sub> =20log(VOUT/VIN)
	Channel balance	CB	-1.5	0	1.5	dB	CB = G <sub>V1</sub> -G <sub>V2</sub>
	Total harmonic distortion 1 (FRONT,REAR)	THD+N1	—	0.001	0.05	%	VOUT=1Vrms BW=400-30KHz
	Total harmonic distortion 2 (SUBWOOFER)	THD+N2	—	0.002	0.05	%	VOUT=1Vrms BW=400-30KHz
	Output noise voltage 1 (FRONT,REAR) *	V <sub>NO1</sub>	—	3.8	15	µVrms	R <sub>g</sub> = 0Ω BW = IHF-A
	Output noise voltage 2 (SUBWOOFER) *	V <sub>NO2</sub>	—	4.8	15	µVrms	R <sub>g</sub> = 0Ω BW = IHF-A
	Residual output noise voltage *	V <sub>NOR</sub>	—	1.8	10	µVrms	Fader = -∞dB R <sub>g</sub> = 0Ω BW = IHF-A
	Cross-talk between channels *	CTC	—	-100	-90	dB	R <sub>g</sub> = 0Ω CTC=20log(VOUT/VIN) BW = IHF-A
	Ripple rejection	RR	—	-70	-40	dB	f=1kHz VRR=100mVrms RR=20log(VCC IN/VOUT)
INPUT SELECTOR	Input impedance(A, B)	R <sub>IN_S</sub>	70	100	130	kΩ	
	Input impedance (C,D,E)	R <sub>IN_D</sub>	175	250	325	kΩ	
	Maximum input voltage	V <sub>IM</sub>	2.1	2.3	—	Vrms	VIM at THD+N(VOUT)=1% BW=400-30KHz
	Cross-talk between selectors *	CTS	—	-100	-90	dB	R <sub>g</sub> = 0Ω CTS=20log(VOUT/VIN) BW = IHF-A
	Common mode rejection ratio *	CMRR	50	65	—	dB	CP1 and CN input CP2 and CN input CMRR=20log(VIN/VOUT) BW = IHF-A
INPUT GAIN	Minimum input gain	G <sub>IN MIN</sub>	-2	0	+2	dB	Input gain 0dB VIN=100mVrms Gin=20log(VOUT/VIN)
	Maximum input gain	G <sub>IN MAX</sub>	18	20	22	dB	Input gain 20dB VIN=100mVrms Gin=20log(VOUT/VIN)
	Gain set error	G <sub>IN ERR</sub>	-2	0	+2	dB	GAIN=+20~+1dB
MUTE	Mute attenuation *	G <sub>MUTE</sub>	—	-105	-85	dB	Mute ON Gmute=20log(VOUT/VIN) BW = IHF-A
VOLUME	Maximum gain	G <sub>V MAX</sub>	13	15	17	dB	Volume = 15dB VIN=100mVrms Gv=20log(VOUT/VIN)
	Maximum attenuation *	G <sub>V MIN</sub>	—	-100	-85	dB	Volume = -∞dB Gv=20log(VOUT/VIN) BW = IHF-A
	Attenuation set error 1	G <sub>V ERR1</sub>	-2	0	2	dB	GAIN & ATT=+15dB~-15dB
	Attenuation set error 2	G <sub>V ERR2</sub>	-3	0	3	dB	ATT=-16dB~-47dB
	Attenuation set error 3	G <sub>V ERR3</sub>	-4	0	4	dB	ATT=-48dB~-79dB

BLOCK	Item	Symbol	Limit			Unit	Condition
			Min.	Typ.	Max.		
BASS	Maximum boost gain	$G_{B\ BST}$	18	20	22	dB	Gain=+20dB f=100Hz VIN=100mVrms $G_B=20\log(VOUT/VIN)$
	Maximum cut gain	$G_{B\ CUT}$	-22	-20	-18	dB	Gain=-20dB f=100Hz VIN=2Vrms $G_B=20\log(VOUT/VIN)$
	Gain set error	$G_{B\ ERR}$	-2	0	2	dB	Gain=-20~+20dB f=100Hz
MIDDLE	Maximum boost gain	$G_{M\ BST}$	18	20	22	dB	Gain=+20dB f=1kHz VIN=100mVrms $G_M=20\log(VOUT/VIN)$
	Maximum cut gain	$G_{M\ CUT}$	-22	-20	-18	dB	Gain=-20dB f=1kHz VIN=2Vrms $G_M=20\log(VOUT/VIN)$
	Gain set error	$G_{M\ ERR}$	-2	0	2	dB	Gain=-20~+20dB f=1kHz
TREBLE	Maximum boost gain	$G_{T\ BST}$	17	20	23	dB	Gain=+20dB f=10kHz VIN=100mVrms $G_T=20\log(VOUT/VIN)$
	Maximum cut gain	$G_{T\ CUT}$	-23	-20	-17	dB	Gain=-20dB f=10kHz VIN=2Vrms $G_T=20\log(VOUT/VIN)$
	Gain set error	$G_{T\ ERR}$	-2	0	2	dB	Gain=-20~+20dB f=10kHz
FADER / SUBWOOFER	Maximum boost gain	$G_{F\ BST}$	13	15	17	dB	Fader=15dB VIN=100mVrms $G_F=20\log(VOUT/VIN)$
	Maximum attenuation *	$G_{F\ MIN}$	—	-100	-90	dB	Fader = -∞dB $G_F=20\log(VOUT/VIN)$ BW = IHF-A
	Gain set error	$G_{F\ ERR}$	-2	0	2	dB	Gain=+1~+15dB
	Attenuation set error 1	$G_{F\ ERR1}$	-2	0	2	dB	ATT=-1~-15dB
	Attenuation set error 2	$G_{F\ ERR2}$	-3	0	3	dB	ATT=-16~-47dB
	Attenuation set error 3	$G_{F\ ERR3}$	-4	0	4	dB	ATT=-48~-79dB
	Output impedance	$R_{OUT}$	-	—	50	Ω	VIN=100mVrms
LOUDNESS	Maximum output voltage	$V_{OM}$	2	2.2	—	Vrms	THD+N=1% BW=400-30KHz
	Maximum gain	$G_{L\ MAX}$	17	20	23	dB	Gain 20dB VIN=100mVrms $G_L=20\log(VOUT/VIN)$
	Gain set error	$G_{L\ ERR}$	-2	0	2	dB	GAIN=+20~+1dB
Level meter	Maximum output voltage	$V_{L\ MAX}$	2.8	3.1	3.5	V	
	Output offset voltage	$V_{L\ OFF}$	—	0	100	mV	

VP-9690A(Average value detection, effective value display) filter by Matsushita Communication is used for \* measurement.

Phase between input / output is same.

● Electrical characteristic curves (Reference data)




Fig.1 Iq vs Vcc




Fig.2 Thd vs Vo




Fig.3 Gain vs Freq




Fig.4 Bass Gain vs Freq




Fig.5 Bass fo vs Freq




Fig.6 Bass Q vs Freq




Fig.7 Middle Gain vs Freq




Fig.8 Middle fo vs Freq




Fig.9 Middle Q vs Freq




Fig.10 Treble Gain vs Freq




Fig.11 Treble fo vs Freq




Fig.12 Treble Q vs Freq




Fig.13 Volume Gain vs Noise




Fig.14 Bass Gain vs Noise




Fig.15 Middle Gain vs Noise




Fig.16 Treble Gain vs Noise




Fig.17 CMRR vs Freq




Fig.18 Rload vs Vo




Fig.19 Advanced Switch 1




Fig.20 Advanced Switch 2




Fig.21 Level Meter Vin vs Vo

### ● Block diagram and pin configuration




Fig.22 BD37524FS

#### Descriptions of terminal

Terminal No.	Terminal Name	Description	Terminal No.	Terminal Name	Description
1	FIL	VCC/2 terminal	13	MUTE	External compulsory mute terminal
2	A1	A input terminal of 1ch	14	LOUT	Output terminal for Level meter
3	A2	A input terminal of 2ch	15	OUTS2	Subwoofer output terminal of 2ch
4	B1	B input terminal of 1ch	16	OUTS1	Subwoofer output terminal of 1ch
5	B2	B input terminal of 2ch	17	OUTR2	Rear output terminal of 2ch
6	CP1	C positive input terminal of 1ch	18	OUTR1	Rear output terminal of 1ch
7	CN	C negative input terminal	19	OUTF2	Front output terminal of 2ch
8	CP2	C positive input terminal of 2ch	20	OUTF1	Front output terminal of 1ch
9	D1	D input terminal of 1ch	21	VCC	Power supply terminal
10	D2	D input terminal of 2ch	22	SCL	I <sup>2</sup> C Communication clock terminal
11	E1	E input terminal of 1ch	23	SDA	I <sup>2</sup> C Communication data terminal
12	E2	E input terminal of 2ch	24	GND	GND terminal

### ● Timming Chart

#### CONTROL SIGNAL SPECIFICATION

##### (1) Electrical specifications and timing for bus lines and I/O stages




Fig. 23 Definition of timing on the I<sup>2</sup>C-bus

Table 1 Characteristics of the SDA and SCL bus lines for I<sup>2</sup>C-bus devices  
(Unless specified particularly, Ta=25°C, VCC=8.5V)

Parameter	Symbol	Fast-mode I <sup>2</sup> C-bus		Unit
		Min.	Max.	
1 SCL clock frequency	f SCL	0	400	kHz
2 Bus free time between a STOP and START condition	tBUF	1.3	—	μs
3 Hold time (repeated) START condition. After this period, the first clock pulse is generated	tHD:STA	0.6	—	μs
4 LOW period of the SCL clock	tLOW	1.3	—	μs
5 HIGH period of the SCL clock	tHIGH	0.6	—	μs
6 Set-up time for a repeated START condition	tSU:STA	0.6	—	μs
7 Data hold time:	tHD:DAT	0.06*	—	μs
8 Data set-up time	tSU:DAT	120	—	ns
9 Set-up time for STOP condition	tSU:STO	0.6	—	μs

All values referred to VIH min. and VIL max. Levels (see Table 2).

\* A device must internally provide a hold time of at least 300 ns for the SDA signal (referred to the VIH min. of the SCL signal) in order to bridge the undefined region of the falling edge of SCL.  
About 7(tHD;DAT), 8(tSU;DAT), make it the setup which a margin is fully in .

Table 2 Characteristics of the SDA and SCL I/O stages for I<sup>2</sup>C-bus devices

	Parameter	Symbol	Fast-mode devices		Unit
			Min.	Max.	
10	LOW level input voltage:	VIL	-0.3	1	V
11	HIGH level input voltage:	VIH	2.3	5	V
12	Pulse width of spikes which must be suppressed by the input filter.	tSP	0	50	ns
13	LOW level output voltage: at 3mA sink current	VOL1	0	0.4	V
14	Input current each I/O pin with an input voltage between 0.4V and 4.5V.	Ii	-10	10	μA




Fig.24 A command timing example in the I2C data transmission

(2) I<sup>2</sup>C BUS FORMAT

MSB	LSB	MSB	LSB	MSB	LSB	A	P
S	Slave Address	A	Select Address	A	Data	A	P
1bit	8bit	1bit	8bit	1bit	8bit	1bit	1bit
S	= Start conditions (Recognition of start bit)						
Slave Address	= Recognition of slave address. 7 bits in upper order are voluntary.						
	The least significant bit is "L" due to writing.						
A	= ACKNOWLEDGE bit (Recognition of acknowledgement)						
Select Address	= Select every of volume, bass and treble.						
Data	= Data on every volume and tone.						
P	= Stop condition (Recognition of stop bit)						

(3) I<sup>2</sup>C BUS Interface Protocol

## 1) Basic form

S	Slave Address	A	Select Address	A	Data	A	P
MSB	LSB	MSB	LSB	MSB	LSB		

## 2) Automatic increment (Select Address increases (+1) according to the number of data).

S	Slave Address	A	Select Address	A	Data1	A	Data2	A	....	DataN	A	P
MSB	LSB	MSB	LSB	MSB	LSB	MSB	LSB	MSB	LSB	MSB	LSB	

(Example) ①Data1 shall be set as data of address specified by Select Address.

②Data2 shall be set as data of address specified by Select Address +1.

③DataN shall be set as data of address specified by Select Address +N-1.

## 3) Configuration unavailable for transmission (In this case, only Select Address1 is set.)

S	Slave Address	A	Select Address1	A	Data	A	Select Address 2	A	Data	A	P
MSB	LSB	MSB	LSB	MSB	LSB	MSB	LSB	MSB	LSB		

(Note) If any data is transmitted as Select Address 2 next to data, it is recognized as data, not as Select Address 2.
--

(4) Slave address

LSB							
A6	A5	A4	A3	A2	A1	A0	R/W
1	0	0	0	0	0	0	0

80H


## (5) Select Address &amp; Data

Items	Select Address (hex)	Data						LSB				
		D7	D6	D5	D4	D3	D2					
Initial setup 1	01	Advanced switch ON/OFF	0	Advanced switch time of Input Gain/Volume Tone/Fader/Loudness	0	0	0	Advanced switch time of Mute				
Initial setup 2	02	LPF Phase	Level Meter RESET	0	0	0	Subwoofer LPF fc	LPF Phase				
Initial setup 3	03	0	0	0	Loudness fo	0	0	1				
Input Selector	05	0	0	0	Input selector							
Input gain	06	Mute ON/OFF	0	0	Input Gain							
Volume gain	20	Volume Gain / Attenuation										
Fader 1ch Front	28	Fader Gain / Attenuation										
Fader 2ch Front	29	Fader Gain / Attenuation										
Fader 1ch Rear	2A	Fader Gain / Attenuation										
Fader 2ch Rear	2B	Fader Gain / Attenuation										
Fader Subwoofer	2C	Fader Gain / Attenuation										
Bass setup	41	0	0	Bass fo	0	0	Bass Q					
Middle setup	44	0	0	Middle fo	0	0	Middle Q					
Treble setup	47	0	0	Treble fo	0	0	0	Treble Q				
Bass gain	51	Bass Boost/Cut	0	0	Bass Gain							
Middle gain	54	Middle Boost/Cut	0	0	Middle Gain							
Treble gain	57	Treble Boost/Cut	0	0	Treble Gain							
Loudness Gain	75	0	Loudness Hicut	Loudness Gain								
System Reset	FE	1	0	0	0	0	0	1				

 Advanced switch

## Note

1. In function changing of the hatching part, it works Advanced switch.
2. Upon continuous data transfer, the Select Address is circulated by the automatic increment function, as shown below.



3. For the function of input selector etc, it is not corresponded for advanced switch. Therefore, please apply mute on the side of a set when changes these setting.
4. When using mute function of this IC at the time of changing input selector, please switch mute ON/OFF for waiting advanced-mute time.

Select address 01 (hex)

Time	MSB Advanced switch time of Mute LSB									
	D7	D6	D5	D4	D3	D2	D1	D0		
0. 6msec	Advanced Switch ON/OFF	0	Advanced switch time of Input gain/Volume Tone/Fader/Loudness			0	0	0		
1. 0msec								0		
1. 4msec								1		
3. 2msec								1		

Time	MSB Advanced switch time of Input gain/Volume/Tone/Fader/Loudness LSB							
	D7	D6	D5	D4	D3	D2	D1	D0
4. 7 msec	Advanced Switch ON/OFF	0	0	0	0	0	Advanced switch Time of Mute	
7. 1 msec			0	1				
11. 2 msec			1	0				
14. 4 msec			1	1				

Mode	MSB Advanced switch ON/OFF LSB								
	D7	D6	D5	D4	D3	D2	D1	D0	
OFF	0	0	Advanced switch time of Input gain/Volume Tone/Fader/Loudness			0	0	Advanced switch Time of Mute	
ON	1								

Select address 02 (hex)

fc	MSB Subwoofer LPF fc LSB							
	D7	D6	D5	D4	D3	D2	D1	D0
OFF	LPF Phase	Level Meter RESET	0	0	0	0	0	0
55Hz						0	0	1
85Hz						0	1	0
120Hz						0	1	1
160Hz						1	0	0
Prohibition						Other setting		

Mode	MSB Level Meter RESET LSB							
	D7	D6	D5	D4	D3	D2	D1	D0
HOLD	LPF Phase	0	0	0	0	Subwoofer LPF fc		
RESET		1						

Phase	MSB LPF Phase LSB							
	D7	D6	D5	D4	D3	D2	D1	D0
0°	0	Level Meter RESET	0	0	0	Subwoofer LPF fc		
180°	1							

Select address 03 (hex)

f0	MSB Loudness fo LSB							
	D7	D6	D5	D4	D3	D2	D1	D0
250Hz	0	0	0	0	0	0	0	1
400Hz				0	1			
800Hz				1	0			
Prohibition				1	1			

 : Initial condition

Select address 05 (hex)

Mode	OUT F1/R1	OUT F2/R2	MSB		Input Selector				LSB					
			D7	D6	D5	D4	D3	D2	D1	D0				
A	A1	A2	0	0	0	0	0	0	0	1				
B	B1	B2					0	0	1	0				
C diff	CP1	CP2					0	1	1	0				
D	D1	D2					1	0	1	0				
E	E1	E2					1	0	1	1				
Input SHORT							1	0	0	1				
Prohibition							Other setting							

**Input SHORT** : The input impedance of each input terminal is lowered from 100kΩ (TYP) to 6 kΩ (TYP).  
 (For quick charge of coupling capacitor)

Select address 06 (hex)

Gain	MSB		Input Gain				LSB	
	D7	D6	D5	D4	D3	D2	D1	D0
0dB	Mute ON/OFF	0	0	0	0	0	0	0
1dB				0	0	0	0	1
2dB				0	0	0	1	0
3dB				0	0	0	1	1
4dB				0	0	1	0	0
5dB				0	0	1	0	1
6dB				0	0	1	1	0
7dB				0	0	1	1	1
8dB				0	1	0	0	0
9dB				0	1	0	0	1
10dB				0	1	0	1	0
11dB				0	1	0	1	1
12dB				0	1	1	0	0
13dB				0	1	1	0	1
14dB				0	1	1	1	0
15dB				0	1	1	1	1
16dB				1	0	0	0	0
17dB				1	0	0	0	1
18dB				1	0	0	1	0
19dB				1	0	0	1	1
20dB				1	0	1	0	0
Prohibition				1	1	0	1	1
				:	:	:	:	:
				1	1	1	1	1

Mode	MSB		Mute ON/OFF				LSB	
	D7	D6	D5	D4	D3	D2	D1	D0
OFF	0	0	0	Input Gain				
ON	1							

 : Initial condition

Select address 20, 28, 29, 2A, 2B, 2C (hex)

Gain & ATT	MSB      Vol, Fader Gain / Attenuation      LSB							
	D7	D6	D5	D4	D3	D2	D1	D0
Prohibition	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	1
	:	:	:	:	:	:	:	:
	0	1	1	1	0	0	0	0
15dB	0	1	1	1	0	0	0	1
14dB	0	1	1	1	0	0	1	0
13dB	0	1	1	1	0	0	1	1
:	:	:	:	:	:	:	:	:
-77dB	1	1	0	0	1	1	0	1
-78dB	1	1	0	0	1	1	1	0
-79dB	1	1	0	0	1	1	1	1
Prohibition	1	1	0	1	0	0	0	0
	:	:	:	:	:	:	:	:
	1	1	1	1	1	1	1	0
$-\infty$ dB	1	1	1	1	1	1	1	1

 : Initial condition

Select address 41 (hex)

Q factor	Bass Q factor							LSB
	D7	D6	D5	D4	D3	D2	D1	
0.5							0	0
1.0							0	1
1.5							1	0
2.0							1	1

fo	Bass fo							LSB
	D7	D6	D5	D4	D3	D2	D1	
60Hz			0	0				
80Hz			0	1				
100Hz			1	0				
120Hz			1	1				

Select address 44 (hex)

Q factor	Middle Q factor							LSB
	D7	D6	D5	D4	D3	D2	D1	
0.75							0	0
1.0							0	1
1.25							1	0
1.5							1	1

fo	Middle fo							LSB
	D7	D6	D5	D4	D3	D2	D1	
500Hz			0	0				
1kHz			0	1				
1.5kHz			1	0				
2.5kHz			1	1				

Select address 47 (hex)

Q factor	Treble Q factor							LSB
	D7	D6	D5	D4	D3	D2	D1	
0.75							0	0
1.25							0	1

fo	Treble fo							LSB
	D7	D6	D5	D4	D3	D2	D1	
7.5kHz			0	0				
10kHz			0	1				
12.5kHz			1	0				
15kHz			1	1				

 : Initial condition

Select address 51, 54, 57 (hex)

Gain	MSB		Bass/ Middle/ Treble			Gain		LSB
	D7	D6	D5	D4	D3	D2	D1	D0
0dB	Bass/ Middle/ Treble Boost /cut	0	0	0	0	0	0	0
1dB				0	0	0	0	1
2dB				0	0	0	1	0
3dB				0	0	0	1	1
4dB				0	0	1	0	0
5dB				0	0	1	0	1
6dB				0	0	1	1	0
7dB				0	0	1	1	1
8dB				0	1	0	0	0
9dB				0	1	0	0	1
10dB				0	1	0	1	0
11dB				0	1	0	1	1
12dB				0	1	1	0	0
13dB				0	1	1	0	1
14dB				0	1	1	1	0
15dB				0	1	1	1	1
16dB				1	0	0	0	0
17dB				1	0	0	0	1
18dB				1	0	0	1	0
19dB				1	0	0	1	1
20dB				1	0	1	0	0
Prohibition				1	0	1	0	1
				:	:	:	:	:
				1	1	1	1	0
				1	1	1	1	1

Mode	MSB		Bass/ Middle/ Treble			Boost/Cut		LSB
	D7	D6	D5	D4	D3	D2	D1	D0
Boost	0	0	0	Bass/Middle/Treble Gain				
Cut	1			Bass/Middle/Treble Gain				

 : Initial condition

Select address 75 (hex)

Mode	MSB   LSB							
	D7	D6	D5	D4	D3	D2	D1	D0
Hicut1	0	0	0	Loudness Gain				
Hicut2		0	1					
Hicut3		1	0					
Hicut4		1	1					

Gain	MSB   LSB							
	D7	D6	D5	D4	D3	D2	D1	D0
0dB	0	Loudness Hicut	0	0	0	0	0	0
1dB			0	0	0	0	0	1
2dB			0	0	0	1	0	0
3dB			0	0	0	1	1	1
4dB			0	0	1	0	0	0
5dB			0	0	1	0	1	1
6dB			0	0	1	1	0	0
7dB			0	0	1	1	1	1
8dB			0	1	0	0	0	0
9dB			0	1	0	0	1	1
10dB			0	1	0	1	0	0
11dB			0	1	0	1	1	1
12dB			0	1	1	0	0	0
13dB			0	1	1	0	1	1
14dB			0	1	1	1	0	0
15dB			0	1	1	1	1	1
16dB			1	0	0	0	0	0
17dB			1	0	0	0	1	0
18dB			1	0	0	1	0	0
19dB			1	0	0	1	1	1
20dB			1	0	1	0	0	0
Prohibition			:	:	:	:	:	:
			1	1	1	1	1	1

:

 Initial condition

#### (6) About power on reset

At on of supply voltage circuit made initialization inside IC is built-in. Please send data to all address as initial data at supply voltage on. And please supply mute at set side until this initial data is sent.

Item	Symbol	Limit			Unit	Condition
		Min.	Typ.	Max.		
Rise time of VCC	Trise	33	—	—	usec	VCC rise time from 0V to 5V
VCC voltage of release power on reset	Vpor	—	4.1	—	V	

#### (7) About external compulsory mute terminal

Mute is possible forcibly than the outside after input again department, by the setting of the MUTE terminal.

Mute Voltage Condition	Mode
GND~1.0V	MUTE ON
2.3V~VCC	MUTE OFF

Establish the voltage of MUTE in the condition to have been defined.

## Volume / Fader volume attenuation of the details

(dB)	D7	D6	D5	D4	D3	D2	D1	D0		(dB)	D7	D6	D5	D4	D3	D2	D1	D0
+15	0	1	1	1	0	0	0	1		-33	1	0	1	0	0	0	0	1
+14	0	1	1	1	0	0	1	0		-34	1	0	1	0	0	0	1	0
+13	0	1	1	1	0	0	1	1		-35	1	0	1	0	0	0	1	1
+12	0	1	1	1	0	1	0	0		-36	1	0	1	0	0	1	0	0
+11	0	1	1	1	0	1	0	1		-37	1	0	1	0	0	1	0	1
+10	0	1	1	1	0	1	1	0		-38	1	0	1	0	0	1	1	0
+9	0	1	1	1	0	1	1	1		-39	1	0	1	0	0	1	1	1
+8	0	1	1	1	1	0	0	0		-40	1	0	1	0	1	0	0	0
+7	0	1	1	1	1	0	0	1		-41	1	0	1	0	1	0	0	1
+6	0	1	1	1	1	0	1	0		-42	1	0	1	0	1	0	1	0
+5	0	1	1	1	1	0	1	1		-43	1	0	1	0	1	0	1	1
+4	0	1	1	1	1	1	0	0		-44	1	0	1	0	1	1	0	0
+3	0	1	1	1	1	1	0	1		-45	1	0	1	0	1	1	0	1
+2	0	1	1	1	1	1	1	0		-46	1	0	1	0	1	1	1	0
+1	0	1	1	1	1	1	1	1		-47	1	0	1	0	1	1	1	1
0	1	0	0	0	0	0	0	0		-48	1	0	1	1	0	0	0	0
-1	1	0	0	0	0	0	0	1		-49	1	0	1	1	0	0	0	1
-2	1	0	0	0	0	0	0	1		-50	1	0	1	1	0	0	1	0
-3	1	0	0	0	0	0	0	1		-51	1	0	1	1	0	0	1	1
-4	1	0	0	0	0	1	0	0		-52	1	0	1	1	0	1	0	0
-5	1	0	0	0	0	0	1	0		-53	1	0	1	1	0	1	0	1
-6	1	0	0	0	0	0	1	1		-54	1	0	1	1	0	1	1	0
-7	1	0	0	0	0	0	1	1		-55	1	0	1	1	0	1	1	1
-8	1	0	0	0	1	0	0	0		-56	1	0	1	1	1	0	0	0
-9	1	0	0	0	1	0	0	1		-57	1	0	1	1	1	0	0	1
-10	1	0	0	0	1	0	1	0		-58	1	0	1	1	1	0	1	0
-11	1	0	0	0	1	0	1	1		-59	1	0	1	1	1	0	1	1
-12	1	0	0	0	1	1	0	0		-60	1	0	1	1	1	1	0	0
-13	1	0	0	0	1	1	0	1		-61	1	0	1	1	1	1	0	1
-14	1	0	0	0	1	1	1	0		-62	1	0	1	1	1	1	1	0
-15	1	0	0	0	1	1	1	1		-63	1	0	1	1	1	1	1	1
-16	1	0	0	1	0	0	0	0		-64	1	1	0	0	0	0	0	0
-17	1	0	0	1	0	0	0	1		-65	1	1	0	0	0	0	0	1
-18	1	0	0	1	0	0	0	1		-66	1	1	0	0	0	0	1	0
-19	1	0	0	1	0	0	0	1		-67	1	1	0	0	0	0	0	1
-20	1	0	0	1	0	1	0	0		-68	1	1	0	0	0	1	0	0
-21	1	0	0	1	0	1	0	1		-69	1	1	0	0	0	1	0	1
-22	1	0	0	1	0	1	1	0		-70	1	1	0	0	0	1	1	0
-23	1	0	0	1	0	1	1	1		-71	1	1	0	0	0	1	1	1
-24	1	0	0	1	1	0	0	0		-72	1	1	0	0	1	0	0	0
-25	1	0	0	1	1	0	0	1		-73	1	1	0	0	1	0	0	1
-26	1	0	0	1	1	0	1	0		-74	1	1	0	0	1	0	1	0
-27	1	0	0	1	1	0	1	1		-75	1	1	0	0	1	0	1	1
-28	1	0	0	1	1	1	0	0		-76	1	1	0	0	1	1	0	0
-29	1	0	0	1	1	1	0	1		-77	1	1	0	0	1	1	0	1
-30	1	0	0	1	1	1	1	0		-78	1	1	0	0	1	1	1	0
-31	1	0	0	1	1	1	1	1		-79	1	1	0	0	1	1	1	1
-32	1	0	1	0	0	0	0	0		-∞	1	1	1	1	1	1	1	1

: Initial condition

About Level meter

## (1) The operation of circuit

Level meter is a function which gives DC voltage proportional to the size of signal of sound. It detects the peak level of signal and keeps the peak level, so that it is possible to monitor the size of signal by resetting DC voltage kept with suitable interval.

## (2) The way to reset level meter output

Please send reset data through I<sup>2</sup>C BUS

When reset output of level meter : Send D6 = "1" of select address 02(hex).


When cancel of output reset of level meter (HOLD) → Send D6 = "0" of select address 02(hex).

## (3) The settings about period of reset

Peak hold operation will start after HOLD data is transmitted. Set the WAIT time after HOLD data transmission according to the frequency bandwidth detected.

WAIT time must be set to a minimum of one cycle over the detected frequency bandwidth.

Ex) Detected frequency bandwidth is above 40Hz, [40Hz = 25ms = WAIT time]

Transmission Example by I<sup>2</sup>C BUS

### ● Application circuit




Fig. 25 Application Circuit Diagram




#### Notes on wiring

- ① Please connect the decoupling capacitor of a power supply in the shortest distance as much as possible to GND.
- ② Lines of GND shall be one-point connected.
- ③ Wiring pattern of Digital shall be away from that of analog unit and cross-talk shall not be acceptable.
- ④ Lines of SCL and SDA of I<sup>2</sup>C BUS shall not be parallel if possible.  
The lines shall be shielded, if they are adjacent to each other.
- ⑤ Lines of analog input shall not be parallel if possible. The lines shall be shielded, if they are adjacent to each other.

## ● Interfaces

Terminal No.	Terminal Name	Terminal Voltage	Equivalent Circuit	Terminal Description
2 3 4 5	A1 A2 B1 B2	4.25		A terminal for signal input. The input impedance is 100kΩ (typ).
6 7 8 9 10 11 12	CP1 CN CP2 D1 D2 E1 E2	4.25		A terminal for signal input. The input impedance is 250kΩ (typ).
13	MUTE	-		A terminal for external compulsory mute. If terminal voltage is High level, the mute is off. And if the terminal voltage is Low level, the mute is on.
16 17 18 19 20	OUTS1 OUTR2 OUTR1 OUTF2 OUTF1	4.25		A terminal for fader and Subwoofer output.

The figure in the pin explanation and input/output equivalent circuit is reference value, it doesn't guarantee the value.

Terminal No.	Terminal Name	Terminal Voltage	Equivalent Circuit	Terminal Description
21	VCC	8.5		Power supply terminal.
22	SCL	-	 <p>The diagram shows the SCL pin connected to Vcc through a diode. It has an open-drain connection to ground through a 1.65V zener diode. A PNP transistor is connected between the output node and ground, with its collector connected to the 1.65V zener diode's cathode. A diode is also present between the base and collector of the PNP transistor.</p>	A terminal for clock input of I <sup>2</sup> C BUS communication.
23	SDA	-	 <p>The diagram shows the SDA pin connected to Vcc through a diode. It has an open-drain connection to ground through a 1.65V zener diode. A PNP transistor is connected between the output node and ground, with its collector connected to the 1.65V zener diode's cathode. A diode is also present between the base and collector of the PNP transistor.</p>	A terminal for data input of I <sup>2</sup> C BUS communication.
24	GND	0		Ground terminal.
1	FIL	4.25	 <p>The diagram shows the FIL pin connected to Vcc through a diode. It has a reference bias circuit consisting of two parallel branches. Each branch contains a 50k resistor connected to ground through a diode. The outputs of these resistors are connected to the base of a PNP transistor. The collector of this PNP transistor is connected to the FIL pin, and its emitter is connected to ground through a diode.</p>	Voltage for reference bias of analog signal system. The simple precharge circuit and simple discharge circuit for an external capacitor are built in.

The figure in the pin explanation and input/output equivalent circuit is reference value, it doesn't guarantee the value.

● Notes for use


1. Absolute maximum rating voltage

When it impressed the voltage on VCC more than the absolute maximum rating voltage, circuit currents increase rapidly, and there is absolutely a case to reach characteristic deterioration and destruction of a device. In particular in a surge examination of a set, when it is expected the impressing surge at VCC terminal (21pin), please do not impress the large and over the absolute maximum rating voltage (including a operating voltage + surge ingredient (around 14V)).

2. About a signal input part

1) About constant set up of input coupling capacitor

In the signal input terminal, the constant setting of input coupling capacitor C(F) be sufficient input impedance  $R_{IN}(\Omega)$  inside IC and please decide. The first HPF characteristic of RC is composed.



2) About the input selector SHORT

SHORT mode is the command which makes switch  $S_{SH}$  =ON an input selector part and input impedance  $R_{IN}$  of all terminals, and makes resistance small. Switch  $S_{SH}$  is OFF when not choosing a SHORT command. A constant time becomes small at the time of this command twisting to the resistance inside the capacitor connected outside and LSI. The charge time of a capacitor becomes short. Since SHORT mode turns ON the switch of  $S_{SH}$  and makes it low impedance, please use it at the time of a non-signal.

3. About Mute terminal (13pin) when power supply is off

Any voltage shall not be supplied to Mute terminal (13pin) when power-supply is off.

Please insert a resistor (about  $2.2k\Omega$ ) to Mute terminal in series, if voltage is supplied to mute terminal in case. (Please refer Application Circuit Diagram.)

### ● Thermal Derating Curve

About the thermal design by the IC

Characteristics of an IC have a great deal to do with the temperature at which it is used, and exceeding absolute maximum ratings may degrade and destroy elements. Careful consideration must be given to the heat of the IC from the two standpoints of immediate damage and long-term reliability of operation.




Fig.26 Temperature Derating Curve


Note) Values are actual measurements and are not guaranteed.

Power dissipation values vary according to the board on which the IC is mounted.

● Ordering part number

<b>B</b>	<b>D</b>	<b>3</b>	<b>7</b>	<b>5</b>	<b>2</b>	<b>4</b>	<b>F</b>	<b>S</b>	-	<b>E</b>	<b>2</b>
Part No.	Part No. 37524			Package FS : SSOP-A24	Packaging and forming specification E2: Embossed tape and reel						

**SSOP-A24**



## Notes

No copying or reproduction of this document, in part or in whole, is permitted without the consent of ROHM Co.,Ltd.

The content specified herein is subject to change for improvement without notice.

The content specified herein is for the purpose of introducing ROHM's products (hereinafter "Products"). If you wish to use any such Product, please be sure to refer to the specifications, which can be obtained from ROHM upon request.

Examples of application circuits, circuit constants and any other information contained herein illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.

Great care was taken in ensuring the accuracy of the information specified in this document. However, should you incur any damage arising from any inaccuracy or misprint of such information, ROHM shall bear no responsibility for such damage.

The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM and other parties. ROHM shall bear no responsibility whatsoever for any dispute arising from the use of such technical information.

The Products specified in this document are intended to be used with general-use electronic equipment or devices (such as audio visual equipment, office-automation equipment, communication devices, electronic appliances and amusement devices).

The Products specified in this document are not designed to be radiation tolerant.

While ROHM always makes efforts to enhance the quality and reliability of its Products, a Product may fail or malfunction for a variety of reasons.

Please be sure to implement in your equipment using the Products safety measures to guard against the possibility of physical injury, fire or any other damage caused in the event of the failure of any Product, such as derating, redundancy, fire control and fail-safe designs. ROHM shall bear no responsibility whatsoever for your use of any Product outside of the prescribed scope or not in accordance with the instruction manual.

The Products are not designed or manufactured to be used with any equipment, device or system which requires an extremely high level of reliability the failure or malfunction of which may result in a direct threat to human life or create a risk of human injury (such as a medical instrument, transportation equipment, aerospace machinery, nuclear-reactor controller, fuel-controller or other safety device). ROHM shall bear no responsibility in any way for use of any of the Products for the above special purposes. If a Product is intended to be used for any such special purpose, please contact a ROHM sales representative before purchasing.

If you intend to export or ship overseas any Product or technology specified herein that may be controlled under the Foreign Exchange and the Foreign Trade Law, you will be required to obtain a license or permit under the Law.



Thank you for your accessing to ROHM product informations.  
More detail product informations and catalogs are available, please contact us.

### ROHM Customer Support System

<http://www.rohm.com/contact/>