

SKUT 115



SEMIPONT™ 5

Three phase antiparallel Thyristor Module

SKUT 115

Target Data

Features


- Compact design
- Two screws mounting
- Heat transfer and isolation through direct copper board (Low R_{th})
- Low resistance in Steady-State and high reliability
- High surge currents
- Glass passivated thyristors chips
- Up to 1600V reverse voltage
- UL recognized, file no. E 63 532

Typical Applications

- Soft starter
- Light control (e.g. studios, theaters)
- Temperature control (e.g. oven, chemical processes)



V_{RSM} V	V_{RRM}, V_{DRM} V	$I_{RMS} = 105$ A (full conduction) ($T_s = 85$ °C)
1300	1200	SKUT 115/12
1700	1600	SKUT 115/16

Symbol	Conditions	Values	Units
I_{RMS}	W3C ; sin. 180° ; $T_s = 85$ °C ; sin. 180° ;	105	A A
I_{TSM}	$T_{vj} = 25$ °C ; 10 ms $T_{vj} = 125$ °C ; 10 ms	1250	A A
i^2t	$T_{vj} = 25$ °C ; 10 ms $T_{vj} = 125$ °C ; 8,3...10 ms	7800	A ² s A ² s
V_T	$T_{vj} = 25$ °C, $I_T = 150$ A	max. 1,6	V
$V_{T(TO)}$	$T_{vj} = 125$ °C	max. 0,9	V
r_T	$T_{vj} = 125$ °C	max. 5	mΩ
I_{DD}, I_{RD}	$T_{vj} = 25$ °C, $V_{RD} = V_{RRM}$ $T_{vj} = 125$ °C, $V_{RD} = V_{RRM}$	max. 1 max. 20	mA mA
t_{gd}	$T_{vj} = 25$ °C, $I_G = 1$ A; $di_G/dt = 1$ A/μs	1	μs
t_{gr}	$V_D = 0,67 * V_{DRM}$	2	μs
$(dv/dt)_{cr}$	$T_{vj} = 125$ °C	500	V/μs
$(di/dt)_{cr}$	$T_{vj} = 125$ °C; $f = 50...60$ Hz	100	A/μs
t_q	$T_{vj} = 125$ °C; typ.	150	μs
I_H	$T_{vj} = 25$ °C; typ. / max.	200	mA
I_L	$T_{vj} = 25$ °C; $R_G = 33$ Ω; typ. / max.	600	mA
V_{GT}	$T_{vj} = 25$ °C; d.c.	min. 3	V
I_{GT}	$T_{vj} = 25$ °C; d.c.	min. 150	mA
V_{GD}	$T_{vj} = 125$ °C; d.c.	max. 0,25	V
I_{GD}	$T_{vj} = 125$ °C; d.c.	max. 6	mA
$R_{th(j-s)}$	sin 180°C per Thyristor	0,63	K/W K/W
T_{vj}		-40...+125	°C
T_{stg}		-40...+125	°C
T_{sold}	Terminals, 10s max	260	°C
V_{isol}	a. c. 50 Hz; r.m.s.; 1 s / 1 min.	3600 / 3000	V~
M_s	Mounting torque to Heatsink, SI units	2,5	Nm
M_t			Nm
a			m/s ²
m		75	g
Case	SEMIPONT 5	G62	



W3C

SKUT 115



This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.