

High-Density Multiconfiguration Matrix Switch Modules

NI PXI-2531, NI PXIe-2531, NI PXI-2532, NI PXIe-2532

- 512-crosspoint matrix in a single 3U PXI slot
- 4x128 (1-wire), 8x64 (1-wire), 4x64 (2-wire), and 8x32 (2-wire) matrix configurations
- Switch capacity
 - NI 2531: Up to 60 VDC/30 VAC, 0.5 A
 - NI 2532: Up to 100 VDC/100 VAC, 0.5 A
- 2,000 cycles/s
- 32,000-step scan list for deterministic scanning
- Fully software programmable
- Onboard relay count tracking
- Multiple-module synchronization with hardware triggers
- Sixteen 2x16 matrix banks for custom matrix configurations
- Available in both PXI and PXI Express versions for optimal slot placement

Operating Systems

- Windows XP/2000/NT

Recommended Software

- LabVIEW
- LabWindows™/CVI
- Measurement Studio for Visual C++
- NI Switch Executive

Other Compatible Software

- Visual Basic
- ANSI C/C++

Driver Software (included)

- NI-SWITCH
- NI-DAQmx

Compliance

- UL (NI 2532 only)
- CE



| Module | Maximum Voltage | Maximum Current | Module Connector | Terminal Block Connector |
|---------|------------------|------------------------------|---|---|
| NI 2531 | 60 VDC, 30 VAC | 0.5 A per channel (10 W max) | 2x 150 pos, Samtec ERM8 series (optimized for ruggedness) | 2x female VHDCI (with optional screw terminal breakout) |
| NI 2532 | 100 VDC, 100 VAC | 0.5 A per channel (10 W max) | 2x 160 pos, Samtec BTE-EM (optimized for high voltage) | Standard 0.050 in. pitch headers to ribbon cables (with optional screw terminal breakout) |

Overview

The NI PXI-2531, PXIe-2531, PXI-2532, and PXIe-2532 are 512-crosspoint, high-speed matrix switch modules. With the ability to create up to a 4x2176 or 8x1088 one-wire matrix in a single PXI chassis and even larger configurations with multichassis solutions, an NI 2531/2 is ideal for high-channel-count automated test configurations. Featuring compact reed relays with switching speeds up to 2,000 cycles/s and the ability to synchronize with instruments, these modules provide maximum throughput in a test system for signals up to 100 VDC/100 VAC or 0.5 A.

Matrix Operation

The NI 2531/2 modules are general-purpose matrices used to route referenced or differential signals. Through software, you can control the modules to connect any row to any column. One of the key advantages of these matrices is you can adapt them to your switching needs. You can configure them in many different matrix configurations by using NI terminal blocks listed. For example, you can create a 4x128 one-wire matrix by using the TB-2640 terminal block with an NI 2531/2 module. You can easily transform the same module into an 8x64 one-wire matrix by using a TB-2641 terminal block. Because the NI 2531/2

modules are built with sixteen 2x16 matrices, you can also create matrix sizes outside the standard terminal block configurations. Other one-wire configurations include a 16x32 matrix or four independent 4x32 matrices. In a two-wire configuration, you can build a dual 4x32 or 16x16 matrix. Contact NI for more information on creating custom configurations.

Relay Count Tracking

An NI 2531/2 counts relay closures on each of its 512 relays. Relay counts are incremented each time a relay is actuated. You can programmatically retrieve the counts, which are stored on board the module, and use them for predictive maintenance to reduce unexpected system downtime.

Automatic Scanning

These modules maximize throughput in automated test applications by the use of scanning. Scanning improves throughput by downloading a list of up to 32,000 connections to the switch and cycling through the list using an event (trigger) without any interruption from the host processor. You can most efficiently implement scanning by mating an NI 2531/2 with an instrument such as the NI PXI-4070 6½-digit FlexDMM, which issues a trigger after each measurement.



High-Density Multiconfiguration Matrix Switch Modules

Signal Connections

You can choose from several solutions for your signal connections. Terminal blocks provide connectivity to strain-relieved 0.050 in. pitch headers ideal for ribbon cable or to 68-pin VHDCI connectors with cabled breakout accessories. You also can use mass interconnect solutions from industry leaders such as Virginia Panel and MAC Panel. Contact NI for details on these products or for information on creating your own custom connectivity solutions.

Software

All National Instruments PXI and SCXI switch modules are shipped with NI-SWITCH, an IVI-compliant driver that offers complete functionality for all switch modules. For additional assistance in configuring, programming, and managing higher-channel-count switching systems, consider using NI Switch Executive.

NI Switch Executive Software

NI Switch Executive is an intelligent switch management and routing application. With NI Switch Executive, you gain increased development productivity by interactively configuring and naming switch modules, external connections, and signal routes. You also increase test code reuse and system performance with switch programming combined with NI TestStand test management software, the LabVIEW and LabWindows/CVI development environments, and Measurement Studio for Microsoft Visual Basic 6.0. Ultimately, NI Switch Executive simplifies switch system configuration and increases test performance, thus lowering your cost of test.

Ordering Information

| | |
|--------------------|-----------|
| NI PXI-2531 | 778572-31 |
| NI PXIe-2531 | 780587-31 |
| NI PXI-2532 | 778572-32 |
| NI PXIe-2532 | 780587-32 |

Includes switch module and NI-SWITCH driver software.

NI 2531 Accessories

| | |
|---|-----------|
| NI TB-2648 4x128 terminal block for NI 2531 | 781181-01 |
| NI TB-2649 dual 4x64 terminal block for NI 2531 | 781181-02 |
| NI TB-2650 8x64 terminal block for NI 2531 | 781181-03 |
| NI TB-2651 dual 8x32 terminal block for NI 2531 | 781181-04 |

NI 2532 Accessories

| | |
|---|-----------|
| NI TB-2640 4x128 terminal block for NI 2532 | 779056-01 |
| NI TB-2641 8x64 terminal block for NI 2532 | 779056-03 |
| NI TB-2643 dual 4x64 terminal block for NI 2532 | 779056-07 |
| NI TB-2644 dual 8x32 terminal block for NI 2532 | 779056-09 |

BUY NOW

For complete product specifications, pricing, and accessory information, call 800 813 3693 (U.S.) or go to ni.com/switches.

High-Density Multiconfiguration Matrix Switch Modules

Specifications

Specifications subject to change without notice. Visit ni.com/manuals for the latest full specifications.

Input Characteristics

All input characteristics are DC, AC_{pk}, or a combination, unless otherwise specified.

Maximum switching voltage

| | |
|---------------------------------|---------------------|
| NI 2531 | |
| Channel-to-ground | 60 V |
| Channel-to-channel | 60 V, CAT I |
| NI 2532 | |
| Channel-to-ground | 100 V |
| Channel-to-channel | 100 V, CAT I |
| Maximum switching current | 2 A |
| Maximum switching current | 0.5 A (per channel) |
| Maximum carry current | 0.5 A (per channel) |
| Maximum switching power | 10 W (per channel) |

DC path resistance

| | |
|--------------------|-------|
| Initial | <1 Ω |
| End of life | >2 Ω |
| Open channel | >1 GΩ |

Transfer Characteristics

Thermal EMF

| | |
|--------------|--------|
| 1-wire | <50 μV |
| 2-wire | <20 μV |

NI-2531 bandwidth, typical

| | |
|---------------------------|--------|
| Module | 20 MHz |
| TB-2648 (4x128) | 10 MHz |
| TB-2649 (Dual 4x64) | 11 MHz |
| TB-2650 (8x64) | 11 MHz |
| TB-2651 (Dual 8x32) | 14 MHz |

NI-2532 bandwidth, typical

| | |
|---------------------------|--------|
| Module | 30 MHz |
| TB-2640 (4x128) | 10 MHz |
| TB-2643 (Dual 4x64) | 11 MHz |
| TB-2641 (8x64) | 9 MHz |
| TB-2644 (Dual 8x32) | 12 MHz |

Crosstalk, typical (50 Ω termination) – channel-to-channel

| | |
|---------------|---------|
| NI 2531 | |
| 10 kHz | <-70 dB |
| 100 kHz | <-70 dB |
| 1 MHz | <-58 dB |
| 10 MHz | <-38 dB |
| NI 2532 | |
| 10 kHz | <-89 dB |
| 100 kHz | <-73 dB |
| 1 MHz | <-54 dB |
| 10 MHz | <-36 dB |

Isolation, typical (50 Ω termination) – open channel

| | |
|---------------|--------|
| 10 kHz | >91 dB |
| 100 kHz | >71 dB |
| 1 MHz | >51 dB |
| 10 MHz | >32 dB |

Dynamic Characteristics

| | |
|--------------------------------|--------------------------|
| Maximum cycle speed | 2000 cycles/s |
| Relay operate time | 0.25 ms |
| Release time | 0.25 ms |
| Simultaneous drive limit | 40 relays |
| Expected relay life | |
| Mechanical | 10 ⁹ cycles |
| Electrical (resistive) | |
| 10 V, 100 mA | 10 ⁹ cycles |
| 25 V, 400 mA | 5x10 ⁶ cycles |
| 60 V, 160 mA | 10 ⁶ cycles |

Physical

| | |
|------------------------------|---|
| Relay type | Reed |
| Relay contact material | Rhodium |
| Dimensions | 10 by 16 cm (3.9 by 6.3 in.) single-slot, 3U |

Environment

| | |
|--------------------------------------|------------------------|
| Operating temperature | 0 to 55 °C |
| Storage temperature | -20 to 70 °C |
| Relative humidity | 5 to 85% noncondensing |
| Pollution degree | 2 |
| Approved at altitudes up to 2,000 m. | |

High-Density Multiconfiguration Matrix Switch Modules

Safety Compliance

- IEC 61010-1, EN 61010-1
- UL 61010-01, CSA 61010-1

Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326 (IEC 61326): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- AS/NZS CISPR 11: Group 1, Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions

Note: For EMC compliance, operate this product according to the documentation.

CE Compliance

This product meets the essential requirements of applicable European Directives as follows:

- 2006/95/EC; Low-Voltage Directive (safety)
- 2004/108/EC; Electromagnetic Compatibility Directive (EMC)

NI Services and Support



NI has the services and support to meet your needs around the globe and through the application life cycle – from planning and development through deployment and ongoing maintenance. We offer services and service levels to meet customer requirements in research, design, validation, and manufacturing.

Visit ni.com/services.

Training and Certification

NI training is the fastest, most certain route to productivity with our products. NI training can shorten your learning curve, save development time, and reduce maintenance costs over the application life cycle. We schedule instructor-led courses in cities worldwide, or we can hold a course at your facility. We also offer a professional certification program that identifies individuals who have high levels of skill and knowledge on using NI products.

Visit ni.com/training.

Professional Services

Our NI Professional Services team is composed of NI applications and systems engineers and a worldwide National Instruments Alliance Partner program of more than 600 independent consultants and integrators. Services range from start-up assistance to turnkey system integration. Visit ni.com/alliance.



OEM Support

We offer design-in consulting and product integration assistance if you want to use our products for OEM applications. For information about special pricing and services for OEM customers, visit ni.com/oem.



ni.com ■ 800 813 3693

National Instruments ■ info@ni.com

Local Sales and Technical Support

In offices worldwide, our staff is local to the country, giving you access to engineers who speak your language. NI delivers industry-leading technical support through online knowledge bases, our applications engineers, and access to 14,000 measurement and automation professionals within NI Developer Exchange forums. Find immediate answers to your questions at ni.com/support.

We also offer service programs that provide automatic upgrades to your application development environment and higher levels of technical support. Visit ni.com/ssp.

Hardware Services

System Assurance Programs

NI system assurance programs are designed to make it even easier for you to own an NI system. These programs include configuration and deployment services for your NI PXI, CompactRIO, or Compact FieldPoint system. The NI Basic System Assurance Program provides a simple integration test and ensures that your system is delivered completely assembled in one box. When you configure your system with the NI Standard System Assurance Program, you can select from available NI system driver sets and application development environments to create customized, reorderable software configurations. Your system arrives fully assembled and tested in one box with your software preinstalled. When you order your system with the standard program, you also receive system-specific documentation including a bill of materials, an integration test report, a recommended maintenance plan, and frequently asked question documents. Finally, the standard program reduces the total cost of owning an NI system by providing three years of warranty coverage and calibration service. Use the online product advisors at ni.com/advisor to find a system assurance program to meet your needs.

Calibration Services

NI recognizes the need to maintain properly calibrated devices for high-accuracy measurements. We provide manual calibration procedures, services to recalibrate your products, and automated calibration software specifically designed for use by metrology laboratories. Visit ni.com/calibration.

Repair and Extended Warranty

NI provides complete repair services for our products. Express repair and advance replacement services are also available. We offer extended warranties to help you meet project life-cycle requirements. Visit ni.com/services.