



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: ttsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date:

Product Name: IF SAW Filter 140 MHz (SMD 13.3mmX6.5mm)

TST Parts No.:TB0541A

Customer Parts No.: _____

Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: _____ Andy Lee

Approval by: _____ Francis Chen

Date: _____ 2007/7/20



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

IF SAW Filter 140 MHz SMD 13.3mmX6.5mm

MODEL NO.: TB0541A

Rev. No.1

A. MAXIMUM RATING:

1. Operating Temperature: -40 °C ~ +85 °C
2. Storage Temperature: -40 °C ~ +85 °C
3. Input Power Level: 10dBm


RoHS Compliant
Lead free
Lead-free soldering

B. Characteristics :

1. Ambient Temperature: 25 °

Characteristics	Value			Note.
	Min.		Max.	
Center frequency F_C MHz	139.6	140	140.4	-
Maximum Insertion loss I.L. dB	-	6.8	7.5	-
1dB Bandwidth MHz	5.80	5.95	-	-
3dB Bandwidth MHz	6.85	6.97	-	-
40dB Bandwidth MHz	-	10.40	11.10	-
Passband Ripple ($F_C \pm 2.4\text{MHz}$) MHz	-	0.40	1.00	-
Phase Linearity ($F_C \pm 2.4\text{MHz}$) (P-P) deg	-	3.6	14	-
Group Delay Ripple ($F_C \pm 2.4\text{MHz}$) nS	-	60	200	-
Group Delay at F_C uS	-	0.94	-	-
Temp Coefficient ppm/°C	-	-18	-	-

C.OUTLINE DRAWING:



Pin configuration

#A RF Input

#B RF Input ground

#G RF Output

#H RF Output ground

#C,D,E,F,J,K,M,N To be ground

□ : Week Code (Follow the table from planner each year)

Unit : mm

△ : Product / Year Code

Year	2005 2009	2006 2010	2007 2011	2008 2012
Product Code	B	b	<u>B</u>	<u>b</u>

D. Frequency Characteristics :

1. S21 Response




Fig1. Horizontal: 8MHz/Div Vertical: 10dB/Div

2. Pass band Ripple and Group Delay Ripple




Fig2. Horizontal: 1.2MHz/Div; Vertical: 1dB/Div,






Fig3. Horizontal: 1.2MHz/Div; Vertical: 100nS/Div,

E. TEST FIXTURE :




F. PCB FOOTPRINT



G. PACKING:

1. REEL DIMENSION



2. TAPE DIMENSION

