



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date:

Product Name: SAW Filter 495MHz SMD 5.0x5.0mm

TST Parts No.:TB0707A

Customer Parts No.: _____

Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: _____ Andy Yu *Andy Yu*

Approval by: _____ Francis Chen *Francis Chen*

Date: _____ 2008/11/14



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 495 MHz SMD 5.0mmX5.0mm

MODEL NO.: TB0707A

preliminary

A. MAXIMUM RATING:

1. Operating Temperature: -25°C to +70°C
2. Storage Temperature: -40°C to +85°C
3. Maximum Input Power : 10dBm

RoHS Compliant
Lead free
Lead-free soldering


B. ELECTRICAL CHARACTERISTICS:

1. Ambient Temperature: 25 °


Item		Min.	Typical	Max.
Center frequency	Fc MHz	-	495	-
Insertion loss at Fc	dB	-	14.7	18
Bandwidth at -1.0dB	MHz	30.0	33.0	-
Bandwidth at -6.0dB	MHz	-	39.0	42.0
Bandwidth at -25.0dB	MhZ		46.0	50.0
Amplitude Ripple (Fc ± 15 MHz)	dB	-	0.4	1
Group Delay Ripple (Fc ± 15 MHz)	nS	-	30	100
Absolute Group delay at Fc	nS	-	310	-
Temp Coefficient	ppm/°C	-	-0.18	-

C. FREQUENCY CHARACTERISTICS :


1.S21 Response: (span:400MHz)




2.S21 Response: (span:50MHz)



3.S11 Smith-Chart: (span:400MHz)




4.S22 Smith-Chart: (span:400MHz)




D. MEASUREMENT CIRCUIT

1. Single ended input 50 ohm to Single ended Output 50 ohm



C1=10.5pF, L1=5.6nH, C2=10pF, L2=5.6nH

E. OUTLINE DRAWING:



Pin A : RF Input

Pin E : RF Output

Pin B,C,D,F,G,H : Ground


Unit: mm

□ : Week Code (Follow the table from planner each year)

△ : Product / Year Code

Year	2005 2009	2006 2010	2007 2011	2008 2012
Product Code	B	b	<u>B</u>	<u>b</u>


F. PCB Footprint



Unit: mm


G. PACKING:

1. REEL DIMENSION



Unit: mm

2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE:

