




Never stop thinking

[Home](#) > [Microcontrollers](#) > [Development Tools, Software and Training](#) > [C166/XC166 Development Tools and Software](#) > [Starter Kits, Evaluation Boards and Application Kits](#) > **SK-XC161 Starter Kit**

SK-XC161 Starter Kit



MCU Derivates: SAK-XC161CJ-16FF

CPU Clock: 40 MHz

On-Chip Memory:

8 kByte SRAM,
128 kByte FLASH

On-Boards Memory:

2 x 512kB SRAM (+ optional: 2 x up to 1 MB Flash)

Interfaces:

- SUB-D9 connector for ASC0 Interface via RS 232 port
- 10pin header (2x5) for ASC1 Interface (second RS 232 port)
- Sub-D25 connector (on-board wiggler) and 16-pin header for JTAG interface
- 10pin header (2x5) for J1850 Interface
- Two 10pin (2x5) Headers connected to the TwinCAN Module
- Six additional connectors (bus expansion, ADC/GPIO, peripherals and CAPCOM unit)

Includings:

- Technical Documentation: allgemein: e.g. User manuals for the System and Peripheral units, Architecture manual, Application notes, Errata sheets, Data Sheets, Board Documentation (pdf-version),
- Low Level Driver Software (LLD),
- Evaluation Versions of Development Tools: e.g. Compiler, Debugger, Operating System from Tool Partners and DAVE Derivative Implementation Files (DIP), MemTool (Flash Programming Tool),
- Training Documentation, Demo Programs, Hands On Training (HOT),
- parallel cable,
- Starter Kit Manual.

Order Nr.: B158-H8048-X-X-7600