





Tous droits strictement réservés. Reproduction ou communication à des tiers interdite sans queique autorisation écrite de l'ingénieur propriétaire. Property of FCI. Droits de reproduction FCI.

FCI

All rights strictly reserved. Reproduction or issue to third parties in any form without written permission is prohibited. Property of FCI. Copyright FCI.



PERFORMANCE CHARACTERISTICS

- CURRENT RATING: 1.5A AT 20°C (FULLY LOADED)
1 A AT 70°C (FULLY LOADED)
- RATED VOLTAGE : 500 V AC (CONT /CONT)
- OPERATING TEMPERATURE : -55°C TO 125°C
- CONTACT RESISTANCE 20 MΩ MAX
- INSERTION FORCE : 0.75N MAX/CONT
- EXTRACTION FORCE : 0.15N MIN/CONT
- INSULATION RESISTANCE : 10⁴ MΩ MIN

- NOTES**
- LEAD FREE INDICATOR : LF-LEAD FREE
 - PERFORMANCE LEVEL INDICATOR (REF: DWG NO. BSC -201844.003)
 - THIS PRODUCT IS CSA APPROVED. THIS PRODUCT IS UL RECOGNIZED.
 - FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING :BS.A.201572.001
 - THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

rev	ecn no	dr	date
A	CONVERSION REVISION 04	HN	14-09-01
B	104-0114	HEX	27-11-04
C	DG05-0297	Mason	05-08-05
-	-	-	-
-	-	-	-
-	-	-	-

Material		Spec ref	
Mat code		tolerance	projection
Heat treat		100CA±0.2 100C 200CA±0.1 200C 200LE±0.1 200C	MM
Plating/Finish		ANALYSIS W/ WETEN	
Dr	M. Fret	31-10-97	size A4
Eng			Scale 2.000
Chr			Product family
Appr			Model Name HM2S30PE5101
			ECN DG05-0297
			Model Revision
			REL Level
FCI	title	MILLIPACS 2/TYPE C(W/O LOCK.PEG) /SHIELDED	Rev. C
Part no		BSC201907010	
Proj/E file	catalog	HM2S30PE5101	CUSTOMER DRAWING

PDM: Rev.C STATUS: Released Printed: Aug 26, 2005