Serial Instrument Control Interfaces for USB

NI USB-232 Series, NI USB-485 Series

- · Compatible with standard PC serial port
- 1, 2, and 4-port versions
- · Handle RTS/CTS hardware handshake lines
- 128 B transmit and receive FIFOs
- 5,6,7, or 8 data bits

NI USB-485

- RS-485 or RS-422 interface
- 460.8 kb/s maximum transfer rate
- · Communicates with up to 31 devices
- Automatic transceiver-control mode for 2-wire RS-485 devices
- · Software-selectable biasing
- · Cable lengths up to 1.2 km (4,000 ft)

- · RS-232 interface
- · 230.4 kb/s maximum transfer rate
- Software-selectable DTE or DCE transceiver modes (2 and 4-port models only)

Operating Systems

Windows 2000/XP

Recommended Software

- LabVIEW[™]
- LabWindows[™]/CVI[™]
- Measurement Studio™

Other Compatible Software

- C/C+
- Visual Basic
- Any package with the Microsoft serial driver interface

Driver Software (included)

NI-Serial



Overview

The National Instruments USB-232 and USB-485 transform your Universal Serial Bus (USB) port into asynchronous serial ports for communication with serial devices. The NI USB-232 and USB-485 are available in either 1, 2, or 4-port versions and use standard RS-232, RS-422, or RS-485 communications. All products include driver software for Windows 2000/XP. You can install and use the USB-232 and USB-485 as standard serial ports from your existing applications or with applications written with NI-VISA.

Additionally, the USB-232 2 and 4-port versions feature software-selectable DTE or DCE transceiver modes, as well as an automatic transceiver detection mode, or Auto232. The USB-485 features software selectable biasing; therefore, you can turn biasing on and off for each port through software.

Development environments, such as Visual Basic, Visual C++, and Excel, as

INFO CODES For more information or to order products online, visit ni.com/info and enter: usb232 usb485 **BUY ONLINE!**

well as National Instruments LabVIEW, LabWindows/CVI and Measurement Studio, can access the serial ports using standard serial I/O functions.

Specifications

FIFO size Maximum transfer rate 460.8 kb/s (RS-485); 230.4 kb/s (RS-232) USB connector (1 port) .. captive cable with USB series A plug USB connector (2 and 4 port). USB standard series B connector Serial connectors. Class A

Power Requirements

USB-232 (100 mA typ, 200 mA max), 5 VDC (from USB) USB-232/2 (200 mA tvp. 500 mA max). USB-232/4 (300 mA typ, 500 mA max), USB-485 (175 mA typ, 500 mA max) USB-485/2 (300 mA typ, 500 mA max),

USB-485/4 (225 mA typ, 500 mA max) +12 VDC (from supply furnished).

Operating Environment

Ambient temperature. 0 to 70 °C

Relative humidity 10 to 90%, noncondensing

Storage Environment

-40 to 80 °C Ambient temperature (1 port)... Ambient temperature (2 and 4 port)..... -40 to 85 °C

Relative humidity. 10 to 90%, noncondensing

Electrostatic Discharge Protection

Case contact and air discharge. ±4 kV ±15 kV (HBM) RS-232 and RS-435 data lines .

Ordering Information

Model	Serial Port	Number of Ports	Part Number
NI USB-232	RS-232	1	778472-01
NI USB-232/2	RS-232	2	778473-02
NI USB-232/4	RS-232	4	778473-04
NI USB-485	RS-485/RS-422	1	778475-01
NI USB-485/2	RS-485/RS-422	2	778476-02
NI USB-485/4	RS-485/RS-422	4	778476-P4*

*External 12 VDC power supply included

P = Power Cord Type 0 = U.S. 120 VAC

4 = Universal Euro 240 VAC 5 = North American 240 VAC

2 = Swiss 220 VAC 3 = Australian 240 VAC

6 = United Kingdom 240 VAC



Global Services and Support

NI has the services and support to meet your needs around the globe and through the application life cycle – from planning and development through deployment and ongoing maintenance – and tailored for customer requirements in research, design, validation, and manufacturing.

We have direct operations in more

than 37 countries and distributors in another

12 locations. Our local sales and support representatives are degreed engineers, ready to partner with you to find solutions that best fit your needs.

Local Sales and Technical Support

In offices around the globe, our staff is local to the country so that you have access to field engineers who speak your language and are available to consult on your unique needs. We also have a worldwide support organization staffed with Applications Engineers trained to quickly provide superior technical assistance. Use our online Request Support interface (ni.com/support) to define your question, then speak to or e-mail an Applications Engineer, or access more than 14,000 worldwide measurement and automation professionals within NI Developer Exchange Discussion Forums. ni.com/support also provides immediate answers to your questions through self-help troubleshooting, product reference, and application development resources. For advanced technical support and software maintenance services, sign up for Premier Support, a program that provides expanded hours of support availability and expedited phone/e-mail response time (typically four business hours).

Training and Certification

NI recognizes that both initial instruction and ongoing education contribute to your success. NI provides a variety of training alternatives, from self-paced tutorials and interactive CDs, to worldwide hands-on courses taught by experienced instructors – all designed so that you can choose how to learn about our products. Further, NI offers certifications acknowledging individual expertise in working with NI products and technologies. Visit *ni.com/training* for more information.

Professional Services

Our Professional Services team consists of National Instruments Applications Engineers, NI Consulting Services, and a worldwide Alliance Program (a network of 600 independent consultants and integrators). Our Professional Services team can offer services ranging from basic start-up assistance and collaborative development with your engineers, to turnkey system integration and maintenance of your system. In addition to our NI Alliance Partners, we have developed global relationships with many industry partners that range from computer software and hardware companies, such as Microsoft, Dell, Siemens, and Tektronix. By collaborating with these companies, you receive a complete spectrum of solutions – from components to turnkey systems. Find the Alliance Program member directory at *ni.com/alliance*

Product Services

NI GPIB products are warranted against defects in workmanship and material for one year from the date of shipment. To help you meet project lifecycle requirements, NI offers extended warranties for an additional charge. NI provides complete repair services for our products. Express repair and advanced replacement services are also available. Or, order your software and hardware installed in PXI and PXI/SCXI™ systems with NI Factory Installation Services.

Ordering Made Easy

Visit *ni.com/products* to browse product specifications, make comparisons, or access technical representatives via online chat or telephone. Worldwide customers can use a purchase order or credit card to buy in local currency and receive direct shipments from local NI offices. Our North American Customer Service Representatives are available Monday through Friday between 7 a.m. and 7 p.m. Central Time. Outside North America, please contact the NI office in your country

Order Status and Service Requests

National Instruments brings you real-time status on current orders at *ni.com/status* Similarly, find out the status of open technical support incidents or hardware repair requests at *ni.com/support/servicereq*



National Instruments • Tel: (512) 683-0100 • Fax: (512) 683-9300 • info@ni.com

This document represents a commitment from National Instruments to the environment.
 2003 National Instruments Corporation. All rights reserved. Product and company names listed are trademarks or trade names of their respective companies.