



Peripheral/Power Drivers

LM75451, LM75452, LM75453, LM351 dual peripheral driver




general description

These devices are general purpose dual peripheral drivers, each capable of sinking two independent 300 mA loads to ground. In the off state (or with $V_{CC} = 0V$) the outputs will withstand 30V. Inputs are fully DTL/TTL compatible. The LM75451 meets or exceeds the specifications for the SN75451 and is a pin-for-pin replacement. The LM75452 and LM75453 meet or exceed the specifications for SN75452 and SN75453, respectively, and are pin-for-pin replacements.


features

- High speed
- Both outputs can sink 300 mA simultaneously
- Withstands 30V on output with $V_{CC} = 0V$ for power strobing applications
- Input clamp diodes
- Two separate drivers per package


schematic diagrams




connection diagrams



Order Number LM75451N
See Package 20



Order Number LM75452N
See Package 20



Order Number LM75453N or LM351
See Package 20

truth tables

Positive logic: AB=X		
A	B	OUTPUT X*
0	0	0
1	0	0
0	1	0
1	1	1

* "0" Output $\leq 0.7V$
"1" Output $\leq 100 \mu A$

Positive logic: $\overline{AB}=X$		
A	B	OUTPUT X*
0	0	1
1	0	1
0	1	1
1	1	0

* "0" Output $\leq 0.7V$
"1" Output $\leq 100 \mu A$

Positive logic: $A + B = X$		
A	B	OUTPUT X*
0	0	0
1	0	1
0	1	1
1	1	1

* "0" Output $\leq 0.7V$
"1" Output $\leq 100 \mu A$

absolute maximum ratings (Note 1)

Supply Voltage V _{CC}	7V	Continuous Total Power Dissipation (Note 3)	800 mW
Input Voltage	5.5V	Operating Free Air Temperature Range	0°C to 70°C
Output Voltage (Note 2)	30V	Storage Temperature Range	-65°C to 150°C
Continuous Output Current	300 mA	Lead Temperature (soldering, 10 sec)	300°C

electrical characteristicsThe following apply for 0°C ≤ T_A ≤ 70°C, V_{CC} = 5V ±5%, unless otherwise specified. (Note 4)

PARAMETER	LOGIC INPUT	OUTPUT	SUPPLY VOLTAGE	COMMENTS	MIN	TYP	MAX	UNIT
Logic "1" Input Voltage	V _{IN}	30V (300 mA)	4.75V	Output ≤ 100 μA (<0.7V)	2		0.8	V
Logic "0" Input Voltage	V _{IN}	300 mA (30V)	4.75V	Output ≤ 0.7V (<100 μA)			100	μA
Output Leakage Currents	2V (0.8V)	30V 30V	4.75V 0V				100	μA
Output LOW Voltages	0.8V (2V) 0.8V (2V)	100 mA 300 mA	4.75V 4.75V			0.25 0.5	0.4 0.7	V
Logic "1" Input Currents	2.4V 5.5V		5.25V 5.25V				40 1	μA mA
Logic "0" Input Current	0.4V		5.25V			-1	-1.6	mA
Supply Currents:								
Output Low				Per Package	48	65		mA
LM75451	0V		5.25V	Per Package	51	71		mA
LM75452	5V		5.25V	Per Package	50	68		mA
LM75453	0V		5.25V	Per Package				
Output High				Per Package	7	11		mA
LM75451	5V		5.25V	Per Package	9	14		mA
LM75452	0V		5.25V	Per Package	9	11		mA
LM75453	5V		5.25V	Per Package				
Input Diode Clamp Voltage	-12 mA		5V	T _A = 25°C			-1.5	V
The following apply for V _{CC} = 5V, T _A = 25°C								
Propagation Delay Times:								
Input to Output HIGH				(Note 5)	11	25		ns
LM75451 & LM75453				(Note 5)	13	35		ns
LM75452								
Input to Output LOW				(Note 5)	16	25		ns
LM75451 & LM75453				(Note 5)	19	.35		ns
LM75452								
Output Risetime					4			ns
Output Falltime					10			ns

Note 1: All voltage values are with respect to ground terminal. Positive current is defined to be current into referenced pin.

Note 2: Maximum voltage to be applied to either output in the off state.

Note 3: The maximum junction temperature is 150°C. For operating at elevated temperatures, the package must be derated based on a thermal resistance of 110°C/W θ_{JA}.

Note 4: Test conditions in parentheses pertain to LM75452, other test conditions pertain to LM75451A and LM75453.

Note 5: Delays measured with 50Ω load to 10V, 15 pF total load capacitance; measured from 1.5V input to 50% of output.