



2SA1201

PNP SILICON TRANSISTOR


SILICON PNP EPITAXIAL TRANSISTOR

DESCRIPTION

The UTC **2SA1201** is designed for power amplifier and voltage amplifier applications.

FEATURES

- *High voltage: $V_{CE0} = -120V$
- *High transition frequency: $f_T = 120MHz$ (typ.)
- * $P_c = 1$ to $2 W$ (mounted on ceramic substrate)



ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
2SA1201L-x-AB3-R	2SA1201G-x-AB3-R	SOT-89	B	C	E	Tape Reel

Note: Pin Assignment: B: BASE C: COLLECTOR E: EMITTER

<p>2SA1201L-x-AB3-R</p> <p>(1) Packing Type (2) Package Type (3) Rank (4) Lead Free</p>	<p>(1) R: Tape Reel (2) AB3: SOT-89 (3) x: refer to Classification of h_{FE} (4) G: Halogen Free, L: Lead Free</p>
---	---

■ ABSOLUTE MAXIMUM RATINGS ($T_A=25^\circ\text{C}$)

PARAMETER	SYMBOL	RATINGS	UNIT
Collector-Base Voltage	V_{CB0}	-120	V
Collector-Emitter Voltage	V_{CEO}	-120	V
Emitter-Base Voltage	V_{EBO}	-5	V
Collector Current	I_C	-800	mA
Base Current	I_B	-160	mA
Collector Power Dissipation	P_C	500	mW
		1000 (Note 2)	mW
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature	T_{STG}	-55 ~ +150	$^\circ\text{C}$

- Note: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.
 2. Mounted on cermic substrate(250mm² × 0.8t)

■ ELECTRICAL CHARACTERISTICS($T_A=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector to Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = -10\text{mA}, I_B = 0$	-120			V
Emitter to Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = -1\text{mA}, I_C = 0$	-5			V
Collector Cut-Off Current	I_{CBO}	$V_{CB} = -120\text{V}, I_E = 0$			-0.1	μA
Emitter Cut-Off Current	I_{EBO}	$V_{EB} = -5\text{V}, I_C = 0$			-0.1	μA
DC Current Gain	h_{FE}	$V_{CE} = -5\text{V}, I_C = -100\text{mA}$	80		240	
Collector to Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C = -500\text{mA}, I_B = -50\text{mA}$			-1.0	V
Base to Emitter Voltage	V_{BE}	$V_{CE} = -5\text{V}, I_C = -100\text{mA}$			-1.0	V
Transition Frequency	f_T	$V_{CE} = -5\text{V}, I_C = -100\text{mA}$		120		MHz
Collector Output Capacitance	C_{OB}	$V_{CB} = -10\text{V}, I_E = 0, f = 1\text{MHz}$			30	pF

■ CLASSIFICATION OF h_{FE}

RANK	O	Y
RANGE	80 - 160	120 - 240

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.