


TYPES 2N339, 2N340, 2N341, 2N342, 2N342A, 2N343  
N-P-N GROWN SILICON TRANSISTORS




absolute maximum ratings at 25°C case temperature (unless otherwise noted)

*Collector Current	60 ma
*Total Device Dissipation (see note 1)	1000 mw
*Total Device Dissipation at 100°C Case Temperature (see note 1)	400 mw
*Total Device Dissipation at 125°C Case Temperature (see note 1)	200 mw
*Storage and Operating Collector Junction Temperature Range	-65° to +150°C
Storage and Operating Collector Junction Temperature Range (TI Guarantee)	-65° to +175°C

electrical characteristics at 25°C case temperature (unless otherwise noted)

parameter	test conditions	2N339		2N340		2N341		2N342		2N342A		2N343		unit
		min	max	min	max	min	max	min	max	min	max	min	max	
$I_{CBO}$ Collector Cutoff Current	$V_{CB} = 30\text{ v}$ $I_E = 0$		1		1		1		1		1		1	$\mu\text{a}$
$I_{CBO}$ Collector Cutoff Current	$V_{CB} = 30\text{ v}$ $I_E = 0$ $T_C = +150^\circ\text{C}$		250		250		250		250		250		250	$\mu\text{a}$
$V_{CB0}$ Collector-Base Breakdown Voltage	$I_C = 50\ \mu\text{a}$ $I_E = 0$	55		85		125		60		85		60		v
$V_{CE0}$ Collector-Emitter Breakdown Voltage	$I_C = 100\ \mu\text{a}$ $I_B = 0$	55		85		85		60		85		60		v
$V_{EB0}$ Emitter-Base Breakdown Voltage	$I_E = 100\ \mu\text{a}$ $I_C = 0$	1		1		1		1		1		1		v
$r_{CE(sat)}$ DC Collector-Emitter Saturation Resistance	$I_B = 3\text{ ma}$ $I_C = 20\text{ ma}$		300		350		400		350		350		350	ohm
$h_{fb}$ AC Common-Base Forward Current Transfer Ratio	$V_{CB} = 10\text{ v}$ $f = 1\text{ kc}$	-0.9	-0.989	-0.9	-0.989	-0.9	-0.989	-0.9	-0.97	-0.9	-0.97	-0.966	-0.989	—
$h_{ib}$ AC Common-Base Input Impedance	$V_{CB} = 10\text{ v}$ $f = 1\text{ kc}$		30		30		30		30		30		30	ohm
$h_{ob}$ AC Common Base Output Admittance	$V_{CB} = 10\text{ v}$ $f = 1\text{ kc}$		2		2		2		2		2		2	$\mu\text{mho}$
$h_{rb}$ AC Common Base Reverse Voltage Transfer Ratio	$V_{CB} = 10\text{ v}$ $f = 1\text{ kc}$		300		300		300		300		300		300	—
			$\times 10^{-6}$		$\times 10^{-6}$		$\times 10^{-6}$		$\times 10^{-6}$		$\times 10^{-6}$		$\times 10^{-6}$	



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.