

E-Series 2-Way 180° Power Divider 40 - 1000 MHz

ESCJ-2-6

V3.00

Features

- 2 Way
- 180°
- Surface Mount

Specifications @ 25°C

Frequency Range	40 - 1000 MHz	
Insertion Loss	Typical	Maximum
40 - 400 MHz	1.0 dB	1.5 dB
400 - 500 MHz	1.2 dB	2.0 dB
500 - 1000 MHz	1.5 dB	3.5 dB
Isolation	Typical	Minimum
40 - 400 MHz	22 dB	19 dB
400 - 500 MHz	21 dB	18 dB
500 - 1000 MHz	20 dB	17 dB
Amplitude Unbalance	Maximum	
40 - 400 MHz	0.5 dB	
400 - 500 MHz	0.8 dB	
500 - 1000 MHz	1.2 dB	
Phase Unbalance	Maximum	
40 - 400 MHz	5°	
400 - 500 MHz	9°	
500 - 1000 MHz	14°	

Operating Characteristics

Impedance	50 Ohms Nominal
Output	50 Ohms Unbalanced
Input	100 Ohms Balanced


Ordering Information

Part No.	Packaging
ESCJ-2-6	Tube
ESCJ-2-6TR	Forward Tape & Reel

Absolute Maximum Ratings

Parameter	Absolute Maximum
Maximum Power Rating	1 Watt
Internal Load Dissipation	0.125 Watt
Pin Temp (10 sec)	260°C
Storage Temperature	-55°C to 100°C

SM-22



Pin Configuration

Function	Pin No.
Ground	2,5
Input	4
Port 1	3
Port 2	1

Specifications Subject to Change Without Notice.

M/A-COM, Inc.

North America: Tel. (800) 366-2266 ■ Asia/Pacific: Tel. +81 (03) 3226-1671 ■ Europe: Tel. +44 (1344) 869 595
Fax (800) 618-8883 Fax +81 (03) 3226-1451 Fax +44 (1344) 300 020