



# MI-200<sup>TM</sup>

## Military DC-DC Converters 50 to 100W

### Product Highlights

The MI-Series is designed for military applications and is based on Vicor's 1st Generation family of zero-current/zero-voltage switching, component level DC-DC converters. Operating at frequencies in excess of 1MHz, the MI-Series offers state-of-the-art performance in terms of power density, efficiency, noise, ease of use, and reliability.

All units are manufactured in ISO 9001-registered facilities. Full epoxy encapsulation in Vicor's industry standard package enables the MI-Series to meet MIL-STD-810 environmental requirements for humidity, fungus, salt, fog, explosive atmosphere, acceleration, vibration, and shock. (See page 32.)

Standard features such as wide output trimming/programming, current limiting, remote sense, output inhibit, and latching OVP and OTP combine to offer a high degree of protection, versatility, and reliability for military power systems.

### Features

- ✦ Inputs:
  - 28Vdc per MIL-STD-704D/E
  - 155Vdc per MIL-STD-1399A
  - 270Vdc per MIL-STD-704D/E
- ✦ Single output: 2 – 48Vdc
- ✦ Up to 23W/in<sup>3</sup>
- ✦ MIL-STD-810 environments
- ✦ Up to 90% efficiency
- ✦ Remote sense
- ✦ Current limit
- ✦ OVP and thermal shutdown
- ✦ Power boosters for higher power outputs
- ✦ ZVS/ZCS power architecture
- ✦ Low noise FM control
- ✦ Size: 4.6" x 2.4" x 0.5" (116,8 x 61,0 x 12,7mm)

### Converter/Booster Specifications

(At  $T_{BP} = 25^{\circ}\text{C}$ , nominal line and 75% load, unless otherwise specified)

PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
<b>Input Characteristics</b>					
Input voltage range	See input voltage chart				
No load power dissipation	1.35		2.0	Watts	
<b>Output Characteristics</b>					
Set point accuracy		0.5	1.0	% Vnom	
Load/line regulation		0.05	0.2	% Vnom	LL to HL, 10% to FL
		0.2	0.5	% Vnom	LL to HL, NL to 10%
Output temperature drift		0.01	0.02	%/°C	
Output noise - pp		1.0	1.5	% Vnom	} Whichever is greater 20MHz BW
		100	150	mV	
Output voltage trimming <sup>(1)</sup>	50		110	% Vnom	
Remote sense compensation		0.5		Vdc	
OVP set point <sup>(2)</sup>	115	125	135	% Vnom	Latching
Current limit	105		125	% Inom	Auto restart
Short circuit current <sup>(3)</sup>	20		130	% Inom	
<b>Control Pin Characteristics</b>					
Gate-in high threshold		6		Vdc	
Gate-in low threshold	0.65			Vdc	
Gate-in low current			6	mA	
Power sharing accuracy	0.95		1.05		
<b>Isolation Characteristics</b>					
Isolation (input to output)	3,000			Vrms	
Isolation (output to baseplate)	500			Vrms	
Isolation (input to baseplate)	1,500			Vrms	
Input/output capacitance		50	75	pF	
<b>Environmental (MIL-STD-810)</b>					
Altitude - method 500.2	70,000			feet	Procedure II
Humidity - method 507.2	86/240			%/hours	Procedure 1, cycle 1
Acceleration - method 513.3	9			g's	Procedure 2
Vibration - method 514.3	20			g's	Procedure 1, category 6
Shock - method 516.3	40			g's	Procedure 1
<b>Reliability (MIL-HDBK-217F)</b>					
25°C Ground Benign: G.B.		2,478,477		hours	
50°C Naval Sheltered: N.S.		584,920		hours	
65°C Airborne Inhabited Cargo: A.I.C.		483,303		hours	
<b>Thermal Characteristics</b>					
Efficiency		80-90		%	
Baseplate to sink		0.07		°C/W	With thermal pads
Thermal shutdown	90	95	105	°C	Latching
Baseplate operating temperature			+85	°C	See product grade
Storage temperature			+100	°C	See product grade
<b>Mechanical Specifications</b>					
Weight		6.0 (170)		ounces (grams)	

<sup>(1)</sup> 10V, 12V, and 15V outputs, standard trim range  $\pm 10\%$ . Consult factory for wider trim range.

<sup>(2)</sup> No over temperature or voltage protection in booster modules.

<sup>(3)</sup> Output voltages of 5V or less incorporate foldback current limiting; outputs of 10V and above provide constant current limiting.

