

PCI-1611U

4-port RS-422/485 Universal PCI Communication Card with Isolation & EFT Surge Protection



RoHS
FCC CE

Features

- PCI bus Specification 2.2 compliant
- Speeds up to 921.6 kbps
- 4-port RS-422/485
- 16PCI954 UARTs with 128-byte FIFOs standard
- I/O address automatically assigned by PCI Plug & Play
- OS supported: Windows® 98/ME/2000/XP/XP Embedded, Linux
- Interrupt status register for increased performance
- Space reserved for termination resistors
- Automatic RS-485 data flow control
- Powerful and easy to use utility (ICOM Tools)
- Universal PCI (Supports 3.3 V or 5 V PCI bus signal)
- 2,500 V_{DC} EFT Surge Protection
- 2,000 V_{DC} Isolation Protection

Introduction

PCI-1611U is a 4-port RS-422/485 PCI communication card that is compatible with the PCI 2.2 bus specification. The PCI-1611U provides many functions such as four independent RS-422/485 ports with isolation protection, high transmission speed of 921.6 kbps, and EFT surge protection. PCI-1611U also comes with high-performance 16PCI954 UARTs with a 128-byte FIFO to reduce CPU loading. These components make your system more stable and reliable. Thus, the PCI-1611U is especially suitable for multitasking environments.

To improve the performance of the system, the PCI-1611U allows transmission rates up to 921.6 kbps, and to further increase reliability, the PCI-1611U offers EFT surge protection technology, protecting your system from abrupt high voltages up to 2,500 V_{DC}. Besides, Advantech also provides a convenient utility program, ICOM Tools, to help you test the PCI card's performance by analyzing the port status. The easy-to-use graphical user interface of ICOM Tools works like a PC-based data scope that lets you set trigger conditions to capture communication data and monitor a signal's status. ICOM Tools is applicable to all series of Advantech ICOM cards.

Specifications

General

- **Bus Type** Universal PCI V 2.2
- **Certifications** CE, FCC class A
- **Connectors** 1 x DB37-F
- **Dimensions** 185 x 100 mm (7.3" x 3.9")
- **Power Consumption** 600 mA @ 5 V

Communications

- **Communication Controller** 16PCI954
- **Data Bits** 5, 6, 7, 8
- **Data Signals** RS-422: Tx+, Tx-, Rx+, Rx-, RTS+, RTS-, CTS+, CTS-, GND
RS-485: Data+, Data-, GND
- **FIFO** 128 bytes
- **Flow Control** RTS/CTS, Xon/Xoff
- **IRQ** Assigned by Plug & Play
- **Parity** None, even, odd
- **Speed** 50 bps ~ 921.6 kbps
- **Stop Bits** 1, 1.5, 2

Protection

- **ESD Protection** 16 kV
- **Isolation Protection** 2,000 V_{DC}
- **EFT Surge Protection** 2,500 V_{DC}

Software

- **Bundled Software** ICOM Tools
- **Driver Support** Windows 98/ME/2000/XP/XP Embedded, Linux

Environment

- **Operating Temperature** 0 ~ 65° C (refer to IEC 68-2-1, 2), (32 ~ 149° F)
- **Humidity (Operating)** 5 ~ 95 % Relative Humidity, non-condensing (refer to IEC 68-2-3)
- **Storage Temperature** -25 ~ 85° C (-13 ~ 185° F)

Ordering Information

- **PCI-1611U** 4-port RS-422/485 Universal PCI Communication Card, w/Isolation & EFT Surge Protection (30 cm DB37 to 4 DB25 cable included)
- **PCI-1611U/9** 4-port RS-422/485 Universal PCI Communication Card, w/Isolation & EFT Surge Protection (30 cm DB37 to 4 DB9 cable included)