



Sparkle Power Inc.

A Leading Power Supply manufacturer
Web site: www.sparklepower.com



ATX-350GU (For Pentium 4 and Athlon XP) 350 Watts ATX12V Switching Power Supply

Features

- Complied with ATX and ATX12V standard
- High efficiency and reliability
- Remote On/Off function
- Internal 12V DC fan included
- Noise Killer (Thermal fan speed control function)
- Low noise and ripple
- Complies with FCC part 15 subpart J class B and CISPR 22 Class B
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Approved by UL 1950, CSA C22.2 Level 3, CB

Input Characteristics

Input Range: 95~132/180~264V AC, Manual-select
Frequency: 47~63Hz
Input Current: 10A (RMS) @115V AC, 5A (RMS) @230VAC
Inrush Current: 80A Max for 132V AC Cold Start

Specification

- **Temperature Range:** Operating 0° C ~ +25° C on full load; storage & shipping -20° C ~ +65° C
- **Humidity:** 90% on operating and 95% on storage
- **Dielectric Withstand:** Primary to frame ground 1800V AC for 1 second
- **Efficiency:** 65% at minimum measured at nominal AC main voltage and frequency with maximum load on all output
- **Rise Time:** Less than 20ms
- **Hold-up Time:** 16ms minimum at 115V/60Hz; 20ms minimum at 230V/50Hz input voltage
- **Power Good Signal:** Power on delay time 100 ms to 500 ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA
- **MTBF:** 100,000 hours on maximum load at +25° C degree
- **Dimension (WxHxL):** 150x86x140mm/5.9"x3.4"x5.5" inches

Output Characteristics

| Output Voltage | Minimum Load | Maximum Load | Load Reg. | Line Reg. | Ripple & Noise |
|----------------|--------------|--------------|-----------|-----------|----------------|
| +3.3V | 0.2A | 15.15/20A | ± 5% | ± 1% | 80mV P-P |
| +5V | 2.0A | 32/28.8A | ± 5% | ± 1% | 60mV P-P |
| +12V | 0.0A | 16A | ± 5% | ± 1% | 150mV P-P |
| -5V | 0.0A | 0.3A | ± 10% | ± 2% | 120mV P-P |
| -12V | 0.0A | 0.8 A | ± 10% | ± 2% | 150mV P-P |
| +5Vsb | 0.0A | 2.0 A | ± 5% | ± 1% | 60mV P-P |

*+5V and +3.3V total output not exceed 210W
 *When +3.3V is load to 20A, the +5V maximum load is 28.8A
 *When +3.3V is load to 15.15A, the +5V maximum load is 32A
 *+3.3V, +5V, and +12V total output not exceed 330W

Sparkle Power Inc.
Main Office
 1000 Rock Avenue
 San Jose, CA 95131
 TEL: 408-519-8888
 FAX: 408-519-9999
 E-MAIL: info@sparklepower.com

Sparkle Power Inc.
Los Angeles Office
 17071 Green Drive
 City of Industry, CA 91745
 TEL: 626-839-7180
 FAX: 626-839-3395

Sparkle Power Inc.
Colorado Office
 1316 Indian Paintbrush Lane
 Longmont, CO 80503
 TEL: 303-776-3281
 FAX: 303-776-7645

