

A Series Crystal



- **HC-49/U Thru-Hole Crystal**
- **RoHS Compliant Available**
- **Wide Frequency Range**
- **AT Cut**
- **Resistance Weld**




ELECTRICAL SPECIFICATIONS:

Frequency Range	1.8432MHz to 200.000MHz
Frequency Tolerance / Stability	(See Part Number Guide for Options)
Operating Temperature Range	(See Part Number Guide for Options)
Storage Temperature	-55°C to +125°C
Aging	±5ppm / first year Max
Shunt Capacitance	7pF Max
Load Capacitance	20pF Standard (See Part Number Guide for Options)
Equivalent Series Resistance	See ESR Chart
Mode of Operation	Fundamental, 3 rd OT or 5 th OT
Drive Level	2mW Max
Shock	MIL-STD-883, Meth 2002, Cond B
Solderability	MIL-STD-883, Meth 2003
Solvent Resistance	MIL-STD-202, Meth 215
Vibration	MIL-STD-883, Meth 2007, Cond A
Gross Leak Test	MIL-STD-883, Meth 1014, Cond C
Fine Leak Test	MIL-STD-883, Meth 1014, Cond A

ESR CHART:

Frequency Range	ESR (Ohms)	Mode / Cut
1.8432MHz to 1.999MHz	800 Max	Fund / AT
2.000MHz to 2.399MHz	550 Max	Fund / AT
2.400MHz to 2.999MHz	350 Max	Fund / AT
3.000MHz to 3.199MHz	250 Max	Fund / AT
3.200MHz to 3.499MHz	200 Max	Fund / AT
3.500MHz to 3.599MHz	150 Max	Fund / AT
3.600MHz to 3.999MHz	120 Max	Fund / AT
4.000MHz to 4.999MHz	100 Max	Fund / AT
5.000MHz to 5.999MHz	70 Max	Fund / AT
6.000MHz to 40.000MHz	40 Max	Fund / AT
24.000MHz to 75.000MHz	40 Max	3 rd OT / AT
75.001MHz to 200.000MHz	100 Max	5 th OT / AT

MECHANICAL DETAIL:




MARKING:

Line 1: MXX.XXX
XX.XXX = Frequency in MHz

Line 2: SYMCCL
S = Internal Code
YM = Date Code (Year/Month)
CC = Crystal Parameters Code
L = Denotes RoHS Compliant

PART NUMBER GUIDE:



* Please consult with MMD sales department for any other parameters or options.
** Not all Frequency Tolerance/Stability options available at this temperature range.

MMD Components, 30400 Esperanza, Rancho Santa Margarita, CA, 92688
Phone: (949) 709-5075, Fax: (949) 709-3536, www.mmdcomp.com
Sales@mmdcomp.com