

Features

- Single Positive Voltage Control: 0 to +3 Volts
- 40 dB Attenuation Range at 0.9 GHz
- ± 2 dB Linearity from BSL
- Low DC Power Consumption
- Lead-Free SOIC-8 Plastic Package
- 100% Matte Tin Plating over Copper
- Halogen-Free "Green" Mold Compound
- 260°C Reflow Compatible
- RoHS* Compliant Version of AT-113

Description

M/A-COM's MAAV-008022 is a GaAs MMIC voltage variable absorptive attenuator in a lead-free low-cost SOIC 8-lead surface mount plastic package. The MAAV-008022 is ideally suited for use where linear attenuation fine tuning and very low power consumption are required.

Typical applications include radio, cellular, GPS equipment and automatic gain/level control circuits.


The MAAV-008022 is fabricated with a monolithic GaAs MMIC using a mature 1-micron process. The process features full chip passivation for increased performance and reliability.

Ordering Information ¹

| Part Number | Package |
|--------------------|-----------------|
| MAAV-008022-000000 | Bulk Packaging |
| MAAV-008022-TR3000 | 3000 piece reel |

1. Reference Application Note M513 for reel size information.

Functional Schematic ^{2,3,4,5}



2. $V_{CC} = +3$ VDC @ 50 μ A maximum.
3. $V_C = 0$ VDC to +3 VDC @ 50 μ A maximum.
4. External DC blocking capacitors are required on all RF ports.
5. 39 pF used for data measurements.

Pin Configuration

| Pin No. | Function | Pin No. | Function |
|---------|----------|---------|----------|
| 1 | Ground | 5 | V_C |
| 2 | Ground | 6 | Ground |
| 3 | RF Port | 7 | RF Port |
| 4 | V_{CC} | 8 | Ground |

Absolute Maximum Ratings ⁶

| Parameter | Absolute Maximum |
|-------------------------|---|
| Input Power | +21 dBm |
| Supply Voltage V_{CC} | $-1 \text{ V} \leq V_{CC} \leq +8 \text{ V}$ |
| Control Voltage V_C | $-1 \text{ V} \leq V_C \leq V_{CC} + 0.5 \text{ V}$ |
| Operating Temperature | -40°C to $+85^\circ\text{C}$ |
| Storage Temperature | -65°C to $+150^\circ\text{C}$ |

6. Exceeding any one or combination of these limits may cause permanent damage to this device.

* Restrictions on Hazardous Substances, European Directive 2002/95/EC.

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 / Fax: 978.366.2266
 • **Europe** Tel: 44.1908.574.200 / Fax: 44.1908.574.300
 • **Asia/Pacific** Tel: 81.44.844.8296 / Fax: 81.44.844.8298
 Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

3 Volt Voltage Variable Absorptive Attenuator 40 dB, 0.5 - 2.0 GHz


Rev. V1

Electrical Specifications ⁷: $T_A = 25^\circ\text{C}$, $Z_0 = 50 \Omega$

| Parameter | Test Conditions | Units | Min | Typ | Max |
|---|--|---------------|------|-----|------|
| Insertion Loss | 0.5 - 1.0 GHz | dB | — | 2.7 | 3.0 |
| | 1.0 - 2.0 GHz | dB | — | 3.0 | 3.5 |
| Attenuation (Relative to Insertion Loss) | Frequency = 0.5 - 2.0 GHz | dB | 34 | 35 | — |
| | $V_c = 0.0 \text{ V}$ (max. atten.) | dB | 26 | 30 | — |
| | $V_c = 1.5 \text{ V}$ | dB | 12.5 | 15 | 17.5 |
| | $V_c = 2.7 \text{ V}$ | dB | — | .5 | 0.7 |
| Slope (at any point on the curve) | $V_c \text{ delta } 0.5 \text{ V} - 1.5 \text{ V}$ | dB/V | 10 | 15 | 23 |
| | $V_c \text{ delta } 1.5 \text{ V} - 2.7 \text{ V}$ | dB/V | 0 | 14 | 17 |
| VSWR | — | Ratio | — | 2:1 | — |
| Trise, Tfall | 10% to 90% RF, 90% to 10% RF | μS | — | 10 | — |
| Ton, Toff | 50% Control to 90% RF, 50% Control to 10% RF | μS | — | 12 | — |
| Transients | In-band | mV | — | 10 | — |

7. The RF ports must be blocked outside of the package from ground or any other voltage.


Lead-Free SOIC-8[†]




[†] Reference Application Note M538 for lead-free solder reflow recommendations.
 Meets JEDEC moisture sensitivity level 1 requirements.

Typical Performance Curves @ 25°C


Attenuation vs. Control Voltage




Attenuation vs. Frequency @ 0V




Insertion Loss vs. Frequency




Return Loss vs. Control Voltage, F = 900 MHz



1 dB Compression vs. Control Voltage




IP3 vs. Control Voltage



Typical Performance Curves @ 25°C

Attenuation vs. Temperature
Normalized @ 25°C, F = 900 MHz



Handling Procedures

Please observe the following precautions to avoid damage:

Static Sensitivity

Gallium Arsenide Integrated Circuits are sensitive to electrostatic discharge (ESD) and can be damaged by static electricity. Proper ESD control techniques should be used when handling these devices.