

# DDP 512Mbit SDRAM

*8M x 16bit x 4 Banks  
Synchronous DRAM  
LVTTL*

Revision 0.1

Sept. 2001

Samsung shall not offer for sale or sell either directly or through and third-party proxy, and DRAM memory products that include "Multi-Die Plastic DRAM" for use as components in general and scientific computers such as, by way of example, mainframes, servers, work stations or desk top computers for the first three years of five year term of this license. Nothing herein limits the rights of Samsung to use Multi-Die Plastic DRAM in other products or other applications under paragrangh such as mobile, telecom or non-computer application(which include by way of example laptop or notebook computers, cell phones, televisions or visual monitors)  
Violation may subject the customer to legal claims and also excludes any warranty against infringement from Samsung."

\* Samsung Electronics reserves the right to change products or specification without notice.



Rev. 0.1 Sept. 2001

**Revision 0.0 (Mar., 2001)**

**Revision 0.1 (Sep., 2001)**

- Redefined IDD1 & IDD4 in DC Characteristics



Rev. 0.1 Sept. 2001

**8M x 16Bit x 4 Banks Synchronous DRAM****FEATURES**


- JEDEC standard 3.3V power supply
- LVTTL compatible with multiplexed address
- Four banks operation
- MRS cycle with address key programs
  - CAS latency (2 & 3)
  - Burst length (1, 2, 4, 8 & Full page)
  - Burst type (Sequential & Interleave)
- All inputs are sampled at the positive going edge of the system clock.
- Burst read single-bit write operation
- DQM for masking
- Auto & self refresh
- 64ms refresh period (8K Cycle)

**GENERAL DESCRIPTION**

The K4S511632C is 536,870,912 bits synchronous high data rate Dynamic RAM organized as 4 x 8,392,608words by 16bits, fabricated with SAMSUNG's high performance CMOS technology. Synchronous design allows precise cycle control with the use of system clock I/O transactions are possible on every clock cycle. Range of operating frequencies, programmable burst length and programmable latencies allow the same device to be useful for a variety of high bandwidth, high performance memory system applications.


**ORDERING INFORMATION**

Part No.	Max Freq.	Interface	Package
K4S511632C-KC/L7C	133MHz(CL=2)	LVTTL	54pin TSOP(II)
K4S511632C-KC/L75	133MHz(CL=3)		
K4S511632C-KC/L1H	100MHz(CL=2)		
K4S511632C-KC/L1L	100MHz(CL=3)		

**FUNCTIONAL BLOCK DIAGRAM**

\* Samsung Electronics reserves the right to change products or specification without notice.

## PIN CONFIGURATION (Top view)



## PIN FUNCTION DESCRIPTION

Pin	Name	Input Function
CLK	<i>System clock</i>	Active on the positive going edge to sample all inputs.
CS	<i>Chip select</i>	Disables or enables device operation by masking or enabling all inputs except CLK, CKE and DQM
CKE	<i>Clock enable</i>	Masks system clock to freeze operation from the next clock cycle. CKE should be enabled at least one cycle prior to new command. Disable input buffers for power down in standby.
A0 ~ A12	<i>Address</i>	Row/column addresses are multiplexed on the same pins. Row address : RA0 ~ RA12, Column address : CA0 ~ CA9
BA0 ~ BA1	<i>Bank select address</i>	Selects bank to be activated during row address latch time. Selects bank for read/write during column address latch time.
RAS	<i>Row address strobe</i>	Latches row addresses on the positive going edge of the CLK with <u>RAS</u> low. Enables row access & precharge.
CAS	<i>Column address strobe</i>	Latches column addresses on the positive going edge of the CLK with <u>CAS</u> low. Enables column access.
WE	<i>Write enable</i>	Enables write operation and <u>row precharge</u> . Latches data in starting from CAS, WE active.
L(U)DQM	<i>Data input/output mask</i>	Makes data output Hi-Z, tshz after the clock and masks the output. Blocks data input when L(U)DQM active.
DQ0 ~ 15	<i>Data input/output</i>	Data inputs/outputs are multiplexed on the same pins.
V <sub>DD</sub> /V <sub>SS</sub>	<i>Power supply/ground</i>	Power and ground for the input buffers and the core logic.
V <sub>DDQ</sub> /V <sub>SSQ</sub>	<i>Data output power/ground</i>	Isolated power supply and ground for the output buffers to provide improved noise immunity.
N.C/RFU	<i>No connection /reserved for future use</i>	This pin is recommended to be left No Connection on the device.

**ABSOLUTE MAXIMUM RATINGS**

Parameter	Symbol	Value	Unit
Voltage on any pin relative to Vss	V <sub>IN</sub> , V <sub>OUT</sub>	-1.0 ~ 4.6	V
Voltage on V <sub>DD</sub> supply relative to Vss	V <sub>DD</sub> , V <sub>DDQ</sub>	-1.0 ~ 4.6	V
Storage temperature	T <sub>TG</sub>	-55 ~ +150	°C
Power dissipation	P <sub>D</sub>	2	W
Short circuit current	I <sub>OS</sub>	50	mA

**Note :** Permanent device damage may occur if "ABSOLUTE MAXIMUM RATINGS" are exceeded.

Functional operation should be restricted to recommended operating condition.

Exposure to higher than recommended voltage for extended periods of time could affect device reliability.

**DC OPERATING CONDITIONS**

Recommended operating conditions (Voltage referenced to V<sub>SS</sub> = 0V, T<sub>A</sub> = 0 to 70°C)

Parameter	Symbol	Min	Typ	Max	Unit	Note
Supply voltage	V <sub>DD</sub> , V <sub>DDQ</sub>	3.0	3.3	3.6	V	
Input logic high voltage	V <sub>IH</sub>	2.0	3.0	V <sub>DD</sub> +0.3	V	1
Input logic low voltage	V <sub>IL</sub>	-0.3	0	0.8	V	2
Output logic high voltage	V <sub>OH</sub>	2.4	-	-	V	I <sub>OH</sub> = -2mA
Output logic low voltage	V <sub>OL</sub>	-	-	0.4	V	I <sub>OL</sub> = 2mA
Input leakage current	I <sub>LI</sub>	-10	-	10	uA	3

**Notes :** 1. V<sub>IH</sub> (max) = 5.6V AC. The overshoot voltage duration is ≤ 3ns.

2. V<sub>IL</sub> (min) = -2.0V AC. The undershoot voltage duration is ≤ 3ns.

3. Any input 0V ≤ V<sub>IN</sub> ≤ V<sub>DDQ</sub>.

Input leakage currents include Hi-Z output leakage for all bi-directional buffers with Tri-State outputs.

**CAPACITANCE** (V<sub>DD</sub> = 3.3V, T<sub>A</sub> = 23°C, f = 1MHz, V<sub>REF</sub> = 1.4V ± 200 mV)

Pin	Symbol	Min	Max	Unit	Note
Clock	C <sub>CLK</sub>	5.0	9.0	pF	
RAS, CAS, WE, DQM	C <sub>IN</sub>	5.0	10.0	pF	
Address, CS, CKE	C <sub>ADD</sub>	5.0	10.0	pF	
DQ <sub>0</sub> ~ DQ <sub>8</sub>	C <sub>OUT</sub>	4.0	6.5	pF	

**DC CHARACTERISTICS**

(Recommended operating condition unless otherwise noted, TA = 0 to 70°C)

Parameter	Symbol	Test Condition	Version				Unit	Note
			-7C	-75	-1H	-1L		
Operating current (One bank active)	Icc1	Burst length = 1 t <sub>RC</sub> ≥ t <sub>RC(min)</sub> I <sub>O</sub> = 0 mA	200	180	180	180	mA	1
Precharge standby current in power-down mode	Icc2P	C <sub>K</sub> E ≤ V <sub>I</sub> L(max), t <sub>CC</sub> = 10ns	4				mA	
	Icc2PS	C <sub>K</sub> E & C <sub>L</sub> K ≤ V <sub>I</sub> L(max), t <sub>CC</sub> = ∞	4					
Precharge standby current in non power-down mode	Icc2N	C <sub>K</sub> E ≥ V <sub>I</sub> H(min), C <sub>S</sub> ≥ V <sub>I</sub> H(min), t <sub>CC</sub> = 10ns Input signals are changed one time during 20ns	40				mA	
	Icc2NS	C <sub>K</sub> E ≥ V <sub>I</sub> H(min), C <sub>L</sub> K ≤ V <sub>I</sub> L(max), t <sub>CC</sub> = ∞ Input signals are stable	20					
Active Standby current in power-down mode	Icc3P	C <sub>K</sub> E ≤ V <sub>I</sub> L(max), t <sub>CC</sub> = 10ns	12				mA	
	Icc3PS	C <sub>K</sub> E & C <sub>L</sub> K ≤ V <sub>I</sub> L(max), t <sub>CC</sub> = ∞	12					
Active standby current in non power-down mode (One bank active)	Icc3N	C <sub>K</sub> E ≥ V <sub>I</sub> H(min), C <sub>S</sub> ≥ V <sub>I</sub> H(min), t <sub>CC</sub> = 10ns Input signals are changed one time during 20ns	60				mA	
	Icc3NS	C <sub>K</sub> E ≥ V <sub>I</sub> H(min), C <sub>L</sub> K ≤ V <sub>I</sub> L(max), t <sub>CC</sub> = ∞ Input signals are stable	50				mA	
Operating current (Burst mode)	Icc4	I <sub>O</sub> = 0 mA Page burst 4banks activated. t <sub>CCD</sub> = 2CLKs	220	220	240	240	mA	1
Refresh current	Icc5	t <sub>RC</sub> ≥ t <sub>RC(min)</sub>	440	400	380	380	mA	2
Self refresh current	Icc6	C <sub>K</sub> E ≤ 0.2V	C	6				mA
			L	3				mA

**Notes :** 1. Measured with outputs open.

2. Refresh period is 64ms.


3. K4S511632C-KC\*\*

4. K4S511632C-KL\*\*


5. Unless otherwise noticed, input swing level is CMOS(V<sub>I</sub>H/V<sub>I</sub>L=V<sub>D</sub>DA/V<sub>SSQ</sub>).

AC OPERATING TEST CONDITIONS ( $V_{DD} = 3.3V \pm 0.3V$ ,  $T_A = 0$  to  $70^\circ C$ )

Parameter	Value	Unit
AC input levels ( $V_{ih}/V_{il}$ )	2.4/0.4	V
Input timing measurement reference level	1.4	V
Input rise and fall time	$t_{rf}/t_f = 1/1$	ns
Output timing measurement reference level	1.4	V
Output load condition	See Fig. 2	



(Fig. 1) DC output load circuit



(Fig. 2) AC output load circuit

## OPERATING AC PARAMETER

(AC operating conditions unless otherwise noted)

Parameter	Symbol	Version				Unit	Note
		-7C	-75	-1H	-1L		
Row active to row active delay	t <sub>RRD(min)</sub>	15	15	20	20	ns	1
RAS to CAS delay	t <sub>RCD(min)</sub>	15	20	20	20	ns	1
Row precharge time	t <sub>RP(min)</sub>	15	20	20	20	ns	1
Row active time	t <sub>RA</sub> (min)	45	45	50	50	ns	1
	t <sub>RA</sub> (max)	100				us	
Row cycle time	t <sub>RC(min)</sub>	60	65	70	70	ns	1
Last data in to row precharge	t <sub>RD(min)</sub>	2				CLK	2, 5
Last data in to Active delay	t <sub>DAL(min)</sub>	2 CLK + t <sub>RP</sub>				-	5
Last data in to new col. address delay	t <sub>CAL(min)</sub>	1				CLK	2
Last data in to burst stop	t <sub>BAL(min)</sub>	1				CLK	2
Col. address to col. address delay	t <sub>CCD(min)</sub>	1				CLK	3
Number of valid output data	CAS latency=3	2				ea	4
	CAS latency=2	1					

- Notes :**
1. The minimum number of clock cycles is determined by dividing the minimum time required with clock cycle time and then rounding off to the next higher integer.
  2. Minimum delay is required to complete write.
  3. All parts allow every cycle column address change.
  4. In case of row precharge interrupt, auto precharge and read burst stop.

**AC CHARACTERISTICS** (AC operating conditions unless otherwise noted)

Parameter		Symbol	-7C		-75		-1H		-1L		Unit	Note
			Min	Max	Min	Max	Min	Max	Min	Max		
CLK cycle time	CAS latency=3	tcc	7.5	1000	7.5	1000	10	1000	10	1000	ns	1
	CAS latency=2		7.5		10		10		12			
CLK to valid output delay	CAS latency=3	tSAC		5.4		5.4		6		6	ns	1,2
	CAS latency=2			5.4		6		6		7		
Output data hold time	CAS latency=3	tOH	3		3		3		3		ns	2
	CAS latency=2		3		3		3		3			
CLK high pulse width		tCH	2.5		2.5		3		3		ns	3
CLK low pulse width		tCL	2.5		2.5		3		3		ns	3
Input setup time		tSS	1.5		1.5		2		2		ns	3
Input hold time		tSH	0.8		0.8		1		1		ns	3
CLK to output in Low-Z		tSLZ	1		1		1		1		ns	2
CLK to output in Hi-Z	CAS latency=3	tSHZ		5.4		5.4		6		6	ns	
	CAS latency=2			5.4		6		6		7		

**Notes :** 1. Parameters depend on programmed CAS latency.

2. If clock rising time is longer than 1ns,  $(tr/2-0.5)$ ns should be added to the parameter.

3. Assumed input rise and fall time ( $tr & tf$ ) = 1ns.

If  $tr & tf$  is longer than 1ns, transient time compensation should be considered,

i.e.,  $[(tr + tf)/2-1]$ ns should be added to the parameter.

**DQ BUFFER OUTPUT DRIVE CHARACTERISTICS**

Parameter	Symbol	Condition	Min	Typ	Max	Unit	Notes
Output rise time	trh	Measure in linear region : 1.2V ~1.8V	1.37		4.37	Volts/ns	3
Output fall time	tfh	Measure in linear region : 1.2V ~1.8V	1.30		3.8	Volts/ns	3
Output rise time	trh	Measure in linear region : 1.2V ~1.8V	2.8	3.9	5.6	Volts/ns	1,2
Output fall time	tfh	Measure in linear region : 1.2V ~1.8V	2.0	2.9	5.0	Volts/ns	1,2

**Notes :** 1. Rise time specification based on  $0pF + 50$  Ohms to Vss, use these values to design to.

2. Fall time specification based on  $0pF + 50$  Ohms to VDD, use these values to design to.


3. Measured into  $50pF$  only, use these values to characterize to.

4. All measurements done with respect to Vss.


## IBIS SPECIFICATION

I<sub>OH</sub> Characteristics (Pull-up)

Voltage	100MHz/ 133MHz Min	100MHz/ 133MHz Max	66MHz Min
(V)	I (mA)	I (mA)	I (mA)
3.45		-2.4	
3.3		-27.3	
3.0	0.0	-74.1	-0.7
2.6	-21.1	-129.2	-7.5
2.4	-34.1	-153.3	-13.3
2.0	-58.7	-197.0	-27.5
1.8	-67.3	-226.2	-35.5
1.65	-73.0	-248.0	-41.1
1.5	-77.9	-269.7	-47.9
1.4	-80.8	-284.3	-52.4
1.0	-88.6	-344.5	-72.5
0.0	-93.0	-502.4	-93.0


I<sub>OL</sub> Characteristics (Pull-down)

Voltage	100MHz/ 133MHz Min	100MHz/ 133MHz Max	66MHz Min
(V)	I (mA)	I (mA)	I (mA)
0	0.0	0.0	0.0
0.4	27.5	70.2	17.7
0.65	41.8	107.5	26.9
0.85	51.6	133.8	33.3
1	58.0	151.2	37.6
1.4	70.7	187.7	46.6
1.5	72.9	194.4	48.0
1.65	75.4	202.5	49.5
1.8	77.0	208.6	50.7
1.95	77.6	212.0	51.5
3	80.3	219.6	54.2
3.45	81.4	222.6	54.9




**V<sub>DD</sub> Clamp @ CLK, CKE, CS, DQM & DQ**

V <sub>DD</sub> (V)	I (mA)
0.0	0.0
0.2	0.0
0.4	0.0
0.6	0.0
0.7	0.0
0.8	0.0
0.9	0.0
1.0	0.23
1.2	1.34
1.4	3.02
1.6	5.06
1.8	7.35
2.0	9.83
2.2	12.48
2.4	15.30
2.6	18.31

**V<sub>SS</sub> Clamp @ CLK, CKE, CS, DQM & DQ**

V <sub>SS</sub> (V)	I (mA)
-2.6	-57.23
-2.4	-45.77
-2.2	-38.26
-2.0	-31.22
-1.8	-24.58
-1.6	-18.37
-1.4	-12.56
-1.2	-7.57
-1.0	-3.37
-0.9	-1.75
-0.8	-0.58
-0.7	-0.05
-0.6	0.0
-0.4	0.0
-0.2	0.0
0.0	0.0



## SIMPLIFIED TRUTH TABLE

Command			CKEn-1	CKEn	<u>CS</u>	<u>RAS</u>	<u>CAS</u>	<u>WE</u>	DQM	BA0,1	A10/AP	A11,A12, A9 ~ A0	Note			
Register	Mode register set		H	X	L	L	L	L	X	OP code			1,2			
Refresh	Auto refresh			H	H	L	L	L	H	X	X					
	Self refresh	Entry			L						X					
		Exit		L	H	L	H	H	H	X	X					
Bank active & row addr.			H	X	L	L	H	H	X	V	Row address					
Read & column address	Auto precharge disable			H	X	L	H	L	H	X	V	L	Column address (A0 ~ A9)			
	Auto precharge enable											H				
Write & column address	Auto precharge disable			H	X	L	H	L	L	X	V	L	Column address (A0 ~ A9)			
	Auto precharge enable											H				
Burst Stop			H	X	L	H	H	L	X	X			6			
Precharge	Bank selection			H	X	L	L	H	L	X	V	L	X			
	All banks											X				
Clock suspend or active power down	Entry	H	L	H	X	X	X	X	X	X						
					L	V	V	V		X						
Precharge power down mode	Entry	H	L	H	X	X	X	X	X	X						
					L	H	H	H		X						
DQM			H	X				V	X				7			
No operation command			H	X	H	X	X	X	X	X						
					L	H	H	H								

(V=Valid, X=Don't care, H=Logic high, L=Logic low)

**Notes :** 1. OP Code : Operand code

A0 ~ A12 &amp; BA0 ~ BA1 : Program keys. (@ MRS)

2. MRS can be issued only at all banks precharge state.

A new command can be issued after 2 CLK cycles of MRS.

3. Auto refresh functions are as same as CBR refresh of DRAM.

The automatical precharge without row precharge command is meant by "Auto".

Auto/self refresh can be issued only at all banks precharge state.

4. BA0 ~ BA1 : Bank select addresses.

If both BA0 and BA1 are "Low" at read, write, row active and precharge, bank A is selected.

If both BA0 is "High" and BA1 is "Low" at read, write, row active and precharge, bank B is selected.

If both BA0 is "Low" and BA1 is "High" at read, write, row active and precharge, bank C is selected.

If both BA0 and BA1 are "High" at read, write, row active and precharge, bank D is selected.

If A10/AP is "High" at row precharge, BA0 and BA1 is ignored and all banks are selected.

5. During burst read or write with auto precharge, new read/write command can not be issued.

Another bank read/write command can be issued after the end of burst.

New row active of the associated bank can be issued at tRP after the end of burst.

6. Burst stop command is valid at every burst length.

7. DQM sampled at positive going edge of a CLK and masks the data-in at the very CLK (Write DQM latency is 0), but makes Hi-Z state the data-out of 2 CLK cycles after. (Read DQM latency is 2)